



SEMICONDUCTOR

GPRC

## EGP30A THRU EGP30M

SUPER FAST RECTIFIER  
Reverse Voltage: 50 to 400 Volts  
Forward Current: 3.0 Amperes


SILICON  
RECTIFIER

## FEATURES

- GPRC( Glass Passivated Rectifier Chip) inside
- Glass passivated cavity-free junction
- Low forward voltage drop, High current capability
- High surge current capability
- Super fast recovery time
- Plastic package has Underwriters Laboratory Flammability
- Classification 94V-0

## MECHANICAL DATA

- Case: JEDEC DO-201AD molded plastic body
- Terminals: Plated axial leads, solderable per MIL-STD-750, method 2026
- Polarity: Color band denotes cathode end
- Mounting Position: Any
- Weight: 0.042ounce, 1.18 grams



Dimensions in inches and (millimeters)

## MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

(Rating at 25 °C ambient temperature unless otherwise specified ,Single phase ,half wave ,60Hz, resistive or inductive load. For capacitive load, derate current by 20%.)

	Symbols	EGP 30A	EGP 30B	EGP 30D	EGP 30F	EGP 30G	EGP 30J	EGP 30K	EGP 30M	Units	
Maximum Recurrent Peak Reverse Voltage	VRRM	50	100	200	300	400	600	800	1000	Volts	
Maximum RMS Voltage	VRMS	35	70	140	210	280	420	480	700	Volts	
Maximum DC Blocking Voltage	VDC	50	100	200	300	400	600	800	1000	Volts	
Maximum Average Forward Rectified Current 0.375"(9.5mm)lead Length at Ta=55 C	I(AV)	3.0								Amp	
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	IFSM	115.0					105.0				Amps
Maximum Instantaneous Forward Voltage at 1.0 A	VF	1.0			1.25		1.7			Volts	
Maximum DC Reverse Current At Rated DC Blocking Voltage	Ta=25°C	5.0								µA	
	Ta=100°C	100									
Maximum Reverse Recovery Time(Note 1)	Trr	50					75				ns
Typical Junction Capacitance(Note 2)	Cj	75								PF	
Operating Junction and Storage Temperature Range	Tj	-65 to +125								°C	
	TSTG	-65 to +150									

Note: 1. Test conditions: IF=0.5A, IR=1.0A, IRR=0.25A.

2. Measured at 1MHz and applied reverse voltage of 4.0 Volts.

# RATINGS AND CHARACTERISTIC CURVES EGP30A THRU EGP30M

FIG.1-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC




FIG.2-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.6-TYPICAL JUNCTION CAPACITANCE

