

Radiation	Type	Technology	Case
Infrared	DDH	AlGaAs/AlGaAs	5 mm plastic lens

		Description
		High-power, high-speed LED, double heterostructure with removed substrate, housing without standoff leads  Note: Special packages with standoff available on request
Applications		Optical communications, safety equipment, automation

### Maximum Ratings

$T_{amb} = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Test conditions	Symbol	Value	Unit
Forward current (DC)		$I_F$	150	mA
Peak forward current	( $t_P \leq 50 \mu\text{s}$ , $t_P/T = 1/2$ )	$I_{FM}$	200	mA
Reverse voltage	$I_R = 10 \mu\text{A}$	$V_R$	5	V
Power dissipation		$P_D$	280	mW
Operating temperature range		$T_{amb}$	-40 to +100	°C
Storage temperature range		$T_{stg}$	-40 to +100	°C
Junction temperature		$T_J$	100	°C

### Optical and Electrical Characteristics

$T_{amb} = 25^\circ\text{C}$ , unless otherwise specified

Parameter	Test conditions	Symbol	Min	Typ	Max	Unit
Forward voltage	$I_F = 100 \text{ mA}$	$V_F$		1,6	2,0	V
Radiant power	$I_F = 100 \text{ mA}$	$\Phi_e$	30	45		mW
Radiant intensity	$I_F = 100 \text{ mA}$	$I_e$	60	90		mW/sr
Peak wavelength	$I_F = 100 \text{ mA}$	$\lambda_p$	865	880	895	nm
Spectral bandwidth at 50%	$I_F = 100 \text{ mA}$	$\Delta\lambda_{0.5}$		50		nm
Viewing angle	$I_F = 100 \text{ mA}$	$\varphi$		30		deg.
Switching time	$I_F = 100 \text{ mA}$	$t_r, t_f$		10/20		ns

Note: All measurements carried out on EPIGAP equipment

We reserve the right to make changes to improve technical design and may do so without further notice.

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer.

EPIGAP Optoelektronik GmbH, D-12555 Berlin, Köpenicker Str.325 b, Haus 201

Tel.: +49-30-6576 2543, Fax : +49-30-6576 2545

1 of 1