

## Metallized Polyester Film Capacitor

Type: **ECQUG[Class X1]**

In accordance with UL/CSA and European safety regulation class X1



### ■ Features

- Equipped with a safety mechanism
- Flame-retardant plastic case and non combustible resin
- RoHS directive compliant

### ■ Recommended Applications

- Interference suppressors

### ■ Explanation of Part Numbers



### ■ Applicable Standard

UL	UL 1414	Across-The-Line Capacitors Antenna-Coupling and Line-By-Pass Components
CSA	CSA C22.2 No.1	Across-the-line capacitors Antenna-Isolation and line-by-pass capacitors
SEMKO	IEC 60384-14 EN 132400	Class X1
DEMKO		
NEMKO		
FIMKO		
VDE		
SEV		

\*When applying this capacitor to European and American safety standards, please use type designation and rating such as ECQUG, 0.1  $\mu$ F.

\*Approval number (File No.) of safety regulations are subject to revision without notice. Ask factory for a copy of the latest file No..

\*European standards marking are VDE and FIMKO only. But, there are no problem using this capacitor in a device which will get approvals from certification bodies in Europe, SEMKO, DEMKO, NEMKO and SEV etc. except VDE and FIMKO.

### ■ Specifications

Category temp. range	-40 °C to +100 °C (85 °C max. on UL/CSA spec.)
Rated voltage	300 VAC (IEC60384-14), 250 VAC (UL, CSA)
Capacitance range	0.010 $\mu$ F to 1.0 $\mu$ F (E6)
Capacitance tolerance	$\pm$ 20 % (M)
Dissipation factor ( $\tan\delta$ )	$\tan\delta \leq 1.0$ % (20 °C, 1 kHz)
Withstand voltage	Between terminals : 575 VAC, 1768 VDC, 60 s Between terminals to enclosure : 2100 VAC, 60 s
Insulation resistance (IR)	C $\leq$ 0.33 $\mu$ F : IR $\geq$ 15000 M $\Omega$ (20 °C, 100 VDC, 60 s) C > 0.33 $\mu$ F : IR $\geq$ 5000 M $\Omega$ · $\mu$ F (20 °C, 100 VDC, 60 s) IR $\geq$ 2000 M $\Omega$ (20 °C, 500 VDC, 60 s)

\* Use of this capacitor is limited to AC voltage (50 Hz or 60 Hz sine wave).

### ■Dimensions in mm (not to scale)

STYLE	(a) side	(b) side	(c) side
1 (0.010 μF to 0.22 μF)	M .01 μF	ECQUG 300 V~X1 40/100/21 <small>Date Code</small>	GMF MKT FI 132400
2 (0.33 μF to 1.0 μF)	M 1.0 μF 300 V~	ECQUG 300 V~ 40/100/21 <small>X1</small> <small>Date Code</small>	GMF MKT FI 132400

### ■Rating & Dimensions

- Capacitance tolerance : ±20 %(M)

Part No.	Cap. (μF)	Dimensions (mm)						
		L	T	H	F	ød	P	Q
ECQU3A103MG	0.010	15.0	5.0	11.5	12.5	0.60	0±0.5	1.3
ECQU3A153MG	0.015	15.0	5.0	11.5	12.5	0.60	0±0.5	1.3
ECQU3A223MG	0.022	15.0	5.0	11.5	12.5	0.60	0±0.5	1.3
ECQU3A333MG	0.033	15.0	6.0	13.0	12.5	0.60	0±0.5	1.3
ECQU3A473MG	0.047	15.0	6.0	13.0	12.5	0.60	0±0.5	1.3
ECQU3A683MG	0.068	15.0	8.0	15.0	12.5	0.60	0±0.5	1.3
ECQU3A104MG	0.10	15.0	8.0	15.0	12.5	0.60	0±0.5	1.3
ECQU3A154MG	0.15	18.0	8.0	16.5	15.0	0.80	0±0.5	1.3
ECQU3A224MG	0.22	18.0	9.0	17.5	15.0	0.80	0±0.5	1.3
ECQU3A334MG	0.33	26.0	9.0	18.5	22.5	0.80	0±0.5	1.5
ECQU3A474MG	0.47	26.0	10.5	20.0	22.5	0.80	0±0.75	1.5
ECQU3A684MG	0.68	26.0	12.5	22.0	22.5	0.80	0±0.75	1.5
ECQU3A105MG	1.0	27.0	16.5	25.5	22.5	0.80	0±0.75	2.2

Cap.tol.code