



# Sparkle Power Inc.

A Leading Power Supply manufacturer  
Web site: [www.sparklepower.com](http://www.sparklepower.com)



## FSP300-60DL(48V) (For Pentium 4 and Athlon XP) 300 Watts -48V DC Input ATX12V Switching Power Supply

### Features

- Complied with ATX and ATX12V standard
- -48V DC Input, DC to DC Power Supply
- High efficiency and reliability
- Remote On/Off function
- Internal 8CM 12V DC fan included
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- +3.3V, +5V, and +12V Remote Sensing
- Complies with FCC Class B and CISPR 22 Class B
- Approved by: UL 60950, CSA C22.2 Level 3, TUV EN60950, NEMKO, CE

### Specification

- **Temperature Range:** Operating 0° C ~ +50° C on full load; storage & shipping -20° C ~ +80° C
- **Humidity:** 95% on operating and 95% on storage
- **Efficiency:** 65% at minimum measured at nominal AC main voltage and frequency with maximum load on all output
- **Rise Time:** Less than 20ms
- **Hold-up Time:** 5mS min with 48Vdc on full load.
- **Power Good Signal:** Power on delay time 100 ms to 500 ms, off delay 1ms minimum (TTL and CMOS compatible)
- **MTBF:** 100,000 hours on maximum load at +25° C degree
- **Dimension (WxHxL):** 150x86x140mm/6"x3.4"x6" inches

### Input Characteristics

**Input Range:** -36~-72V DC

**Input Line Current:** -36V DC /15A (RMS) Max.

### Output Characteristics

Output Voltage	Minimum Load	Maximum Load	Peak	Load Reg.	Line Reg.	Ripple & Noise
+3.3V	0.3A	28.0A		± 5%	± 1%	50mV P-P
+5V	0.3A	30.0A		± 5%	± 1%	50mV P-P
+12V	0.0A	15.0A	18A	± 5%	± 1%	120mV P-P
-5V	0.0A	0.3A		± 5%	± 2%	100mV P-P
-12V	0.0A	0.3A		± 5%	± 2%	120mV P-P
+5Vsb	0.0A	2.0 A		± 5%	± 1%	100mV P-P

\*+5V and +3.3V total output not exceed 180W

\*+3.3V, +5V, and +12V total output cannot exceed 280W

**Sparkle Power Inc.**  
**Main Office**  
 1000 Rock Avenue  
 San Jose, CA 95131  
 TEL: 408-519-8888  
 FAX: 408-519-9999  
 E-MAIL: [info@sparklepower.com](mailto:info@sparklepower.com)

**Sparkle Power Inc.**  
**Los Angeles Office**  
 17071 Green Drive  
 City of Industry, CA 91745  
 TEL: 626-839-7180  
 FAX: 626-839-3395

**Sparkle Power Inc.**  
**Colorado Office**  
 1316 Indian Paintbrush Lane  
 Longmont, CO 80503  
 TEL: 303-776-3281  
 FAX: 303-776-7645