



Surface Mount Power Voltage-Regulating Diodes



DO-215AA (SMBG)

FEATURES

- Low profile package
- Ideal for automated placement
- Glass passivated chip junction
- Low Zener impedance
- Low regulation factor
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Solder dip 260 °C, 40 s
- Component in accordance to RoHS 2002/95/EC and WEEE 2002/96/EC



RoHS
COMPLIANT

TYPICAL APPLICATIONS

For general purpose regulation and protection applications.

PRIMARY CHARACTERISTICS	
V_Z	9.1 V to 68 V
P_D	1.5 W
$I_R (V_Z > 12 V)$	5.0 μA
$T_J \text{ max.}$	150 °C

MECHANICAL DATA

Case: DO-215AA (SMBG)

Molding compound meets UL 94 V-0 flammability rating

Base P/N-E3 - RoHS compliant, commercial grade

Base P/NHE3 - RoHS compliant, high reliability/automotive grade (AEC Q101 qualified)

Terminals: Matte tin plated leads, solderable per J-STD-002 and JESD22-B102

E3 suffix meets JESD 201 class 1A whisker test, HE3 suffix meets JESD 201 class 2 whisker test

Polarity: Color band denotes cathode end

MAXIMUM RATINGS ($T_A = 25 \text{ }^\circ\text{C}$ unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Operating junction and storage temperature range	T_J, T_{STG}	- 55 to + 150	°C

ELECTRICAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)									
PART NUMBER ⁽¹⁾	DEVICE MARKING CODE	NOMINAL ZENER VOLTAGE V_Z AT I_{ZT} (V)	TEST CURRENT I_{ZT} (mA)	MAX. ZENER IMPEDANCE LEAKAGE CURRENT			MAX. REVERSE CURRENT I_R AT V_R		MAX. ZENER CURRENT I_{ZM} (mA) ⁽²⁾
				Z_{ZT} AT I_{ZT}	Z_{ZK} AT I_{ZK}		μA	(V)	
					(Ω)	(Ω)			
SMZG3788A,B	VK,L	9.1	41.2	4.0	1000	0.50	50	7.0	140
SMZG3789A,B	WA,B	10	37.5	5.0	1000	0.25	50	7.6	125
SMZG3790A,B	WC,D	11	34.1	6.0	650	0.25	10	8.4	115
SMZG3791A,B	WE,F	12	31.2	7.0	550	0.25	5.0	9.1	105
SMZG3792A,B	WG,H	13	28.8	7.5	550	0.25	5.0	9.9	98
SMZG3793A,B	WI,J	15	25.0	9.0	600	0.25	5.0	11.4	85
SMZG3794A,B	WK,L	16	23.4	10	600	0.25	5.0	12.2	80
SMZG3795A,B	XA,B	18	20.8	12	650	0.25	5.0	13.7	70
SMZG3796A,B	XC,D	20	18.7	14	650	0.25	5.0	15.2	62
SMZG3797A,B	XE,F	22	17.0	17.5	650	0.25	5.0	16.7	56
SMZG3798A,B	XG,H	24	15.6	19	700	0.25	5.0	18.2	51
SMZG3799A,B	XI,J	27	13.9	23	700	0.25	5.0	20.6	46
SMZG3800A,B	XK,L	30	12.5	26	750	0.25	5.0	22.8	41
SMZG3801A,B	YA,B	33	11.4	33	800	0.25	5.0	25.1	38
SMZG3802A,B	YC,D	36	10.4	38	850	0.25	5.0	27.4	35
SMZG3803A,B	YE,F	39	9.6	45	900	0.25	5.0	29.7	31
SMZG3804A,B	YG,H	43	8.7	53	950	0.25	5.0	32.7	28
SMZG3805A,B	YI,J	47	8.0	67	1000	0.25	5.0	35.8	26
SMZG3806A,B	YK,L	51	7.3	70	1100	0.25	5.0	38.8	24
SMZG3807A,B	ZA,B	56	6.7	86	1300	0.25	5.0	42.6	22
SMZG3808A,B	ZC,D	62	6.0	100	1500	0.25	5.0	47.1	20
SMZG3809A,B	ZE,F	68	5.5	120	1700	0.25	5.0	51.7	18

Notes:

- (1) Suffix "A" denotes $\pm 10\%$ and suffix "B" denotes $\pm 5\%$
- (2) Maximum steady state power dissipation is 1.5 W at $T_L = 75\text{ }^\circ\text{C}$ (Fig. 1)

ORDERING INFORMATION (Example)				
PREFERRED P/N	UNIT WEIGHT (g)	PREFERRED PACKAGE CODE	BASE QUANTITY	DELIVERY MODE
SMZG3788A-E3/52	0.096	52	750	7" diameter plastic tape and reel
SMZG3788A-E3/5B	0.096	5B	3200	13" diameter plastic tape and reel
SMZG3788AHE3/52 ⁽¹⁾	0.096	52	750	7" diameter plastic tape and reel
SMZG3788AHE3/5B ⁽¹⁾	0.096	5B	3200	13" diameter plastic tape and reel

Note:

- (1) Automotive grade AEC Q101 qualified

RATINGS AND CHARACTERISTICS CURVES

($T_A = 25\text{ }^\circ\text{C}$ unless otherwise noted)




Figure 1. Maximum Continuous Power Dissipation




Figure 3. Typical Zener Impedance




Figure 2. Typical Zener Impedance






Figure 4. Typical Temperature Coefficients

PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

DO-215AA (SMBG)



Mounting Pad Layout





Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.