


Standard Recovery Diodes (Stud Version), 300 A



DO-205AB (DO-9)

FEATURES

- Diffused glass passivated die
- Popular series for rough service
- Stud cathode and stud anode version
- High surge capability
- Very low V_F
- RoHS compliant
- Designed and qualified for industrial level


RoHS
COMPLIANT

PRODUCT SUMMARY

$I_{F(AV)}$	300 A
-------------	-------

TYPICAL APPLICATIONS

- Welders
- Power supplies
- Motor controls
- Battery charges
- General industrial current rectification

MAJOR RATINGS AND CHARACTERISTICS

PARAMETER	TEST CONDITIONS	VALUES	UNITS
$I_{F(AV)}$		300	A
	T_C	120	°C
I_{FSM}	50 Hz	5700	A
	60 Hz	5900	
I^2t	50 Hz	160	kA ² s
	60 Hz	148	
V_{RRM}	Range	400/600	V
T_J		- 40 to 180	°C

ELECTRICAL SPECIFICATIONS

VOLTAGE RATINGS

TYPE NUMBER	VOLTAGE CODE	V_{RRM} , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE V	V_{RSM} , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE V	I_{RRM} MAXIMUM AT $T_J = 180$ °C mA
300HF	40	400	500	10
	60	600	700	

FORWARD CONDUCTION					
PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNITS
Maximum average forward current at case temperature	$I_{F(AV)}$	180° conduction, half sine wave		300	A
				120	°C
Maximum peak, one cycle forward, non-repetitive surge current	I_{FSM}	t = 10 ms	No voltage reappplied	5700	A
		t = 8.3 ms		5900	
		t = 10 ms	100 % V_{RRM} reappplied	4800	
		t = 8.3 ms		5000	
Maximum I^2t for fusing	I^2t	t = 10 ms	No voltage reappplied	160	kA ² s
		t = 8.3 ms		148	
		t = 10 ms	100 % V_{RRM} reappplied	115	
		t = 8.3 ms		105	
Maximum $I^2\sqrt{t}$ for fusing	$I^2\sqrt{t}$	t = 0.1 to 10 ms, no voltage reappplied		1600	kA ² √s
Maximum value of threshold voltage	$V_{F(TO)}$	$T_J = 180\text{ °C}$		0.70	V
Maximum value of forward slope resistance	r_{f1}			0.40	mΩ
Maximum forward voltage drop	V_{FM}	$I_{pk} = 942\text{ A}, T_J = 25\text{ °C}$		1.14	V

THERMAL AND MECHANICAL SPECIFICATIONS					
PARAMETER	SYMBOL	TEST CONDITIONS		VALUES	UNITS
Maximum junction operating and storage temperature range	T_J, T_{Stg}			- 40 to 180	°C
Maximum thermal resistance, junction to case	R_{thJC}	DC operation		0.17	K/W
Maximum thermal resistance, case to heatsink	R_{thCS}	Mounting surface, smooth, flat and greased		0.08	
Maximum allowed mounting torque + 0 - 20 %		Not lubricated threads		37	N · m
		lubricated threads		28	
Approximate weight				250	g
Case style		See dimensions - link at the end of datasheet		DO-205AB (DO-9)	




Fig. 1 - Current Ratings Characteristics




Fig. 4 - Forward Power Loss Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 3 - Forward Power Loss Characteristics




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - Forward Voltage Drop Characteristics





Fig. 8 - Thermal Impedance Z_{thJC} Characteristic



ORDERING INFORMATION TABLE



- 1** - Current rating (300 = 300 A)
- 2** - Diode diffused
- 3** - Voltage ratings

40 = 400 V
60 = 600 V
- 4** -
 - P = 3/4 UNF
 - M = Metric M16 x 1.5
- 5** - Glass-metal seal
- 6** - L = Low V_F
- 7** -
 - 1 = Lead 150 mm
 - 2 = Lead 200 mm

Note: For "M" type contact factory

LINKS TO RELATED DOCUMENTS	
Dimensions	http://www.vishay.com/doc?95341



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.