



Recommended Panel Cut-Out

**Material:**

- Waterproof Rate: IP67
- LED Holder: Brass, Nickel plating
- LED: ø3MM, Blue
- Forward Voltage: Blue Typ. 3.5V/Max.4V
- Forward Current: Blue Max. 30mA
- Luminous Intensity: Blue Min.1,080/ Typ.2,000(Mcd)
- Operating Voltage: 4V DC
- Reverse Voltage: 5V DC
- Gasket: EPDM, Black
- Screw Nut: Brass, Nickel plating
- Operating Temperature: -40°C~+80°C
- For Panel Thickness 6.5MM Max.

QC Quality Control: Important Dimension to check  
Unit: MM±0.25MM

⊕ = Assmann logo



ITEM NO.	<b>A-LED8-1BAAS-MR7-1-R</b>
TITLE	Waterproof LED - Blue color, M8 size connector, ø3MM, Metal housing, Solder pins, IP67 unmated

**ASSMANN**  
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283  
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED  
©Copyright 2010 by Assmann Electronic Components  
All International Rights Reserved