



**Model 6744
BNC (F/F) Adapter Panel Mount, Hermetically Sealed 75 Ω**



6744 BNC (F/F) Panel Mount Hermetically Sealed-75 Ω



PANEL CUTOUT

Use 75 Ω Pomona BNC connectors with panel or box broadcast applications

Features

- Hermetically sealed.
- Panel mount design.
- Precision machined. Gold plated contacts. Dielectric is PTFE (not delrin).

Materials

- Machined brass with tarnish-resistant nickel plating.
- Female center contacts are gold plated heat-treated beryllium copper.
- Precision machined high quality brass (not die cast).
- High quality machined PTFE dielectric.

Ordering Information

Model: 6744 BNC (F/F) Panel Mount
Hermetically Sealed-75 Ω

Specifications

Nominal impedance	75 Ω
Frequency	0-3 GHz
VSWR	1.10 max. 0-1 GHz 1.35 max. 1-3 GHz
Center contact resistance	1.5 mΩ
Insulation resistance	5000 MΩ
Number of insertions	500
Ratings: Voltage: 500 Vrms Operating temperature: -85 °F to +131 °F (-65 °C to +155 °C) Max.	

USA: Sales: 800-490-2361 Technical Support: 800-241-2060 Fax: 888-403-3360

Europe: 31-(0) 40 2675 150 International: 425-446-5500

e-mail: technicalsupport@pomonatest.com

Where to Buy: www.pomonaelectronics.com

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies.