

FGA15N120AN

General Description



Employing NPT technology, Fairchild's AN series of IGBTs provides low conduction and switching losses. The AN series offers solutions for applications such as induction heating (IH), motor control, general purpose inverters and uninterruptible power supplies (UPS).

Features

- High speed switching
- Low saturation voltage : $V_{CE(sat)} = 2.4 \text{ V @ } I_C = 15\text{A}$
- High input impedance

Applications

Induction Heating, UPS, AC & DC motor controls and general purpose inverters.



Absolute Maximum Ratings $T_C = 25^\circ\text{C}$ unless otherwise noted

| Symbol | Description | FGA15N120AN | Units |
|-------------|---|-------------|------------------|
| V_{CES} | Collector-Emitter Voltage | 1200 | V |
| V_{GES} | Gate-Emitter Voltage | ± 20 | V |
| I_C | Collector Current @ $T_C = 25^\circ\text{C}$ | 24 | A |
| | Collector Current @ $T_C = 100^\circ\text{C}$ | 15 | A |
| $I_{CM(1)}$ | Pulsed Collector Current | 45 | A |
| P_D | Maximum Power Dissipation @ $T_C = 25^\circ\text{C}$ | 200 | W |
| | Maximum Power Dissipation @ $T_C = 100^\circ\text{C}$ | 80 | W |
| T_J | Operating Junction Temperature | -55 to +150 | $^\circ\text{C}$ |
| T_{stg} | Storage Temperature Range | -55 to +150 | $^\circ\text{C}$ |
| T_L | Maximum Lead Temp. for soldering Purposes, 1/8" from case for 5 seconds | 300 | $^\circ\text{C}$ |

Notes :

(1) Repetitive rating : Pulse width limited by max. junction temperature

Thermal Characteristics

| Symbol | Parameter | Typ. | Max. | Units |
|------------------------------|---|------|------|--------------------|
| $R_{\theta JC}(\text{IGBT})$ | Thermal Resistance, Junction-to-Case | -- | 0.63 | $^\circ\text{C/W}$ |
| $R_{\theta JA}$ | Thermal Resistance, Junction-to-Ambient | -- | 40 | $^\circ\text{C/W}$ |

Electrical Characteristics of the IGBT T_C = 25°C unless otherwise noted

| Symbol | Parameter | Test Conditions | Min. | Typ. | Max. | Units |
|-------------------------------------|--|---|------|------|-------|-------|
| Off Characteristics | | | | | | |
| BV _{CES} | Collector-Emitter Breakdown Voltage | V _{GE} = 0V, I _C = 3mA | 1200 | -- | -- | V |
| ΔBV _{CES} /ΔT _J | Temperature Coefficient of Breakdown Voltage | V _{GE} = 0V, I _C = 3mA | -- | 0.6 | -- | V/°C |
| I _{CES} | Collector Cut-Off Current | V _{CE} = V _{CES} , V _{GE} = 0V | -- | -- | 3 | mA |
| I _{GES} | G-E Leakage Current | V _{GE} = V _{GES} , V _{CE} = 0V | -- | -- | ± 100 | nA |

On Characteristics

| | | | | | | |
|----------------------|---|---|-----|-----|-----|---|
| V _{GE(th)} | G-E Threshold Voltage | I _C = 15mA, V _{CE} = V _{GE} | 3.5 | 5.5 | 7.5 | V |
| V _{CE(sat)} | Collector to Emitter Saturation Voltage | I _C = 15A, V _{GE} = 15V | -- | 2.4 | 3.2 | V |
| | | I _C = 15A, V _{GE} = 15V, T _C = 125°C | -- | 2.9 | -- | V |
| | | I _C = 24A, V _{GE} = 15V | -- | 3.0 | -- | V |

Dynamic Characteristics

| | | | | | | |
|------------------|------------------------------|---|----|------|----|----|
| C _{ies} | Input Capacitance | V _{CE} = 30V, V _{GE} = 0V, f = 1MHz | -- | 1150 | -- | pF |
| C _{oes} | Output Capacitance | | -- | 120 | -- | pF |
| C _{res} | Reverse Transfer Capacitance | | -- | 56 | -- | pF |

Switching Characteristics

| | | | | | | |
|---------------------|-----------------------------|--|------|------|-----|----|
| t _{d(on)} | Turn-On Delay Time | V _{CC} = 600 V, I _C = 15A, R _G = 20Ω, V _{GE} = 15V, Inductive Load, T _C = 25°C | -- | 90 | -- | ns |
| t _r | Rise Time | | -- | 70 | -- | ns |
| t _{d(off)} | Turn-Off Delay Time | | -- | 310 | -- | ns |
| t _f | Fall Time | | -- | 60 | 120 | ns |
| E _{on} | Turn-On Switching Loss | | -- | 3.27 | 4.9 | mJ |
| E _{off} | Turn-Off Switching Loss | | -- | 0.6 | 0.9 | mJ |
| E _{ts} | Total Switching Loss | -- | 3.68 | 5.8 | mJ | |
| t _{d(on)} | Turn-On Delay Time | V _{CC} = 600 V, I _C = 15A, R _G = 20Ω, V _{GE} = 15V, Inductive Load, T _C = 125°C | -- | 80 | -- | ns |
| t _r | Rise Time | | -- | 60 | -- | ns |
| t _{d(off)} | Turn-Off Delay Time | | -- | 310 | -- | ns |
| t _f | Fall Time | | -- | 50 | -- | ns |
| E _{on} | Turn-On Switching Loss | | -- | 3.41 | -- | mJ |
| E _{off} | Turn-Off Switching Loss | | -- | 0.84 | -- | mJ |
| E _{ts} | Total Switching Loss | -- | 4.25 | -- | mJ | |
| Q _g | Total Gate Charge | V _{CE} = 600 V, I _C = 15A, V _{GE} = 15V | -- | 120 | 180 | nC |
| Q _{ge} | Gate-Emitter Charge | | -- | 9 | 14 | nC |
| Q _{gc} | Gate-Collector Charge | | -- | 63 | 95 | nC |
| L _e | Internal Emitter Inductance | Measured 5mm from PKG | -- | 14 | -- | nH |




Fig 1. Typical Output Characteristics




Fig 2. Typical Saturation Voltage Characteristics




Fig 3. Saturation Voltage vs. Case Temperature at Variant Current Level




Fig 4. Load Current vs. Frequency




Fig 5. Saturation Voltage vs. V_{GE}




Fig 6. Saturation Voltage vs. V_{GE}




Fig 7. Capacitance Characteristics




Fig 8. Turn-On Characteristics vs. Gate Resistance




Fig 9. Turn-Off Characteristics vs. Gate Resistance




Fig 10. Switching Loss vs. Gate Resistance




Fig 11. Turn-On Characteristics vs. Collector Current




Fig 12. Turn-Off Characteristics vs. Collector Current




Fig 13. Switching Loss vs. Collector Current




Fig 14. Gate Charge Characteristics




Fig 15. SOA Characteristics




Fig 16. Turn-Off SOA





Fig 17. Transient Thermal Impedance of IGBT

Package Dimension

TO-3P (FS PKG CODE)



Dimensions in Millimeters

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

| | | | | |
|---|----------------------------------|----------------------------|----------------------------------|------------------------------|
| ACE ^x TM | FACT Quiet Series TM | LittleFET TM | Power247 TM | SuperSOT TM -6 |
| ActiveArray TM | FAST [®] | MICROCOUPLER TM | PowerTrench [®] | SuperSOT TM -8 |
| Bottomless TM | FAST ^r TM | MicroFET TM | QFET [®] | SyncFET TM |
| CoolFET TM | FRFET TM | MicroPak TM | QS TM | TinyLogic [®] |
| CROSSVOLT TM | GlobalOptoisolator TM | MICROWIRE TM | QT Optoelectronics TM | TINYOPTO TM |
| DOMET TM | GTO TM | MSX TM | Quiet Series TM | TruTranslation TM |
| EcoSPARK TM | HiSeC TM | MSXPro TM | RapidConfigure TM | UHC TM |
| E ² CMOS TM | I ² C TM | OCX TM | RapidConnect TM | UltraFET [®] |
| EnSigna TM | ImpliedDisconnect TM | OCXPro TM | SILENT SWITCHER [®] | VCX TM |
| FACT TM | ISOPLANAR TM | OPTOLOGIC [®] | SMART START TM | |
| Across the board. Around the world. TM | | OPTOPLANAR TM | SPM TM | |
| The Power Franchise TM | | PACMAN TM | Stealth TM | |
| Programmable Active Droop TM | | POP TM | SuperSOT TM -3 | |

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

| Datasheet Identification | Product Status | Definition |
|--------------------------|------------------------|---|
| Advance Information | Formative or In Design | This datasheet contains the design specifications for product development. Specifications may change in any manner without notice. |
| Preliminary | First Production | This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| No Identification Needed | Full Production | This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design. |
| Obsolete | Not In Production | This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only. |