

## CABLE-D 9SUB/S/S/200/KONFEK/S

Order No.: 2305583

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2305583>

Assembled, shielded circular cable, with D-SUB pin strip, 9-pos. from both sides, cable length: 2m

### Commercial data

EAN	4046356011921
Pack	1 pcs.
Customs tariff	85444290
Weight/Piece	0.1856 KG
Catalog page information	Page 271 (IF-2009)

### Product notes

WEEE/RoHS-compliant since:  
04/22/2008



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

### Technical data

#### General

Nominal voltage $U_N$	125 V AC/DC
Max. current carrying capacity per path	2 A
Max. conductor resistance	$\leq 0.09 \Omega/m$
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Number of positions	9
Number of positions, control side	9
Number of connectors, control side	1
Number of positions, module side	9
Number of connectors, modul side	1
Fixed cable length	2 m
Single wire, cross section	0.25 mm <sup>2</sup>
AWG	24
External diameter	7.5 mm
Shielding	yes
	Tinned copper-braided shield, approx. 85% covering
Insertion/withdrawal cycles	> 200
Width	32.1 mm
Length	40 mm

#### Certificates / Approvals



Certification

CUL, UL

**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2010 Phoenix Contact  
Technical modifications reserved;