


SS12 THRU S100

SURFACE MOUNT SCHOTTKY BARRIER RECTIFIER VOLTAGE - 20 to 100 Volts CURRENT - 1.0 Ampere

FEATURES

- Plastic package has Underwriters Laboratory Flammability Classification 94V-O
- For surface mounted applications
- Low profile package
- Built-in strain relief
- Metal to silicon rectifier majority carrier conduction
- Low power loss, High efficiency
- High current capability, low V_F
- High surge capacity
- For use in low voltage high frequency inverters, free wheeling, and polarity protection applications
- High temperature soldering:
260 $^{\circ}\text{C}$ /10 seconds at terminals

SMA/DO-214AC



Dimensions in inches and (millimeters)

MECHANICAL DATA

Case: JEDEC DO-214AC molded plastic
 Terminals: Solder plated, solderable per MIL-STD-750, Method 2026
 Polarity: Color band denotes cathode
 Standard packaging: 12mm tape (EIA-481)
 Weight: 0.002 ounce, 0.064 gram

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 $^{\circ}\text{C}$ ambient temperature unless otherwise specified.

Resistive or inductive load.

	SYMBOLS	SS12	SS13	SS14	SS15	SS16	SS18	SS19	S100	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	20	30	40	50	60	80	90	100	Volts
Maximum RMS Voltage	V_{RMS}	14	21	28	35	42	56	64	71	Volts
Maximum DC Blocking Voltage	V_{DC}	20	30	40	50	60	80	90	100	Volts
Maximum Average Forward Rectified Current at T_L (See Figure 1)	$I_{(AV)}$	1.0								Amps
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load(JEDEC method)	I_{FSM}	30.0								Amps
Maximum Instantaneous Forward Voltage at 1.0A (Note 1)	V_F	0.5		0.70		0.85			Volts	
Maximum DC Reverse Current $T_A=25^{\circ}\text{C}$ (Note 1) At Rated DC Blocking Voltage $T_A=100^{\circ}\text{C}$	I_R	0.5				20.0				mA
Maximum Thermal Resistance (Note 2)	$R_{\theta KJL}$ $R_{\theta KJA}$	28				88				$^{\circ}\text{C}/\text{W}$
Operating Junction Temperature Range	T_J	-50 to +125								$^{\circ}\text{C}$
Storage Temperature Range	T_{STG}	-50 to +150								$^{\circ}\text{C}$

NOTES:

1. Pulse Test with $PW=300 \mu\text{s}$ sec, 2% Duty Cycle.
2. Mounted on P.C.Board with 5.0mm^2 (.013mm thick) copper pad areas.

RATING AND CHARACTERISTIC CURVES

SS12 THRU S100




Fig. 1-FORWARD CURRENT DERATING CURVEE




Fig. 2-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




Fig. 3-MAXIMUM NON-REPETITIVE SURGE CURRENT




Fig. 4-TYPICAL JUNCTION CAPACITANCE