



### 1. CONFIGURATION & DIMENSIONS :



UNIT : mm (inch)

SIZE (VA)	L	W	H	A-6 6 PIN	B	WT. (gram)	OPTIONAL BRACKET *		
							NO.	MW	MD
10	48.50 (1.909)	36.51 (1.438)	41.28 (1.625)	10.16 (0.400)	33.02 (1.300)	356.15	10-BR	41.67 (1.641)	28.58 (1.125)

### 2. SCHEMATIC :



### 3. ELECTRICAL CHARACTERISTICS ( @ 25°C ) :

a. Primary Voltage	AC 115 V 60 Hz .
b. No Load Primary Current	Less Than 35mA .
c. Secondary Voltage (±5%)	Series AC 30.10 V . Parallel AC 15.05 V .
d. Secondary Load Current	Series 450mA . Parallel 900mA .
e. Full Load Primary Current	Less Than 135 mA .
f. Full Load Secondary Voltage (±5%)	Series 24.00V . Parallel 12.00V .
g. DC Resistance	
Pin 1-2	Primary = 71.80 Ohm .
Pin 3-4	Secondary = 3.61 Ohm .
Pin 5-6	= 3.96 Ohm .
h. Insulation Resistance	DC 500V 100Meg Ohm Of More .
i. Withstand Voltage (Hi-Pot)	AC 1500V 60Hz 1 Minutes .
j. Temperature Rise	Less Than 60 Deg C .
k. Core Size	EI-48 x 16.50 m/m .
l. Turns & Wire Gauge	
Primary Pin 1-2	1325 Turns Diameter 0.18 mm
Secondary-1 Pin 3-4	174 Turns Diameter 0.32 mm
Secondary-2 Pin 5-6	174 Turns Diameter 0.32 mm



**RoHS Compliant**

NOTE : Specifications subject to change without notice. Please check our website for latest information.

25.02.2008



**SUPERWORLD ELECTRONICS (S) PTE LTD**