2514096 CRIMSON SEMICONDUCTOR INC 99D 00361 D 7-41

LIGHT EMITTING DIODE TYPE SELECTION GUIDE

P/N	PACKAGE	DESCRIPTION	To at IF	CASE
C3RD C3GD	T-1 T-1	red diffused, 15mm leads green diffused, 15mm leads	0.8mc at 15mA 2.0mc at 20mA	1 1
C3AD	T-1	yellow diffused, 15mm leads	4.0mcd at 20mA	1
C5RDL	T- 1 3/4	red diffused, 25mm leads	3.0mcd at 15mA	2 2 2
C5GDL	T- 1 3/4	green diffused, 25mm leads	15.0mcd at 20mA	2
C5YDL	т- 1 3/4	yellow diffused, 25mm leads	8.0mcd at 20mA	2
C5ROS	T- 1 3/4	red diffused, 12mm leads	3.0mcd at 15mA	3
C5GDS	т- 1 3/4	green diffused, 12mm leads	15.0mcd at 20mA	3 3 3
C5YDS	T- 1 3/4	yellow diffused, 12mm leads	8.0mcd at 20mA	3
-C6RD	rectangular	red diffused, 15mm leads	0.4mcd at 15mA	4
C6GD	rectangular	green diffused, 15mm leads	1.5mcd at 20mA	4
C6YD	rectangular	yellow diffused, 15mm leads	2.0mcd at 20mA	4
C7RD	slot	red diffused, 13mm leads	0.6mcd at 15mA	5
C7GD	slot	green diffused, 13mm leads	2.5mcd at 20mA	5 5
C7ŸD	slot	yellow diffused, 13mm leads	2.0mcd at 20mA	5
C8RD	triangle	red diffused, 14mm leads	0.8mcd at 15mA	6
C8GD	triangle	green diffused, 14mm leads	2.lmcd at 20mA	6
C8XD	triangle	yellow diffused, 14mm leads	1.0mcd at 20mA	6

CASE DRAWINGS

