

HOME PHONE NETWORKING BANDPASS AND 10BASE-T FILTER MODULE



- For use with AMD's 79C978 Phoneline/Ethernet LAN Controller
- Supports HomePNA™ 1M8 Technology
- Includes protection circuitry, isolation and EMI filtering
- Contains 10BASE-T transmit/receive isolation and EMI filtering

Electrical Specifications @ 25°C — Operating Temperature 0°C to 70°C


PARAMETER	TEST CONDITION	MIN.	NOM.	MAX.	UNITS
HPN 1M8 Insertion Loss 6.0 MHz to 9.0 MHz	Input (7-8), Output (9-10) HP-8751A S21 100 Ω	1.2	1.7	2.2	dB
HPN 1M8 Attenuation 1.0 MHz 27 MHz	Input (7-8), Output (9-10) HP-8751A S21 100 Ω	70 55	80 60	— —	dB dB
HPN 1M8 Return Loss (6.0 MHz to 9.0 MHz)	Input (14-13), 100 Ω (1-2) HP-8751A S11 100 Ω	12	15	—	dB
10BASE-T Turns Ratio	Transmit (4-5):(13-12) Receive (1-2):(16-15)	1.38 0.98	1.41 1.0	1.44 1.02	— —
10BASE-T Inductance	Transmit (4-5) 10 KHz, 0.02 Vrms Receive (1-2) 10 KHz, 0.02 Vrms	140 140	180 180	— —	μH μH
10BASE-T Leakage Inductance	(1-2) with (16-15) shorted (4-5) with (13-12) shorted	— —	0.4 0.7	0.7 1.0	μH μH
10BASE-T Interwinding Capacitance	(1-2) short to (16-15) shorted (4-5) short to (13-12) shorted	— —	10 10	12 12	pF pF
10BASE-T DC Resistance	(1-2) = (3-5) (4-5) (16-15) = (13-12)	— — —	0.20 0.15 0.60	0.30 0.20 0.80	Ω Ω Ω
10BASE-T Return Loss	(13-12) to (4-5) 50 Ω (16-15) to (1-2) 100 Ω	18 18	23 23	— —	dB dB
Isolation	Pins (1-8) shorted to (9-16) shorted	2000	—	—	Vrms

NOTE: Filters are shipped in tubes unless tape and reel is specified. Please add the suffix "T" (i.e. B6006T) for tape and reel orders.

Mechanical


Schematic

B6006



Weight6.0 grams
Tape & Reel200/reel
Tube20/tube

Dimensions: Inches
 mm
 Unless otherwise specified, all tolerances are ± .010
 0.25



For More Information :

UNITED STATES (Worldwide)

12220 World Trade Drive
 San Diego, CA 92128
 U.S.A.
<http://www.pulseeng.com>
 TEL: 858 674 8100
 FAX: 858 674 8262

UNITED KINGDOM (Northern Europe)

1 & 2 Huxley Road
 The Surrey Research Park
 Guildford, Surrey GU2 5RE
 United Kingdom
 TEL: 44 1483 401700
 FAX: 44 1483 401701

FRANCE (Southern Europe)

Zone Industrielle
 F-39270
 Orgelet
 France
 TEL: 33 3 84 35 04 04
 FAX: 33 3 84 25 46 41

SINGAPORE (Southern Asia)

150 Kampong Ampat
 #07-01/02
 KA Centre
 Singapore 368324
 TEL: 65 287 8998
 FAX: 65 280 0080

TAIWAN, R.O.C. (Northern Asia)

3F-4, No. 81, Sec. 1
 HsinTai Wu Road
 Hsi-Chih, Taipei Hsien
 Taiwan, R.O.C.
 Tel: 886 2 2698 0228
 FAX: 886 2 2698 0948

DISTRIBUTOR

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

Printed on recycled paper. ©2000, Pulse Engineering, Inc.

PRELIMINARY B919.P (4/00)