


ADSL LINE TRANSFORMERS



- For use with Analog Devices AD20msp930 ADSL Chipset (Central Office)
- Excellent THD performance in a small footprint
- Designed to meet UL1950 and EN60950 supplementary insulation requirements for working voltages up to 250 Vrms

Electrical Specifications @ 25°C — Operating Temperature -40°C to 85°C

Part Number	Mounting	Application	Turns Ratio (10-7):(1-4) (± 2%)	OCL @ 10 KHz, 0.1 V (mH - MIN)		Leakage Inductance @ 100 KHz, 0.1 V (MAX) (10-7) with 2-3, 1-4, 8-9 shorted	Longitudinal Balance (10 KHz - 1.1 MHz)
				(1-4) with 2-3 shorted	(10-7) with 8-9 shorted		
B2162	SMT	CO	1:1.1	2.03	1.75	7.5 µH	50 dB MIN

Additional Specifications

Part Number	THD Typical (Linearity)	Load Resistance (Ω)	DC Resistance (Ω - MAX)		Isolation Voltage (Vrms)	Insertion Loss ¹ (dB @ 300 KHz)
			(1-4) with 2-3 shorted	(10-7) with 8-9 shorted		
B2162	-80 dB @ 30 KHz	100	1.30	1.50	1500	<0.5



¹ Frequency Response: ± 1.0 dB MAX, from 30 KHz to 1.1 MHz.

² Transformers are shipped in trays, unless Tape & Reel packaging is specified by adding the suffix "T" to this part number (B2162T)

Mechanical

Schematic

B2162



Weight6.2 grams

Tape & Reel150/reel

Tray60/tray

Dimensions: $\frac{\text{Inches}}{\text{mm}}$

Unless otherwise specified, all tolerances are ± $\frac{.010}{0.25}$

For More Information :

UNITED STATES (Worldwide)

12220 World Trade Drive
San Diego, CA 92128
Quick-Facts: 858 674 9672
<http://www.pulseeng.com>
TEL: 858 674 8100
FAX: 858 674 8262

UNITED KINGDOM (Northern Europe)

1 & 2 Huxley Road
The Surrey Research Park
Guildford, Surrey GU2 5RE
United Kingdom
TEL: 44 1483 401700
FAX: 44 1483 401701

FRANCE (Southern Europe)

Zone Industrielle
F-39270
Orgelet
France
TEL: 33 3 84 35 04 04
FAX: 33 3 84 25 46 41

SINGAPORE (Southern Asia)

150 Kampong Ampat
#07-01/02
KA Centre
Singapore 368324
TEL: 65 287 8998
FAX: 65 280 0080

TAIWAN, R.O.C. (Northern Asia)

3F-4, No. 81, Sec. 1
HsinTai Wu Road
Hsi-Chih, Taipei Hsien
Taiwan, R.O.C.
Tel: 886 2 2698 0228
FAX: 886 2 2698 0948

DISTRIBUTOR

Performance warranty of products offered on this data sheet is limited to the parameters specified. Data is subject to change without notice. Other brand and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

Printed on recycled paper. ©2000, Pulse Engineering, Inc.

PRELIMINARY B957.P (2/00)