

moulded single phase bridges

ponts monophasés montés 940

Types	V _{RRM} (V)	V _{RMS} recom- mended max (V)	I _d on re- sistive load <i>sur charge résistive</i> (A)	Use <i>Fonction</i>	Max Fwd Voltage (a) T _a = 25 °C		I _{dsm} / I _{fsm} (A)	I _R per diode @ V _R		Case
					V _F (V)	I _o (A)		25 °C (μA)	125 °C (mA)	

moulded bridges « 940 »

ponts moulés

60 A T_{case} = 90 °C

BY 60 940	50	35	60		1.2	30	600	100	1	
BA 60 940	100	70	60		1.2	30	600	100	1	
BB 60 940	200	140	60		1.2	30	600	100	1	
BD 60 940	400	280	60		1.2	30	600	100	1	
BF 60 940	600	420	60		1.2	30	600	100	1	
BH 60 940	800	560	60		1.2	30	600	100	1	
BJ 60 940	1000	700	60		1.2	30	600	100	1	
BL 60 940	1200	800	60		1.2	30	600	100	1	

Bortier 940

three phases bridges 940

ponts triphasés 940

90 A T_{case} = 90 °C

GY 60 940	50	35	90		1.2	30	600	100	1	
GA 60 940	100	70	90		1.2	30	600	100	1	
GB 60 940	200	140	90		1.2	30	600	100	1	
GD 60 940	400	280	90		1.2	30	600	100	1	
GF 60 940	600	420	90		1.2	30	600	100	1	
GH 60 940	800	560	90		1.2	30	600	100	1	
GJ 60 940	1000	700	90		1.2	30	600	100	1	
GL 60 940	1200	800	90		1.2	30	600	100	1	

Bortier 940

