



CHENMKO ENTERPRISE CO.,LTD

SURFACE MOUNT

P-Channel Enhancement Mode Field Effect Transistor

VOLTAGE 20 Volts CURRENT 7.7 Ampere

CHM9424JPT

Lead free devices

APPLICATION

- * Servo motor control.
- * Power MOSFET gate drivers.
- * Other switching applications.


FEATURE

- * Small flat package. (SO-8)
- * High density cell design for extremely low R_{DS(ON)}.
- * Rugged and reliable.
- * High saturation current capability.


CONSTRUCTION

- * P-Channel Enhancement

CIRCUIT



SO-8



Dimensions in millimeters

SO-8

Absolute Maximum Ratings

T_A = 25°C unless otherwise noted

Symbol	Parameter	CHM9424JPT	Units
V _{DSS}	Drain-Source Voltage	-20	V
V _{GSS}	Gate-Source Voltage	±8	V
I _D	Maximum Drain Current - Continuous	-7.7	A
	- Pulsed (Note 3)	-30	
P _D	Maximum Power Dissipation	2500	mW
T _J	Operating Temperature Range	-55 to 150	°C
T _{STG}	Storage Temperature Range	-55 to 150	°C

Note : 1. Surface Mounted on FR4 Board , t <=10sec

2. Pulse Test , Pulse width <= 300us , Duty Cycle <= 2%

3. Repetitive Rating , Pulse width limited by maximum junction temperature

4. Guaranteed by design , not subject to production testing

Thermal characteristics

R _{θJA}	Thermal Resistance, Junction-to-Ambient (Note 1)	50	°C/W
------------------	--	----	------

2008-04

ELECTRICAL CHARACTERISTIC (CHM9424JPT)

Electrical Characteristics $T_A = 25^\circ\text{C}$ unless otherwise noted

Symbol	Parameter	Conditions	Min	Typ	Max	Units
--------	-----------	------------	-----	-----	-----	-------

OFF CHARACTERISTICS

BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}} = 0 \text{ V}$, $I_D = -250 \mu\text{A}$	-20			V
I_{DSS}	Zero Gate Voltage Drain Current	$V_{\text{DS}} = -24 \text{ V}$, $V_{\text{GS}} = 0 \text{ V}$			-1	μA
I_{GSSF}	Gate-Body Leakage	$V_{\text{GS}} = 8 \text{ V}$, $V_{\text{DS}} = 0 \text{ V}$			+100	nA
I_{GSSR}	Gate-Body Leakage	$V_{\text{GS}} = -8 \text{ V}$, $V_{\text{DS}} = 0 \text{ V}$			-100	nA

ON CHARACTERISTICS (Note 2)

$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{DS}} = V_{\text{GS}}$, $I_D = -250 \mu\text{A}$	-0.6		-1	V
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}} = -4.5 \text{ V}$, $I_D = -7.7 \text{ A}$		20	25	$\text{m}\Omega$
		$V_{\text{GS}} = -2.5 \text{ V}$, $I_D = -6.6 \text{ A}$		29	35	
g_{FS}	Forward Transconductance	$V_{\text{DS}} = -10 \text{ V}$, $I_D = -7.7$		23		S

Dynamic Characteristics

C_{iss}	Input Capacitance	$V_{\text{DS}} = -10 \text{ V}$, $V_{\text{GS}} = 0 \text{ V}$, $f = 1.0 \text{ MHz}$		2130		pF
C_{oss}	Output Capacitance			760		
C_{rss}	Reverse Transfer Capacitance			127		

SWITCHING CHARACTERISTICS (Note 4)

Q_g	Total Gate Charge	$V_{\text{DS}} = -6 \text{ V}$, $I_D = -7.7 \text{ A}$ $V_{\text{GS}} = -4.5 \text{ V}$		45	54	nC
Q_{gs}	Gate-Source Charge			6		
Q_{gd}	Gate-Drain Charge			14		
t_{on}	Turn-On Time	$V_{\text{DD}} = -6 \text{ V}$ $I_D = -1.0 \text{ A}$, $V_{\text{GS}} = -4.5 \text{ V}$ $R_{\text{GEN}} = 6 \Omega$		60	80	nS
t_r	Rise Time			90	130	
t_{off}	Turn-Off Time			310	400	
t_f	Fall Time			190	250	

DRAIN-SOURCE DIODE CHARACTERISTICS AND MAXIMUM RATINGS

I_s	Drain-Source Diode Forward Current	(Note 1)			-2.3	A
V_{SD}	Drain-Source Diode Forward Voltage	$I_s = -2.3 \text{ A}$, $V_{\text{GS}} = 0 \text{ V}$ (Note 2)			-1.2	V