OSCILENT Data S	heet		(C) telephone 949 252 0522 (C) BACK	
Corporation		Product Category: SMD Quartz Crystal		
Series Number	Package	Description	Last Modified	
265	7x5mm Chip Type	2 Pad Quartz Crystal	July 28 2008	

#### FEATURES

- 7x5mm Chip Type quartz crystal
- Low profile 2 pad
- Tight stability / High reliability
- Cost Efficient
- Tape and Reel

- RoHS / Lead Free compliant




# **OPERATING CONDITIONS / ELECTRICAL CHARACTERISTICS**

PARAMETERS		CHARACTERISTICS	UNITS
Frequency Range	fo	12.00 ~ 35.00	MHz
Frequency Tolerance	@ 25°C	±30	ppm
Frequency Stability	Ta = -20 +70°C	±50	ppm
Operating Temperature	TOPR	-20 ~ +70	°C
Storage Temperature	TSTG	-40 ~ +85	°C
Shunt Capacitance	Со	7.0 max.	pF
Load Capacitance	CL (Customer Specified)	18 ~ 30, Series	pF

## EQUIVALENT SERIES RESISTANCE / MODE OF OSCILLATION

FREQUENCY RANGE (MHz)	MODE	MAX ESR Ohm	
12.000 ~ 16.000	Fundamental	60	
16.001 ~ 35.000	Fundamental	40	

### PACKAGE DIMENSIONS (mm)



#### PART NUMBER GUIDE

Series Number	Frequency	Load Capacitance	Operating Temp ( °C )	Packaging**			
265	- 12.0M	- 20	- S	- TR			
Oscilent		Enter capacitance e.g20 for 20pF . Enter -SR for Series Resonance.	S = -20~+70	Blank* = Bulk TR = Tape/Reel			
NOTE: Deviations on all parameters available. Please consult Oscilent for details.							
DEFINITIONS: Click on the characteristic names above for definitions of that particular characteristic.							
*STANDARDS: "Blank" part number selections indicate standard variables for that particular characteristic.							
**PACKAGING: Click on the packaging name above for tape/reel specifications							
Oscilent Corporation - CALL 949.252.0522				Series No.:	265		

18195 East McDurmott Street . Building D . Irvine . CA 92614 . USA Fax: 949.252.0599 . E-Mail: Sales@Oscilent.com

Crystal Oscillators | Quartz Crystal | TCXO | VCXO | IF SAW Filter | RF SAW Filter | Ceramic Resonator Crystal Filter | Ceramic Filter | SAW Filter / SAW Devices | Site Map