



## Features

- ▶ **Temperature stability down to 5ppb**
- ▶ **Single 12V supply (15v or 18V optional)**
- ▶ **Compact package**
- ▶ **Standard European IEC CO-08 pin-out**
- ▶ **Custom options available**

## Standard Models

The table shows the most common models. In most cases selecting one of these models will ensure the best combination of price / performance and availability.

Freq	Specification	Ageing per day	Temperature stability	Part No
5.0MHz	HCD361/DPFN	$\pm 1 \times 10^{-9}$	$\pm 2 \times 10^{-8}$ -20+70°C	MS06942
5.0MHz	HCD361/ERFN	$\pm 5 \times 10^{-10}$	$\pm 1 \times 10^{-8}$ -20+70°C	MS06944
10.0MHz	HCD361/DPFN	$\pm 1 \times 10^{-9}$	$\pm 2 \times 10^{-8}$ -20+70°C	MS06941
10.0MHz	HCD361/ERFN	$\pm 5 \times 10^{-10}$	$\pm 1 \times 10^{-8}$ -20+70°C	MS06943

## Specifications

Parameters	Product	Option Codes
	HCD361	
<b>Frequency range:</b> 5.0 ~ 20.0MHz	■	
<b>Ageing per day (at despatch):</b> $< \pm 1 \times 10^{-9}$ $< \pm 5 \times 10^{-10}$ $< \pm 2 \times 10^{-10}$	<input type="checkbox"/> ■ <input type="checkbox"/>	D E F
<b>Frequency stability:</b> $< \pm 5 \times 10^{-8}$ per year $< \pm 1 \times 10^{-9}$ per 10% change in $V_{DD}$	■ ■	
<b>Short term stability:</b> $< \pm 1 \times 10^{-11}$ over 1 sec	■	
<b>Temperature stability:</b> $< \pm 2 \times 10^{-8}$ $< \pm 1 \times 10^{-8}$ $< \pm 5 \times 10^{-9}$	<input type="checkbox"/> ■ <input type="checkbox"/>	P R S
<b>Operating temperature range:</b> 0 to +50°C -10 to +60°C -20 to +70°C	<input type="checkbox"/> <input type="checkbox"/> ■	A C F
<b>Storage temperature range:</b> -40 to +90°C	■	
<b>Output waveform:</b> HCMOS / TTL compatible	■	
<b>Frequency adjustment:</b> $\pm 5 \times 10^{-7}$ (typ) over +0.5 to +7.0V (sufficient for 10 years ageing min) Stabilised +7.0V supply provided	■	
<b>Supply voltage (<math>V_{DD}</math>):</b> +12V ( $\pm 0.5V$ ) +15V ( $\pm 0.5V$ ) +18V ( $\pm 0.5V$ )	■ <input type="checkbox"/> <input type="checkbox"/>	N P R
<b>Power consumption:</b> 5.0W max at switch on 1.2W typ when stabilised at 25°C	■ ■	
<b>Warm up:</b> $< \pm 1 \times 10^{-8}$ after 10mins at +20°C	■	
<b>Phase noise (@ 10.0MHz):</b> $< -125$ dBc/Hz @ 10Hz $< -135$ dBc/Hz @ 100Hz $< -150$ dBc/Hz @ 1kHz $< -155$ dBc/Hz @ 10kHz $< -155$ dBc/Hz @ 50kHz	■ ■ ■ ■ ■	
<b>Harmonics:</b> $< -30$ dB wrt carrier	■	
<b>Shock:</b> IEC 68-2-27 Test Ea 50G for 11ms	■	
<b>Vibration:</b> IEC 68-2-06 Test Fc 10-55Hz, 1.5mm. 55-500Hz, 10G	■	

■ Standard. □ Optional - Please specify required code(s) when ordering

## Ordering Information

Part No, or product name + option codes + frequency  
 eg: **HCD361/DPFN 10.0MHz**  
**HCD361/ERFN 5.0MHz**

Option code X (eg HCD361/X) denotes a custom specification.