

Features

1. Effective in suppressing noise at high frequencies.
2. Suited for preventing the abnormal oscillation from high frequency amplifying circuits.
3. Excellent solder heat resistance for soldering.
4. High reliability in the circuits of high current.
5. Lead Free (RoHS Compliance)

Applications

1. Noise suppression in digital equipments.
2. Computers and peripheral devices, VCR and camera.
3. Noise suppression in automotive electronic equipment, car stereo, car engine controller.
4. Noise suppression for OA electronic instruments.

Ordering Information

SHB - 1 M 2012 - 102 J T
 (1) (2) (3) (4) (5) (6)

(1) Series

SHB : For Signal line

(2) Material & Design

S, B : For high speed
 M : For high impedance type
 T : For Low speed

(3) Dimension

First two digits : length (mm)
 Last two digits : width (mm)

(4) Impedance (at 100MHz)

First two digits are impedance values.
 Last digit is the number of zeros


(5) Termination

J : Nickel barrier

(6) Packaging

B : Bulk package
 T : Tape & Reel ($\Phi 178\text{mm}$ [7 inches])
 L : Tape & Reel ($\Phi 254\text{mm}$ [10 inches])

Shape and Dimensions



Unit : mm [inches]

Type	L	W	T	C
SHB-1□2012-	2.0±0.20 [.079±.008]	1.25±0.20 [.049±.008]	0.8±0.15 (.049±.008)	0.50±0.30 [.020±.012]


Electrical Parameters

Part No.	IZI at 100MHz(Ω)		DC Resistance (Ω) max.	Rated current (mA) max.
	typ.	min.		
SHB-1M2012-150□□	15	12	0.02	600
SHB-1M2012-260□□	26	20	0.02	600
SHB-1M2012-300□□	30	23	0.02	600
SHB-1M2012-320□□	32	24	0.03	600
SHB-1M2012-800□□	80	60	0.08	300
SHB-1M2012-121□□	120	90	0.10	300
SHB-1M2012-151□□	150	115	0.12	300
SHB-1M2012-221□□	220	165	0.12	300
SHB-1M2012-301□□	300	225	0.15	300
SHB-1M2012-451□□	450	338	0.25	300
SHB-1M2012-601□□	600	450	0.25	300
SHB-1M2012-102□□	1000	750	0.30	300
SHB-1M2012-202□□	2000 (at 70MHz)	1500	0.50	300
SHB-1M2012-252□□	2500 (at 50MHz)	1875	0.60	300
SHB-1S2012-5R0□□	5	3.5	0.05	300
SHB-1S2012-8R0□□	8	6	0.05	300
SHB-1S2012-400□□	40	30	0.15	250
SHB-1S2012-800□□	80	60	0.18	200
SHB-1S2012-121□□	120	90	0.20	300
SHB-1S2012-221□□	220	165	0.30	300
SHB-1S2012-251□□	250	190	0.50	300
SHB-1T2012-260□□	26	20	0.04	600
SHB-1T2012-400□□	40	30	0.05	600
SHB-1T2012-800□□	80	60	0.08	300
SHB-1T2012-121□□	120	90	0.08	300
SHB-1T2012-151□□	150	115	0.08	300
SHB-1T2012-221□□	220	170	0.12	200
SHB-1T2012-251□□	250	188	0.12	200
SHB-1T2012-301□□	300	225	0.15	200
SHB-1T2012-331□□	330	250	0.15	200
SHB-1T2012-401□□	400	300	0.15	200
SHB-1T2012-601□□	600	450	0.25	200
SHB-1T2012-102□□	1000 (at 60MHz)	750	0.30	200
SHB-1T2012-202□□	2000 (at 40MHz)	1500	0.50	200
SHB-1T2012-252□□	2500 (at 35MHz)	1875	0.60	200
SHB-1B2012-222□□	2200	1650	0.60	300
SHB-1B2012-272□□	2700	2025	0.70	300

※ Parts with other electrical characteristics available upon request.


※ Test equipment : HP4291 + HP16192A

Electrical Characteristic Curves




*All specifications are subject to change without notice.


SHB-1S2012-5R0J




SHB-1S2012-8R0J




SHB-1S2012-400J




SHB-1S2012-800J




SHB-1S2012-121J




SHB-1S2012-221J




SHB-1T2012-400J




SHB-1T2012-800J




SHB-1T2012-121J




SHB-1T2012-221J



SHB-1T2012-301J




SHB-1T2012-331J




*All specifications are subject to change without notice.


SHB-1T2012-601J




SHB-1T2012-102J




SHB-1T2012-202J




SHB-1T2012-252J



SHB-1B2012-222J



SHB-1B2012-272J



*All specifications are subject to change without notice.