



**NEC's 6-PIN DIP  
400 V BREAK DOWN VOLTAGE  
1-CH OPTICAL COUPLED MOS FET**

**PS7142-1A  
PS7142L-1A**

---

**FEATURES**

---

- **1 CHANNEL TYPE:**  
1 a Output
- **LOW LED OPERATING CURRENT:**  
 $I_F = 2\text{mA}$
- **DESIGNED FOR AC/DC SWITCHING LINE CHANGER**
- **SMALL PACKAGE:**  
6-Pin DIP
- **LOW OFFSET VOLTAGE**
- **PS7142L-1A:**  
Surface mount type
- **SAFETY STANDARDS:**  
UL approved: File No. E72422 (S)  
BSI approved: File No. 8245/8246  
CSA approved: File No. CA 101391

---

**DESCRIPTION**

---

NEC's PS7142-1A and PS7142L-1A are solid state relays containing GaAs LEDs on the light emitting side (input side) and MOS FETs on the output side.

They are suitable for analog signal control because of their low offset and high linearity.

The PS7142L-1A has a surface mount type lead.

---


**APPLICATION**

---


- **Exchange Equipment**
- **Measurement Equipment**
- **FA/OA Equipment**

PACKAGE DIMENSIONS (UNIT: mm)


PS7142-1A




TOP VIEW




- 1. LED Anode
- 2. LED Cathode
- 3. NC
- 4. MOS FET Drain
- 5. MOS FET Source
- 6. MOS FET Drain




PS7142L-1A



TOP VIEW



- 1. LED Anode
- 2. LED Cathode
- 3. NC
- 4. MOS FET Drain
- 5. MOS FET Source
- 6. MOS FET Drain



**ORDERING INFORMATION**

PART NUMBER	PACKAGE	PACKING STYLE	APPLICATION PART NUMBER *1
PS7142-1A	6-pin DIP	Magazine case 50 pcs	PS7142-1A
PS7142L-1A			PS7142L-1A
PS7142L-1A-E3		Embossed Tape 1000 pcs/reel	
PS7142L-1A-E4			


\*1 For the application of the Safety Standard, following part number should be used.

**ABSOLUTE MAXIMUM RATINGS** ( $T_A = 25^\circ\text{C}$ , unless otherwise Specified)

PARAMETER		SYMBOL	RATINGS	UNIT	
<b>Diode</b>	Forward Current (DC)	$I_F$	50	mA	
	Reverse Voltage	$V_R$	5.0	V	
	Power Dissipation	$P_D$	50	mW	
	Peak Forward Current *1	$I_{FP}$	1	A	
<b>MOS FET</b>	Break Down Voltage	$V_L$	400	V	
	Continuous Load Current *2	Connection A	$I_L$	200	mA
		Connection B		250	
		Connection C		400	
	Pulse Load Current *3 (AC/DC Connection)	$I_{LP}$	400	mA	
Power Dissipation	$P_D$	560	mW		
Isolation Voltage *4		BV	1 500	Vr.m.s.	
Total Power Dissipation		$P_T$	610	mW	
Operating Ambient Temperature		$T_A$	-40 to +85	$^\circ\text{C}$	
Storage Temperature		$T_{stg}$	-40 to +100	$^\circ\text{C}$	

\*1  $PW = 100 \mu\text{s}$ , Duty Cycle = 1 %

\*2 Conditions:  $I_F \geq 2 \text{ mA}$ . The following types of load connections are available.



\*3  $PW = 100 \text{ ms}$ , 1 shot

\*4 AC voltage for 1 minute at  $T_A = 25 \text{ }^\circ\text{C}$ , RH = 60 % between input and output



**RECOMMENDED OPERATING CONDITIONS** ( $T_A = 25^\circ\text{C}$ )

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT
LED Operating Current	$I_F$	2	10	20	mA
LED Off Voltage	$V_F$	0		0.5	V

**ELECTRICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$ )


PARAMETER	SYMBOL	CONDITIONS	MIN.	TYP.	MAX.	UNIT
<b>Diode</b>	Forward Voltage	$V_F$ $I_F = 10\text{ mA}$		1.2	1.4	V
	Reverse Current	$I_R$ $V_R = 5\text{ V}$			5.0	$\mu\text{A}$
<b>MOS FET</b>	Off-state Leakage Current	$I_{\text{Loff}}$ $V_D = 400\text{ V}$		0.03	1.0	$\mu\text{A}$
	Output Capacitance	$C_{\text{out}}$ $V_D = 0\text{ V}, f = 1\text{ MHz}$		225		pF
<b>Coupled</b>	LED On-state Current	$I_{\text{Fon}}$ $I_L = 200\text{ mA}$			2.0	mA
	On-state Resistance	$R_{\text{on1}}$ $I_F = 10\text{ mA}, I_L = 10\text{ mA}$		6.0	10	$\Omega$
		$R_{\text{on2}}$ $I_F = 10\text{ mA}, I_L = 200\text{ mA}, t \leq 10\text{ ms}$				
	Turn-on Time *1	$t_{\text{on}}$ $I_F = 10\text{ mA}, V_O = 5\text{ V}, R_L = 500\ \Omega,$		0.8	5.0	ms
	Turn-off Time *1	$t_{\text{off}}$ $PW \geq 10\text{ ms}$		0.02	0.2	
	Isolation Resistance	$R_{\text{I-O}}$ $V_{\text{I-O}} = 1.0\text{ kV}_{\text{DC}}$	$10^9$			$\Omega$
Isolation Capacitance	$C_{\text{I-O}}$ $V = 0\text{ V}, f = 1\text{ MHz}$		1.1		pF	

\*1 Test Circuit for Switching Time




**TYPICAL CHARACTERISTICS** ( $T_A = 25^\circ\text{C}$ , unless otherwise specified)


MAXIMUM FORWARD CURRENT vs. AMBIENT TEMPERATURE




MAXIMUM LOAD CURRENT vs. AMBIENT TEMPERATURE




FORWARD VOLTAGE vs. AMBIENT TEMPERATURE




OUTPUT CAPACITANCE vs. APPLIED VOLTAGE




OFF-STATE LEAKAGE CURRENT vs. APPLIED VOLTAGE




LORD CURRENT vs. LORD VOLTAGE




NORMALIZED ON-STATE RESISTANCE vs. AMBIENT TEMPERATURE




ON-STATE RESISTANCE DISTRIBUTION




TURN-ON TIME vs. FORWARD CURRENT




TURN-OFF TIME vs. FORWARD CURRENT




TURN-ON TIME DISTRIBUTION




TURN-OFF TIME DISTRIBUTION



NORMALIZED TURN-ON TIME vs. AMBIENT TEMPERATURE



NORMALIZED TURN-OFF TIME vs. AMBIENT TEMPERATURE




**Remark** The graphs indicate nominal characteristics.




TAPING SPECIFICATIONS (UNIT:mm)


Outline and Dimensions (Tape)



Tape Direction



Outline and Dimensions (Reel)




Packing: 1 000 pcs/reel

**RECOMMENDED SOLDERING CONDITIONS**

**(1) Infrared reflow soldering**

- Peak reflow temperature 260°C or below (package surface temperature)
- Time of peak reflow temperature 10 seconds or less
- Time of temperature higher than 220°C 60 seconds or less
- Time to preheat temperature from 120 to 180°C 120±30 s
- Number of reflows Three
- Flux Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt% is recommended.)

Recommended Temperature Profile of Infrared Reflow



**(2) Wave soldering**

- Temperature 260°C or below (molten solder temperature)
- Time 10 seconds or less
- Preheating conditions 120°C or below (package surface temperature)
- Number of times One
- Flux Rosin flux containing small amount of chlorine (The flux with a maximum chlorine content of 0.2 Wt% is recommended.)

**(3) Cautions**

- Fluxes  
Avoid removing the residual flux with freon-based and chlorine-based cleaning solvent.

Life Support Applications

These NEC products are not intended for use in life support devices, appliances, or systems where the malfunction of these products can reasonably be expected to result in personal injury. The customers of CEL using or selling these products for use in such applications do so at their own risk and agree to fully indemnify CEL for all damages resulting from such improper use or sale.