



9-Bit Parity Generator/Checker

The LS280 is a bipolar, NPN, sealed-junction, silicon integrated circuit. It is manufactured in low-power Schottky technology and is available in a wire-bonded, 14-pin plastic DIP or surface mount package.



Logic Diagram



Electrical Characteristics

VCC = 5.0 ±0.5 V, TA = -55 to +125°C (WA-LS)

VCC = 5.0 ±0.25 V, TA = 0 to 70°C (WP90352L2)

VCC = 5.0 ±0.5 V, TA = -40 to +85°C (WP91400L3)

| Parameter | Symbol | WA-LS | | WP | | Units |
|--|-------------------|---------------|---------------------|---------------|---------------------|----------------|
| | | Min | Max | Min | Max | |
| Output Voltage, VCC = 4.5 V (WA-LS), 4.75 V (WP) Low, IOL = 4.0 mA IOL = 8.0 mA High, IOH = -0.4 mA | VOL VOL VOH | — — 2.5 | 0.4 0.5 — | — — 2.7 | 0.4 0.5 — | V V V |
| Input Voltage, VCC = 4.5 V (WA-LS), 4.75 V (WP) Low High Clamp, IIN = -18.0 mA | VIL VIH VIK | — 2.0 — | 0.7 7.5 -1.5 | — 2.0 — | 0.8* 5.5 -1.5 | V V V |
| Input Current, VCC = 5.5 V (WA-LS), 5.25 V (WP) Low, VIL = 0.4 V High, VIH = 2.7 V @ VI max, VI = 7.0 V (WA-LS), 5.5 V (WP) | IIL IIH II | — — — | -0.4 20.0 0.1 | — — — | -0.4 20.0 0.1 | mA μA mA |
| Output Current, VCC = 5.5 V (WA-LS), 5.25 V (WP) Short-Circuit | Ios | -20.0 | -100.0 | -20.0 | -100.0 | mA |
| Supply Current, VCC = 5.5 V (WA-LS), 5.25 V (WP) | ICC | — | 27.0 | — | 27.0 | mA |

* WP91400L3: VIL = 0.7 V

Timing Characteristics

VCC = 5.0 V, TA = 25°C, CL = 15 pF

| Parameter | Symbol | WA-LS | | WP | | Units |
|--|--------|-------|------|-----|------|-------|
| | | Min | Max | Min | Max | |
| Propagation Delay Data to Output (Σ Even) | | | | | | |
| Low-to-High | tPLH | — | 50.0 | — | 50.0 | ns |
| High-to-Low | tPHL | — | 45.0 | — | 45.0 | ns |
| Data to Output (Σ Odd) | | | | | | |
| Low-to-High | tPLH | — | 35.0 | — | 35.0 | ns |
| High-to-Low | tPHL | — | 50.0 | — | 50.0 | ns |

Maximum Ratings

| | |
|---------------------------------|---|
| Power supply voltage (Vcc)..... | 7.0 V |
| Operating temperature (TA)..... | WA-LS: -55 to +125°C WP90352L2: 0 to 70°C WP91400L3: -40 to +85°C |
| Storage temperature (Tstg)..... | -65 to +150°C |

Maximum ratings are defined as the limiting conditions that the user can apply to the device under all variations of circuit and environmental conditions. If any rating is exceeded, permanent damage to the device may result.

Bonding or soldering of the external leads of this device can be performed safely at temperatures up to 300°C.