

# SPECIFICATION

Product : Thermoelectric module

Part Number : PE-241-10-13

1 . Scope

- 1—1 This specification is applied to Multicomp thermoelectric modules
- 1—2 Revision of these specifications is carried out after consent.

2 . Specification

2 - 1 Parameters

| Parameters           |             | Remarks |
|----------------------|-------------|---------|
| Internal resistance  | 6.8 Ω ± 10% | Note-1  |
| I <sub>max</sub> .   | 3.9 A       | Note-2  |
| V <sub>max</sub> .   | 29.9 V      | Note-3  |
|                      | Th=25°C     |         |
| Q <sub>max</sub> .   | 71.8 W      | Note-4  |
| ΔT <sub>max</sub> .  | 74°C        | Note-5  |
| solder melting point | 138 °C      | Note-6  |
| Maximum. compress.   | 1MPa        | Note-7  |

Note-1 Measured by AC 4-terminal method at 25°C.

Note-2 Maximum current at ΔT<sub>max</sub>.

Note-3 Maximum voltage at ΔT<sub>max</sub>.

Note-4 Maximum cooling capacity at I<sub>max</sub>.,V<sub>max</sub>. and ΔT = 0°C.

Note-5 Maximum temperature difference at I<sub>max</sub>.,V<sub>max</sub>. and Q = 0W.

( Maximum parameters are measured in a vacuum 1.3P )

Note-6 The solder melting point of thermoelectric module

Note-7 Recommended maximum compression (not destruction limit)



## 2 -2 Recommendations:

- maximum temperature for short time: 110 °C
- operation temperature up to 90°C for long lifetime;
- good reliability in ON-OFF mode
- recommended operation current not higher than 0.7 of Imax

## 2 - 3 Performance Graph

