

REVISIONS																			
LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED																
A	Add case outlines Y and Z. Table I, $I_{IN}$ maximum limit, change from 4 mA to 5 mA.	99-07-12	R. Monnin																

REV																			
SHEET																			
REV																			
SHEET																			
REV STATUS OF SHEETS				REV		A	A	A	A	A	A	A	A	A	A	A			
				SHEET		1	2	3	4	5	6	7	8	9	10	11	12		
PMIC N/A				PREPARED BY Gary Zahn						<b>DEFENSE SUPPLY CENTER COLUMBUS</b> <b>P. O. BOX 3990</b> <b>COLUMBUS, OHIO 43216-5000</b>									
<b>STANDARD MICROCIRCUIT DRAWING</b>  THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE  AMSC N/A				CHECKED BY Michael C. Jones															
				APPROVED BY Kendall A. Cottongim															
				DRAWING APPROVAL DATE 93-12-06															
				REVISION LEVEL  A															
								SIZE		CAGE CODE									
				<b>A</b>		<b>67268</b>		<b>5962-93093</b>											
				SHEET		1		OF		12									

DSCC FORM 2233

APR 97


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

5962-E-336-99

## 1. SCOPE.

1.1 Scope. This drawing documents five product assurance classes, class D (lowest reliability), class E, (exceptions), class G (lowest high reliability), class H (high reliability), and class K, (highest reliability) and a choice of case outlines and lead finishes are available and are reflected in the Part or Identifying Number (PIN). When available, a choice of radiation hardness assurance levels are reflected in the PIN.

1.2 PIN. The PIN shall be as shown in the following example:



1.2.1 Radiation hardness assurance (RHA) designator. Device classes H and K RHA marked devices shall meet the MIL-PRF-38534 specified RHA levels and shall be marked with the appropriate RHA designator. A dash (-) indicates a non-RHA device. Only, the RHA levels specified herein are available.

1.2.2 Device type(s). The device type(s) shall identify the circuit function as follows:

<u>Device type</u>	<u>Generic number</u>	<u>Circuit function</u>
01	MSA2812S/883, MGA2812S	DC-DC converter, 5 W, +12 V output

1.2.3 Device class designator. This device class designator shall be a single letter identifying the product assurance level as follows:

<u>Device class</u>	<u>Device performance documentation</u>
D, E, G, H, or K	Certification and qualification to MIL-PRF-38534

1.2.4 Case outline(s). The case outline(s) shall be as designated in MIL-STD-1835 and as follows:

<u>Outline letter</u>	<u>Descriptive designator</u>	<u>Terminals</u>	<u>Package style</u>
X	See figure 1	8	Dual-in-line
Y	See figure 1	20	Flat pack
Z	See figure 1	20	Flat pack with formed leads

1.2.5 Lead finish. The lead finish shall be as specified in MIL-PRF-38534.

## 1.3 Absolute maximum ratings. 1/

Input voltage range .....	-0.5 V dc to +50 V dc
Power dissipation ( $P_D$ ) .....	3.1 W
Output power .....	5.2 W
Lead soldering temperature (10 seconds) .....	+300° C
Storage temperature range .....	-65° C to +150° C

1/ Stresses above the absolute maximum rating may cause permanent damage to the device. Extended operation at the maximum levels may degrade performance and affect reliability.

<b>STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000</b>	<b>SIZE A</b>		<b>5962-93093</b>
		<b>REVISION LEVEL A</b>	<b>SHEET 2</b>

#### 1.4 Recommended operating conditions.

Input voltage range ..... +16 V dc to +40 V dc  
Case operating temperature range ( $T_C$ ) ..... -55° C to +125° C

## 2. APPLICABLE DOCUMENTS

2.1 Government specification, standards, and handbook. The following specification, standards, and handbook form a part of this drawing to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

### SPECIFICATION

#### DEPARTMENT OF DEFENSE

MIL-PRF-38534 - Hybrid Microcircuits, General Specification for.

### STANDARDS

#### DEPARTMENT OF DEFENSE

MIL-STD-883 - Test Methods and Procedures for Microelectronics.  
MIL-STD-973 - Configuration Management.  
MIL-STD-1835 - Microcircuit Case Outlines.

### HANDBOOK

#### DEPARTMENT OF DEFENSE

MIL-HDBK-780 - Standard Microcircuit Drawings.

(Unless otherwise indicated, copies of the specification, standards, and handbook are available from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

## 3. REQUIREMENTS

3.1 Item requirements. The individual item performance requirements for device classes D, E, G, H, and K shall be in accordance with MIL-PRF-38534. Compliance with MIL-PRF-38534 may include the performance of all tests herein or as designated in the device manufacturer's Quality Management (QM) plan or as designated for the applicable device class. Therefore, the tests and inspections herein may not be performed for the applicable device class (see MIL-PRF-38534). Furthermore, the manufacturers may take exceptions or use alternate methods to the tests and inspections herein and not perform them. However, the performance requirements as defined in MIL-PRF-38534 shall be met for the applicable device class.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-PRF-38534 and herein.

3.2.1 Case outline(s). The case outline(s) shall be in accordance with 1.2.4 herein and figure 1.

3.2.2 Terminal connections. The terminal connections shall be as specified on figure 2.

<b>STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000</b>	<b>SIZE A</b>		<b>5962-93093</b>
		<b>REVISION LEVEL A</b>	<b>SHEET 3</b>

3.3 Electrical performance characteristics. Unless otherwise specified herein, the electrical performance characteristics are as specified in table I and shall apply over the full specified operating temperature range.

3.4 Electrical test requirements. The electrical test requirements shall be the subgroups specified in table II. The electrical tests for each subgroup are defined in table I.

3.5 Marking of device(s). Marking of device(s) shall be in accordance with MIL-PRF-38534. The device shall be marked with the PIN listed in 1.2 herein. In addition, the manufacturer's vendor similar PIN may also be marked as listed in QML-38534.

3.6 Data. In addition to the general performance requirements of MIL-PRF-38534, the manufacturer of the device described herein shall maintain the electrical test data (variables format) from the initial quality conformance inspection group A lot sample, for each device type listed herein. Also, the data should include a summary of all parameters manually tested, and for those which, if any, are guaranteed. This data shall be maintained under document revision level control by the manufacturer and be made available to the preparing activity (DSCC-VA) upon request.

3.7 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to supply to this drawing. The certificate of compliance (original copy) submitted to DSCC-VA shall affirm that the manufacturer's product meets the performance requirements of MIL-PRF-38534 and herein.

3.8 Certificate of conformance. A certificate of conformance as required in MIL-PRF-38534 shall be provided with each lot of microcircuits delivered to this drawing.

#### 4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with MIL-PRF-38534 or as modified in the device manufacturer's Quality Management (QM) plan. The modification in the QM plan shall not affect the form, fit, or function as described herein.

4.2 Screening. Screening shall be in accordance with MIL-PRF-38534. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to either DSCC-VA or the acquiring activity upon request. Also, the test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1015 of MIL-STD-883.

(2)  $T_C$  as specified in accordance with table I of method 1015 of MIL-STD-883.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000	SIZE A		5962-93093
		REVISION LEVEL A	SHEET 4

TABLE I. Electrical performance characteristics.

Test	Symbol	Conditions -55°C ≤ T <sub>C</sub> ≤ +125°C V <sub>IN</sub> = 28V dc ±0.5 V unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Output voltage	V <sub>OUT</sub>	I <sub>OUT</sub> = 417 mA	1	01	11.88	12.12	V
			2,3		11.52	12.48	
Output current	I <sub>OUT</sub>	V <sub>IN</sub> = 16, 28, and 40 V dc	1,2,3	01	0.0	417	mA
Output ripple voltage <u>1/</u>	V <sub>RIP</sub>	I <sub>OUT</sub> = 417 mA, B.W. = 10 kHz to 2 MHz	1	01		200	mVp-p
			2,3			300	
Line regulation	V <sub>RLINE</sub>	I <sub>OUT</sub> = 417 mA, V <sub>IN</sub> = 16 V dc and 40 V dc	1,2,3	01		50	mV
Load regulation	V <sub>RLOAD</sub>	I <sub>OUT</sub> = 0 to 417 mA	1,2,3	01		50	mV
Input current	I <sub>IN</sub>	I <sub>OUT</sub> = 0, inhibit (pin 5) = 0	1,2,3	01		5	mA
		I <sub>OUT</sub> = 0, inhibit (pin 5) = open				42	
Input ripple current	I <sub>RIP</sub>	I <sub>OUT</sub> = 417 mA, B.W. = 10 kHz to 10 MHz	1	01		100	mAp-p
			2,3			150	
Efficiency	Eff	I <sub>OUT</sub> = 417 mA	1	01	70		W
			2,3		68		
Isolation	ISO	Input to output or any pin to case except pin 8, T <sub>C</sub> = +25°C	1	01	100		MΩ
Internal power dissipation, load fault	P <sub>D</sub>	Short circuit	1	01		1.9	W
			2,3			2.1	
Switching frequency	F <sub>S</sub>	I <sub>OUT</sub> = 417 mA	4	01	450	600	kHz
			5,6		400	660	
Output response to step transient load changes <u>2/</u>	V <sub>OLOAD</sub>	50 percent load to/from 100 percent load	4	01	-375	+375	mV pk
			5,6		-1100	+1100	
Recovery time, step transient load changes <u>2/ 3/</u>	T <sub>TLOAD</sub>	50 percent load to/from 100 percent load	4	01		500	μs
			5,6			3000	

See footnotes at end of table.

**STANDARD  
MICROCIRCUIT DRAWING  
DEFENSE SUPPLY CENTER COLUMBUS  
COLUMBUS, OHIO 43216-5000**

**SIZE  
A**

REVISION LEVEL  
A

**5962-93093**

SHEET  
**5**

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C ≤ T <sub>C</sub> ≤ +125°C V <sub>IN</sub> = 28V dc ±0.5V unless otherwise specified	Group A subgroups	Device type	Limits		Unit
					Min	Max	
Output response to transient step line changes <u>4/ 5/</u>	V <sub>O</sub> TLINE	Input step from 16 V dc to 40 V dc, I <sub>OUT</sub> = 417 mA	4,5,6	01		+0.8	V pk
		Input step from 40 V dc to 16 V dc, I <sub>OUT</sub> = 417 mA			-1		
Recovery time to transient step line changes <u>3/ 4/ 5/</u>	T <sub>T</sub> LINE	Input step from 16 V dc to 40 V dc, I <sub>OUT</sub> = 417 mA	4,5,6	01		1.3	ms
		Input step from 40 V dc to 16 V dc, I <sub>OUT</sub> = 417 mA				1.3	
Turn-on overshoot <u>4/</u>	V <sub>ton</sub> OS	V <sub>IN</sub> = 0 to 28 V dc, I <sub>OUT</sub> = 417 mA	4,5,6	01		500	mV pk
Turn-on delay <u>3/ 6/</u>	T <sub>onD</sub>	V <sub>IN</sub> = 0 to 28 V dc, I <sub>OUT</sub> = 417 mA	4,5,6	01		30	ms
Load fault recovery <u>3/ 4/</u>	T <sub>rLF</sub>	I <sub>OUT</sub> = 417 mA	4,5,6	01		30	ms
Capacitive load <u>4/ 7/</u>	C <sub>L</sub>	No effect on dc performance, T <sub>C</sub> = +25°C	4	01		500	μF

1/ Bandwidth guaranteed by design. Tested for 10 kHz to 2 MHz.

2/ Load step transition time is 10 microseconds minimum.

3/ Recovery time is measured from the initiation of the transient to where V<sub>OUT</sub> has returned to within ±1 percent of V<sub>OUT</sub> final value.

4/ Parameter shall be tested as part of design characterization and after design or process changes. Therefore, the parameter shall be guaranteed to the limits specified in table I.

5/ Input step transition time greater than 10 microseconds.

6/ Turn-on delay time measurement is for either a step application of power at the input or the removal of a ground signal from the inhibit pin (pin 5) while power is applied to the input.

7/ Capacitive load may be any value from 0 to the maximum limit without compromising dc performance.

**STANDARD  
MICROCIRCUIT DRAWING  
DEFENSE SUPPLY CENTER COLUMBUS  
COLUMBUS, OHIO 43216-5000**


**SIZE  
A**

**5962-93093**

**REVISION LEVEL  
A**

**SHEET  
6**

Case outline X.



Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A		6.86		0.270
b	1.79 DIA		0.070 DIA	
b1	0.64 DIA		0.025 DIA	
D/E		27.31		1.075
E1	20.19	20.45	0.795	0.805
e/S	3.23	3.48	0.127	0.137
e1	8.31	8.56	0.327	0.337
e2	13.39	13.64	0.527	0.537
e3	18.47	18.72	0.727	0.737
e4/S1	23.55	23.80	0.927	0.937
L		5.59		0.220
R	1.14	1.40	0.045	0.055


NOTES:

1. The U.S. government preferred system of measurement is the metric SI. This item was designed using inch-pound units of measurement. In case of problems involving conflicts between the metric and inch-pound units, the inch-pound units shall rule.
2. Pin numbers are for reference only.
3. Device weight: 15 grams maximum.

FIGURE 1. Case outline(s).

<b>STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000</b>	<b>SIZE A</b>		<b>5962-93093</b>
		<b>REVISION LEVEL A</b>	<b>SHEET 7</b>

Case outline Y.



Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A		6.36		0.250
b	0.30	0.56	0.012	0.022
c	0.20	0.41	0.008	0.016
D/E	27.81	28.07	1.095	1.105
e	2.54 BSC		0.100 BSC	
L	12.7 TYP		0.500 TYP	
Q	1.78	2.29	0.070	0.090
R		1.52		0.060
S1	2.29	2.79	0.090	0.110

NOTES:


1. The U.S. government preferred system of measurement is the metric SI. This case outline was designed using inch-pound units of measurement. In case of problems involving conflicts between the metric and inch-pound units, the inch-pound units shall rule.
2. Lead identification for reference only.
3. Case outline Y weight: 15 grams maximum.

FIGURE 1. Case outline(s) - Continued.

<b>STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000</b>	<b>SIZE A</b>		<b>5962-93093</b>
		<b>REVISION LEVEL A</b>	<b>SHEET 8</b>



Case outline Z.



Symbol	Millimeters		Inches	
	Min	Max	Min	Max
A		6.36		0.250
A1	0.13	0.51	0.005	0.020
b	0.30	0.56	0.012	0.022
c	0.20	0.41	0.008	0.016
D/E	27.81	28.07	1.095	1.105
e	2.54 BSC		0.100 BSC	
L	3.43 REF		0.135 REF	
L1	1.52	2.03	0.060	0.080
L2	1.14	1.65	0.045	0.065
R		1.52		0.060
S1	2.29	2.79	0.090	0.110

NOTES:

1. The U.S. government preferred system of measurement is the metric SI. This case outline was designed using inch-pound units of measurement. In case of problems involving conflicts between the metric and inch-pound units, the inch-pound units shall rule.
2. Lead identification for reference only.
3. Case outline Z weight: 15 grams maximum.

FIGURE 1. Case outline(s) - Continued.

<b>STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000</b>	<b>SIZE A</b>		<b>5962-93093</b>
		<b>REVISION LEVEL A</b>	<b>SHEET 9</b>

Device types	01	01
Case outlines	Y and Z	X
Terminal number	Terminal symbol	Terminal symbol
1	Inhibit	Output
2	Positive input	Output return
3	Positive input	No connection
4	No connection	No connection
5	Input common	Inhibit
6	Input common	Input
7	Case ground	Input return
8	Case ground	Case ground
9	No connection	
10	No connection	
11	Positive output	
12	Positive output	
13	Positive output	
14	Output common	
15	Output common	
16	Output common	
17	No connection	
18	No connection	
19	Case ground	
20	Case ground	

FIGURE 2. Terminal connections.

<b>STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000</b>	<b>SIZE A</b>		<b>5962-93093</b>
		<b>REVISION LEVEL A</b>	<b>SHEET 10</b>

DSCC FORM 2234  
APR 97

TABLE II. Electrical test requirements.

MIL-PRF-38534 test requirements	Subgroups (in accordance with MIL-PRF-38534, group A test table)
Interim electrical parameters	
Final electrical parameters	1*,2,3,4,5,6
Group A test requirements	1,2,3,4,5,6
Group C end-point electrical parameters	1
MIL-STD-883, group E end-point electrical parameters for RHA devices	Subgroups** (in accordance with method 5005, group A test table)

\* PDA applies to subgroup 1.

\*\* When applicable to this standard microcircuit drawing,  
the subgroups shall be defined.

4.3 Conformance and periodic inspections. Conformance inspection (CI) and periodic inspection (PI) shall be in accordance with MIL-PRF-38534 and as specified herein.

4.3.1 Group A inspection (CI). Group A inspection shall be in accordance with MIL-PRF-38534 and as follows:

- a. Tests shall be as specified in table II herein.
- b. Subgroups 7, 8, 9, 10, and 11 shall be omitted.

4.3.2 Group B inspection (PI). Group B inspection shall be in accordance with MIL-PRF-38534.

4.3.3 Group C inspection (PI). Group C inspection shall be in accordance with MIL-PRF-38534 and as follows:

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test, method 1005 of MIL-STD-883.
  - (1) Test condition A, B, C, or D. The test circuit shall be maintained by the manufacturer under document revision level control and shall be made available to either DSCC-VA or the acquiring activity upon request. Also, the test circuit shall specify the inputs, outputs, biases, and power dissipation, as applicable, in accordance with the intent specified in test method 1005 of MIL-STD-883.
  - (2)  $T_C$  as specified in accordance with table I of method 1005 of MIL-STD-883.
  - (3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

4.3.4 Group D inspection (PI). Group D inspection shall be in accordance with MIL-PRF-38534.

<b>STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000</b>	<b>SIZE A</b>		<b>5962-93093</b>
		<b>REVISION LEVEL A</b>	<b>SHEET 11</b>

4.3.5 Group E inspection. Group E inspection is required only for parts intended to be marked as radiation hardness assured (see 3.5 herein). RHA levels for device classes H and K shall be M, D, R, and H. RHA quality conformance inspection sample tests shall be performed at the RHA level specified in the acquisition document.

- a. RHA tests for device classes H and K for levels M, D, R, and H shall be performed through each level to determine at what levels the devices meet the RHA requirements. These RHA tests shall be performed for initial qualification and after design or process changes which may affect the RHA performance of the device.
- b. End-point electrical parameters shall be as specified in table II herein.
- c. Prior to total dose irradiation, each selected sample shall be assembled in its qualified package. It shall pass the specified group A electrical parameters in table I for subgroups specified in table II herein.
- d. For device classes H and K, the devices shall be subjected to radiation hardness assured tests as specified in MIL-PRF-38534 for RHA level being tested, and meet the postirradiation end-point electrical parameter limits as defined in table I at  $T_A = +25^{\circ}\text{C} \pm 5$  percent, after exposure.
- e. Prior to and during total dose irradiation testing, the devices shall be biased to establish a worst case condition as specified in the radiation exposure circuit.
- f. For device classes H and K, subgroups 1 and 2 in table V, method 5005 of MIL-STD-883 shall be tested as appropriate for device construction.
- g. When specified in the purchase order or contract, a copy of the RHA delta limits shall be supplied.

## 5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-PRF-38534.

## 6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use for Government microcircuit applications (original equipment), design applications, and logistics purposes.

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Configuration control of SMD's. All proposed changes to existing SMD's will be coordinated with the users of record for the individual documents. This coordination will be accomplished in accordance with MIL-STD-973 using DD Form 1692, Engineering Change Proposal.

6.4 Record of users. Military and industrial users shall inform Defense Supply Center Columbus when a system application requires configuration control and the applicable SMD. DSCC will maintain a record of users and this list will be used for coordination and distribution of changes to the drawings. Users of drawings covering microelectronic devices (FSC 5962) should contact DSCC-VA, telephone (614) 692-0544.

6.5 Comments. Comments on this drawing should be directed to DSCC-VA, P. O. Box 3990, Columbus, Ohio 43216-5000, or telephone (614) 692-0512.

6.6 Sources of supply. Sources of supply are listed in QML-38534. The vendors listed in QML-38534 have submitted a certificate of compliance (see 3.7 herein) to DSCC-VA and have agreed to this drawing.

<b>STANDARD MICROCIRCUIT DRAWING DEFENSE SUPPLY CENTER COLUMBUS COLUMBUS, OHIO 43216-5000</b>	<b>SIZE A</b>		<b>5962-93093</b>
		<b>REVISION LEVEL A</b>	<b>SHEET 12</b>

# STANDARD MICROCIRCUIT DRAWING SOURCE APPROVAL BULLETIN

DATE: 99-07-12

Approved sources of supply for SMD 5962-93093 are listed below for immediate acquisition only and shall be added to QML-38534 during the next revision. QML-38534 will be revised to include the addition or deletion of sources. The vendors listed below have agreed to this drawing and a certificate of compliance has been submitted to and accepted by DSCC-VA. This bulletin is superseded by the next dated revision of QML-38534.

Standard microcircuit drawing PIN <u>1</u> /	Vendor CAGE number	Vendor similar PIN <u>2</u> /
5962-9309301HXA	50821	MSA2812S/883
5962-9309301HXC	50821	MSA2812S/883
5962-9309301HYA	50821	MGA2812SY/883
5962-9309301HYC	50821	MGA2812SY/883
5962-9309301HZA	50821	MGA2812SZ/883
5962-9309301HZC	50821	MGA2812SZ/883

- 1/ The lead finish shown for each PIN representing a hermetic package is the most readily available from the manufacturer listed for that part. If the desired lead finish is not listed contact the vendor to determine its availability.
- 2/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE  
number

50821

Vendor name  
and address

Interpoint Corporation  
10301 Willows Road  
Redmond, WA 98073-9705

The information contained herein is disseminated for convenience only and the Government assumes no liability whatsoever for any inaccuracies in this information bulletin.