

SUBMINIATURE

LT-5™ Fast-Acting Fuse 662 Series



ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Time
210%	30 minutes, Maximum
275%	.010 sec Min. ; 3 sec Max
400%	.003 sec Min. ; .030 sec Max
1000%	.020 sec Maximum

AGENCY APPROVALS: IEC 127-3/1: Semko and VDE approved 50 mA through 3.15 A. Recognized under the Components Program Underwriters Laboratories and recognized by CSA.

INTERRUPTING RATINGS: 35A or 10X rated current; whichever is greater.

PACKAGING:

Please refer to the following suffixes when ordering.

Bulk 100 pieces:

Short Lead (Bulk) HXSL

Long Lead (Bulk) HXLL

Tape and Reel 750 pieces:

Long Lead (Tape and Reel IEC 286-2) ZRLL

PATENTED

ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating	Nominal Melting I ² t (A ² Sec)
0662.050	.050	250	0.004
0662.063	.063	250	0.001
0662.080	.080	250	0.001
0662.100	.100	250	0.002
0662.125	.125	250	0.006
0662.160	.160	250	0.014
0662.200	.200	250	0.024
0662.250	.250	250	0.058
0662.315	.315	250	0.104
0662.400	.400	250	0.044
0662.500	.500	250	0.090
0662.630	.630	250	0.150
0662.800	.800	250	0.220
0662.001.	1.00	250	0.330
0662 1.25	1.25	250	0.680
0662 01.6	1.60	250	0.940
0662 002.	2.00	250	1.330
0662 02.5	2.50	250	1.940
0662 3.15	3.15	250	5.400
0662 004.	4.00	250	7.900
0662 005.	5.00	250	11.190

Refer to page 96 for LT-5™ holder information.

