

Foster®**PRODUCT DATA**
81-28

An H.B. Fuller Company

71 92897

TECHNICAL DATA:**TYPE**

Aerosol Adhesive

COLOUR

Straw

BASE

Synthetic Rubber/Resin

SOLIDS CONTENT

24% by weight

APPLICATION METHOD

Aerosol spray

APPLICATION TEMP

+5°C to +40°C

DRYING TIME

2-5 minutes

CLEAN UP

Multi-Purpose Cleaner

STORAGE

Store in clean dry shaded conditions between 5°C and 25°C

SHELF LIFE

12 months when stored as above

PACKAGING

500ml aerosol can

**FOSTER
SPRAYTACK
81-28**

Foster Spraytack is an aerosol adhesive which does not contain CFC's, Dichloromethane or 1,1,1, Trichloroethane. It bonds a wide variety of materials giving rapid bond formation and is economical in use.

- Halogen and CFC free
- Faster tack
- Foaming formula for low soak in
- Economical in use
- Variable spray

USES

Spraytack bonds wood, concrete, stone, tiles, rubber, foam, metals, rigid plastics, polyethylene, canvas fabrics, cardboard, paper and cork.

Spraytack is ideal for fixing polyethylene sheeting for enclosures prior to asbestos removal, for fixing thermal insulation and for packaging applications such as palletising or case sealing. It may be used for foam bonding, upholstery, automotive, carpets and trim and is useful for temporary bonding instead of double sided tapes.

Foster Products UK

Moor Road, Chesham, Bucks HP5 1SB England

Tel: +(44) (0) 1494 784444 Direct Sales (01494) 602221 Fax: +(44) (0) 1494 791903

Foster SPRAYTACK 81-28

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

H B FULLER UK Ltd
Moor Road
Chesham
Buck
HP8 2D
England

Tel: +44 (0)1494 784444
Fax: +44 (0)1494 791903

SAFETY DATA SHEET

PRODUCT NAME : Foster SPRAYTACK 81-28

PRODUCT CODE : MS2586/TIP8128

2 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Cas No.	EC No.	Weight%	Symbols	R Phrases
Polymers, resins, and other additives. non-hazardous.			10 - 25	---	---
Butane/propane propellant			25 - 50	F+	12
Acetone	67-64-1	200-662-2	10 - 25	F-Xi	11-36-66-67
Petroleum distillate (cyclopentadiene hydrocarbons)	92062-15-2	295-529-9	10 - 25	F, Xn, N	11-38-67-51/53-65

3 HAZARDOUS IDENTIFICATION

- Extremely Flammable (R12)
- Pressurized aerosol container

4 FIRST AID MEASURES

CONTACT WITH SKIN

- After contact with skin, wash immediately with plenty of soap and water (S26)
- Do not use solvents to clean skin
- Seek medical attention if irritation persists

CONTACT WITH EYES

- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice (S26)

Creation Date 06/06/2000
GBR

MS2586/TIP8128 Page 1 of 5

Foster SPRAYTANK 81-28

4 FIRST-AID MEASURES

INGESTION

- * Seek immediate medical attention
- * Do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention

INHALATION

- * Remove patient to fresh air
- * Keep warm and at rest
- * See medical advice

OTHER INFORMATION

5 FIRE-FIGHTING MEASURES

- * In case of fire use water, foam, carbon dioxide or dry agent (S43)
 - * In case of fire, do not breathe fumes
 - * Inform Fire Brigade of potential danger of exploding and rocketing cylinders
-

6 ACCIDENTAL RELEASE MEASURES

- * Ventilate area
 - * Absorb spillage in earth or sand
 - * Wear suitable protective clothing gloves and eye/face protection (S36/37/39)
-

7.1 HANDLING

- * Do not breathe vapour/fumes (S23)
 - * Use only in well ventilated areas (S51)
 - * Avoid contact with skin & eyes
 - * In use, may form flammable/explosive vapour-air mixture (R18)
 - * Keep away from heat and sources of ignition
 - * Do not spray on naked flame or any incandescent material
-

7.2 STORAGE

- * Keep out of reach of children (S2)
 - * Store above 5 deg C
 - * Do not store above 30 deg C
 - * Keep container in a well ventilated place (S9)
 - * Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 deg C
-

8.1 EXPOSURE CONTROLS/PERSONAL PROTECTION

- * In case of insufficient ventilation, wear suitable respiratory equipment (S38)
-

Poster SPRAYTEK 61-28

8.2 EXPOSURE LIMITS

Constituent Exposure Limit:

Butane/Propane propellant

- * OES LTSL 600 ppm
- * OES STEL 750 ppm

Acetone

- * OES LTSL 750 ppm
- * OES STEL 1500 ppm

Petroleum distillate (cycloparaffinic hydrocarbons)

- * Exposure limit (in house) 300 ppm

9 PHYSICAL AND CHEMICAL PROPERTIES

- * Liquid, colourless, solution, miscible with most organic solvents
- * Extremely flammable (R12)
- * Boiling point - not applicable
- * Flash point approx -40 deg C (CC)
- * Melting point - not applicable
- * Auto-ignition point - not known
- * pH - not applicable
- * Specific gravity - not applicable
- * Insoluble in water
- * Viscosity - not applicable
- * Vapour density (air = 1) >1.8

10 STABILITY AND REACTIVITY

- * This article is considered stable under normal conditions
- * In use, may form flammable/explosive vapour-air mixture (R16)
- * Insoluble with water
- * No hazardous reactions known if used for its intended purpose
- * Keep away from heat

11 TOXICOLOGICAL INFORMATION

- * Vapours or aerosols may cause irritation of eyes, nose and respiratory tract
- * Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis
- * Inhalation of solvent vapours may give rise to nausea, headaches and dizziness

12 ECOLOGICAL INFORMATION

- * Volatile portion is biodegradable
- * The dried residue is not readily biodegradable

14.2 TRANSPORT INFORMATION

UN

UN No. : 1950
Packaging Group

Road/Rail (ADR/RID)

ADR UN No. : 1950
ADR Item No. : 5.1
Transport : 20053

Sea (IMD)

IMDG UN No. : 1950
IMDG Page No. : 2102-
IMDG Bms : 2-12

Air (ICAO/IATA)

ICAO UN No. : 1950
ICAO Packing Group : ---

ICAO Hazard Class : 2.1
IMDG Hazard Class : 2.1
IMDG Pack. Group : ---
IMDG Bms : 2-12

Hazard Class : 1
ADR/RID No. : 2
ADR Hazard Class

14.1 TRANSPORT REGULATIONS

Disposal should be in accordance with local, state or national legislation
Do not place or burn container, even after use

13 DISPOSAL CONSIDERATIONS

Foster Bryant UK 81-28

Foster SPRAYTACK 81-28

15 REGULATORY INFORMATION

- * The COSHH Regulations apply in the UK
- * The CHIP Regulations apply in the UK
- * The Environmental Protection Act applies in the UK
- * The information provided about the product on this Safety Data Sheet has been compiled from knowledge of the individual constituents
- * The data given here only applies when product used for proper application(s). The product is not sold as suitable for other applications - usage in such may cause risks not mentioned in this sheet. Do not use for other application(s) without seeking advice from manufacturer.
- * The data given here is based on current knowledge and experience. This Safety Data Sheet describes the product in terms of safety requirements and does not signify any warranty with regard to the product's properties
- * This Safety Data Sheet does not constitute a workplace risk assessment

15.1 RISK PHRASES

- * Extremely Flammable (R12)

15.2 SAFETY PHRASES

- * Keep away from sources of ignition - No Smoking (S16)
- * Do not breathe vapour (S23)
- * In case of insufficient ventilation, wear suitable respiratory equipment (S38)
- * Keep out of reach of children (S2)

16 OTHER INFORMATION

Section 15: Additional risk phrase:
R57: Vapours may cause drowsiness and dizziness.

For intended uses and applications please refer to the product Technical Data Sheet.

If you have purchased the product for supply to a third party for use at work, it is your duty to ensure that any person handling or using the product is provided with the information in this sheet.

If you are an employer, it is your duty to tell your employees, and others who may be affected, of any hazards described in this sheet and of any precautions which should be taken.

APPLICATION GUIDE FOR FOSTER SPRAYTACK 81-28

HOW TO APPLY

Shake before use. Select fan width by turning to desired setting. Spray adhesive from 6"-8" away onto one or both surfaces. Surfaces should be clean, dry and free from grease.

For 1-way application let adhesive dry for 30 seconds until tacky, then press into position.

For 2-way application, spray both surfaces and allow to dry for 2-5 minutes before bonding.

For temporary bonding, spray one surface and allow to dry for 2-5 minutes before bonding. Excess adhesive can be removed with Multi-Purpose Cleaner. To prevent spray nozzle from blocking, at the end of each day turn can upside down and press nozzle until spray is clear of adhesive.

Not suitable for use with plasticised PVC or expanded polystyrene.

HEALTH AND SAFETY DATA:

Full Health and Safety Information on SPRAYTACK 81-28 is available from the manufacturer.

IMPORTANT NOTE:

All the information in this Data Sheet is based on practical experience and is published in good faith. However, because we have no control over the manner or conditions in which our products are used, or over work undertaken or end product manufactured by the purchaser, we cannot accept liability for results. Responsibility for ascertaining the suitability of products for his purposes rests with the purchaser. All conditions, representations, statements, warranties or guarantees whatsoever, whether express, implied or statutory, in respect of any goods manufactured, sold or supplied by us are hereby expressly excluded and we accept no liability in respect of any claim for damage or consequential loss caused to any property arising directly or indirectly out of the use of our products or goods.

IMPORTANT: Foster Products Corporation warrants that each of its products will be manufactured in accordance with Foster's specifications in effect on the date of manufacture. **FOSTER MAKES NO OTHER WARRANTIES AND EXPRESSLY DISCLAIMS ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If a product fails to meet this limited warranty, purchaser's sole and exclusive remedy is replacement of the product or, at Foster's option, refund of the purchase price. **FOSTER'S ACCEPTANCE OF ANY ORDERS FOR THIS PRODUCT IS EXPRESSLY CONDITIONAL UPON PURCHASER'S ASSENT TO THE TERMS ON THE APPLICABLE INVOICE.**

ADEQUATE TEST: The information contained herein we believe is correct to the best of our knowledge and tests. The recommendations and suggestions herein are made without guarantee or representation as to results. We recommend that adequate tests be performed by you to determine if this product meets all of your requirements. The warranted shelf life of Foster products is six months from date of shipment to the original purchaser.

For industrial use only. Keep out of reach of children.

Consult Material Safety Data Sheet and container label for further information.