

 **Seagate** Microelectronics Limited

5 AMP POSITIVE ADJUSTABLE REGULATORS

IP138A, IP338A, IP138, LM138, IP338, LM338

DESCRIPTION

The IP138A series are 3-terminal positive adjustable voltage regulators capable of supplying in excess of 5A over a 1.25V to 35V output range. These regulators are exceptionally easy to use and require only two external resistors to set the output voltage. In addition to improved line and load regulation, a major feature of the "A" series is the initial output voltage tolerance, which is guaranteed to be less than 1%. Over full operating conditions, including load, line and lower dissipation, the reference voltage is guaranteed not to vary more than 2%. These devices exhibit current limit, thermal overload protection, and improved power device safe operating area protection, making them essentially indestructible.

FEATURES


T-58-11-23

- Available in low cost TO-218
- Guaranteed 1% output voltage tolerance
- Guaranteed 0.3% load regulation
- Guaranteed 0.01%/V line regulation
- Internal current limiting constant with temperature
- Internal thermal overload protection
- Improved output transistor safe operating area compensation
- Output adjustable between 1.25V and 35V

4


CONNECTIONS

(Top View)



TO-218 Plastic

(Bottom View)



TO-3 Metal Can



IP138A, IP338A, IP138, LM138, IP338, LM338

5 AMP POSITIVE ADJUSTABLE REGULATORS

ABSOLUTE MAXIMUM RATINGS

T-58-1123

Power Dissipation Internally Limited

Storage Temperature Range -65°C to +150°C

Input to Output Voltage Differential 35V

Lead Temperature (Soldering, 10 sec.) 300°C

Operating Junction Temperature Range

IP138A, LM138, IP138 -55°C to +150°C

IP338A, LM338, IP338 0°C to +125°C

Absolute maximum ratings are those values beyond which the safety of the device cannot be guaranteed. They are not meant to imply that the device should be operated at these limits. The electrical characteristics provide conditions for actual device operation.

ELECTRICAL CHARACTERISTICS (NOTE 1)

Parameter	Test Conditions	IP138A			LM138/IP138			Units
		Min	Typ	Max	Min	Typ	Max	
Reference Voltage, V_{REF}	$I_{OUT} = 10 \text{ mA}$	1.238	1.250	1.262				V
	$3V \leq (V_{IN} - V_{OUT}) \leq 35V$	1.225	1.250	1.270	1.19	1.24	1.29	V
	$10 \text{ mA} \leq I_{OUT} \leq 5A, P \leq 50W$							
Line Regulation, $\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	$3V \leq (V_{IN} - V_{OUT}) \leq 35V$		0.005	0.01		0.005	0.01	%/V
	(See Note 2)		0.020	0.04		0.020	0.04	%/V
Load Regulation, $\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$	$10 \text{ mA} \leq I_{OUT} \leq 5A$							
	$V_O \leq 5V$		5	15		5	15	mV
	$V_O \geq 5V$		0.1	0.3		0.1	0.3	%
	$V_O \leq 5V$		20	30		20	30	mV
	$V_O \geq 5V$		0.3	0.6		0.3	0.6	%
Thermal Regulation	20 msec Pulse		0.002	0.01		0.002	0.01	%/W
Ripple Rejection	$V_{OUT} = 10V, C_{ADJ} = 0$		60			60		dB
	$f = 120 \text{ Hz}, C_{ADJ} = 10\mu F$	60	75		60	75		dB
Adjust Pin Current, I_{ADJ}			45	100		45	100	μA
Adjust Pin Current Change, ΔI_{ADJ}	$10 \text{ mA} \leq I_{OUT} \leq 5A$		0.2	5		0.2	5	μA
	$3V \leq (V_{IN} - V_{OUT}) \leq 35V$							
Minimum Load Current, I_{MIN}	$(V_{IN} - V_{OUT}) = 35V$		3.5	5		3.5	5	mA
Current Limit, I_{SC}	$(V_{IN} - V_{OUT}) \leq 10V$		5	8		5	8	A
	DC		7	12		7	12	A
	$(V_{IN} - V_{OUT}) = 30V$		1			1		A
Temperature Stability, $\frac{\Delta V_{OUT}}{\Delta TEMP}$			1	2		1		%
Long Term Stability, $\frac{\Delta V_{OUT}}{\Delta TIME}$	$T_A = 125^\circ C, 1000 \text{ Hrs}$		0.3	1		0.3	1	%
RMS Output Noise (% of V_{OUT}), e_n	$10 \text{ Hz} \leq f \leq 10 \text{ kHz}$		0.001			0.001		%
Thermal Resistance Junction to Case, θ_{JC}	K Package			1			1	$^\circ C/W$



IP138A, IP338A, IP138, LM138, IP338, LM338

5 AMP POSITIVE ADJUSTABLE REGULATORS

ELECTRICAL CHARACTERISTICS (NOTE 1)

T-58-11-23

Parameter	Test Conditions	IP338A			LM338/IP338			Units
		Min	Typ	Max	Min	Typ	Max	
Reference Voltage, V_{REF}	$I_{OUT} = 10\text{ mA}$	1.238	1.250	1.262				V
	$3\text{V} \leq (V_{IN} - V_{OUT}) \leq 35\text{V}$	• 1.225	1.250	1.270	1.19	1.24	1.29	V
	$10\text{ mA} \leq I_{OUT} \leq 5\text{A}$, $P \leq 50\text{W}$							
Line Regulation, $\frac{\Delta V_{OUT}}{\Delta V_{IN}}$	$3\text{V} \leq (V_{IN} - V_{OUT}) \leq 35\text{V}$		0.005	0.01		0.005	0.03	%/V
	(See Note 2)	•	0.02	0.04		0.020	0.06	%/V
Load Regulation, $\frac{\Delta V_{OUT}}{\Delta I_{OUT}}$	$10\text{ mA} \leq I_{OUT} \leq 5\text{A}$		5	15		5	25	mV
	(See Note 2)							
	$V_O \leq 5\text{V}$		0.1	0.3		0.1	0.5	%
	$V_O \geq 5\text{V}$	•	20	30		20	50	mV
Thermal Regulation	$V_O \leq 5\text{V}$	•	0.3	0.6		0.3	1	%
	$V_O \geq 5\text{V}$	•						
Ripple Rejection	20 msec Pulse		0.002	0.02		0.002	0.02	%/W
	$V_{OUT} = 10\text{V}$, $f = 120\text{ Hz}$							
Adjust Pin Current, I_{ADJ}	$C_{ADJ} = 0$	•	60			60		dB
	$C_{ADJ} = 10\mu\text{F}$	• 60	75		60	75		dB
Adjust Pin Current Change, ΔI_{ADJ}		•	45	100		45	100	μA
Adjust Pin Current Change, ΔI_{ADJ}	$10\text{ mA} \leq I_{OUT} \leq 5\text{A}$, $3\text{V} \leq (V_{IN} - V_{OUT}) \leq 35\text{V}$	•	0.2	5		0.2	5	μA
Minimum Load Current, I_{MIN}	$(V_{IN} - V_{OUT}) = 35\text{V}$	•	3.5	10		3.5	10	mA
Current Limit, I_{SC}	$(V_{IN} - V_{OUT}) \leq 10\text{V}$							
	DC	• 5	8		5	8		A
	0.5ms peak	• 6	12		6	12		A
Temperature Stability, $\frac{\Delta V_{OUT}}{\Delta T_{EMP}}$	$(V_{IN} - V_{OUT}) = 30\text{V}$		1			1		A
		•	1	2		1		%
Long Term Stability, $\frac{\Delta V_{OUT}}{\Delta T_{IME}}$	$T_A = 125^\circ\text{C}$, 1000 hrs		0.3	1		0.3	1	%
RMS Output Noise (% of V_{OUT}), e_n	$10\text{Hz} \leq f \leq 10\text{kHz}$		0.001			0.003		%
Thermal Resistance Junction to Case, θ_{JC}	K Package			1			1	$^\circ\text{C/W}$
	V Package			1			1	$^\circ\text{C/W}$

The • denotes the specifications which apply over the full operating temperature range, all others apply at $T_j = 25^\circ\text{C}$ unless otherwise specified.













Note 1. Unless otherwise specified, these specifications apply for $V_{IN} - V_{OUT} = 5\text{V}$, $I_{OUT} = 2.5\text{A}$.
Although power dissipation is internally limited, these specifications apply for dissipations of 50W and $I_{MAX} = 5\text{A}$.

Note 2. Regulation is measured at constant junction temperature, using pulse testing at a low duty cycle. Changes in output voltage due to heating effects are covered under thermal regulation specifications. Load regulation is measured from the bottom of the package for the TO-3, and at the junction of the wide and narrow portion of the output lead for the TO-218.



5 AMP POSITIVE ADJUSTABLE REGULATORS

TYPICAL PERFORMANCE CHARACTERISTICS T-58-11-23




IP138A, IP338A, IP138, LM138, IP338, LM338


5 AMP POSITIVE ADJUSTABLE REGULATORS

TYPICAL PERFORMANCE CHARACTERISTICS (CONTINUED)

Line Transient Response




Load Transient Response




T-5871-23

TYPICAL APPLICATIONS




Remote Sensing




	OE	V _{DD}
READ	0V	5V
WRITE		
BYTE	5V	21V
CHIP ERASE	12V	21V


2816 EEPROM Supply Programmer for Read/Write Control



5V Regulator with Shut Down



Improving Ripple Rejection



Temperature Compensated Lead Acid Battery Charger



*IP138A, IP338A, IP138, LM138, IP338, LM338***5 AMP POSITIVE ADJUSTABLE REGULATORS****ORDER INFORMATION****T-58-11-23**

Part Number	Temperature Range	Package
IP138AK	-55°C to +150°C	TO-3
IP138K	-55°C to +150°C	TO-3
LM138K	-55°C to +150°C	TO-3
IP338AK	0°C to +125°C	TO-3
IP338K	0°C to +125°C	TO-3
LM338K	0°C to +125°C	TO-3
IP338AV	0°C to +125°C	TO-218
IP338V	0°C to +125°C	TO-218

