

VE 15A SERIES (15 WATTS DESK TOP AC ADAPTER)

Features

- Three pin IEC C6 input receptacle
- Wide range AC input
- Level B EMI filter
- Fully enclosed plastic case
- Fully regulated output
- High efficiency
- High Quality



Electrical specifications

Input

Voltage 90-264VAC (wide range)
 Current 1.0Arms Max.
 Frequency 47-63Hz

Output

Voltage (Vo) (see table)
 Tolerance 5%
 Power (Po) 15W
 Hold up time 10ms min. at full load, 115VAC
 OVP (see table)
 Overcurrent protection ... Built-in
 Short circuit protection ... Pulsing mode, auto recovery
 Efficiency 80% typ. at full load and 115VAC
 Ripple/Noise(Vp-p) 1% (20MHz bandwidth)

Environmental

Operating temperature

0 deg. C to +40 deg. C ambient

Storage temperature

-20 deg. C to +80 deg. C ambient

EMI


Meet FCC class B, CISPR 22 class B, VCCI class B

Safety

UL: UL1950
 CUL: CSA 22.2 NO.950
 TUV: EN 60950
 IEC: 950
 CE:

Output Electronic Specifications

Model No.	Po	Vo	Io max	OVP max
VE15A-050	15W	5.0V	3.0A	6.5V
VE15A-060	15W	6.0V	2.5A	8.0V
VE15A-075	15W	7.5V	2.0A	9.5V
VE15A-090	15W	9.0V	1.67A	12V
VE15A-120	18W	12.0V	1.5A	15V



Power Systems – The Power Solution

Web: www.Power-Systems.de
 Email: Info@Power-Systems.de

Address: Dörnet 8 ; 74360 Ilfeld-Auenstein / Germany
 Tel. : + 49 / 70 62 / 67 59 - 6
 Fax: + 49 / 70 62 / 67 59 - 80