


Specifications**Maximum Ratings****Electrical Characteristics**

Part Number	Working Voltage		Rated Single Pulse Transient		Varistor Voltage @ 1mA DC		Maximum Clamping Voltage 8/20µs 10A	Typical Capacitance @ 1MHZ
	AC RMS Volts	DC Volts	Energy 10/1000µs Joules	Peak 8/20µs Amps	Min Volts	Max Volts	Volts	PicoFarads
VA-A3216-3R5□□	2.5	3.5	0.4	150	3.7	5.5	14	8000
VA-A3216-5R5□□	4.0	5.5	0.4	150	7.1	9.3	16	5300
VA-A3216-080□□	5.7	8.0	0.4	150	9.6	12.5	24	4100
VA-A3216-110□□	7.8	11.0	0.4	150	12.7	15.5	27	3300
VA-A3216-140□□	10.0	14.0	0.4	150	15.9	20.3	30	3100
VA-A3216-180□□	12.7	18.0	0.4	150	22.0	28.0	40	2400
VA-A3216-260□□	18.4	26.0	0.4	120	29.5	38.5	58	1800
VA-A3216-330□□	23.3	33.0	0.4	120	38.0	45.0	72	950
VA-A3216-420□□	30.0	42.0	0.4	100	46.0	56.0	86	550
VA-A3216-560□□	40.0	56.0	0.4	100	58.0	76.0	110	350
VA-A3216-680□□	48.1	68.0	0.4	100	76.0	90.0	130	260
Low Capacitance Series								
VA-A3216-3R5J□□	2.5	3.5	0.1	30	3.7	5.5	14	4300
VA-A3216-5R5J□□	4.0	5.5	0.1	40	7.1	9.3	16	2800
VA-A3216-080J□□	5.7	8.0	0.1	40	9.6	12.5	24	2200
VA-A3216-110J□□	7.8	11.0	0.1	40	12.7	15.5	27	1800
VA-A3216-140J□□	10.0	14.0	0.1	40	15.9	20.3	30	1600
VA-A3216-180J□□	12.7	18.0	0.1	30	22.0	28.0	40	1300
Very Low Capacitance Series								
VL-A3216-180J□□	12.7	18.0	0.1	20	22.0	28.0	50	<200

1206 Series is the U. S. equivalent for the 3216 millimeter series.

Dimensions

L =	3.2 ± 0.2 mm 0.126 ± 0.008 inches
W =	1.6 ± 0.2 mm 0.063 ± 0.008 inches
T =	1.3 ± 0.2 mm 0.039 ± 0.008 inches
C =	0.7 mm max 0.028 inches max



9914368 0000710 741

Standard Quantities


The quantity per reel or per bulk package is indicated below. Orders for all Multilayer Varistors are processed and shipped in full reel/bulk increments, or multiples of.

<u>3,000 Taped and Reeled:</u>	0805 Series, 1206 Series	<u>4,000 Taped and Reeled:</u>	0603 Series
<u>7,000 Taped and Reeled:</u>	0805 Series, 1206 Series	<u>8,000 Taped and Reeled:</u>	0603 Series

The packaging specifications indicated are standard for the majority of configurations. Please consult World Products for specific details.




Reel Dimensions

W = 9.0 ± 0.3 mm
 0.354 ± 0.012 inches



Taping Dimension


mm [inches]



The pitch holes shift within $\pm 0.3\text{mm}$ [0.012inches] for cumulative 10 pitches.

	0603 Series		0805 Series		1206 Series	
	mm	inches	mm	inches	mm	inches
A $\pm 0.1\text{mm}$ (0.004 inches)	1.00	0.040	1.45	0.057	1.90	0.075
B $\pm 0.1\text{ mm}$ (0.004 inches)	1.80	0.070	2.25	0.088	3.60	0.142
P $\pm 0.1\text{ mm}$ (0.004 inches)	2.0	0.080	4.0	0.157	4.0	0.157
K ₀ $\pm 0.1\text{ mm}$ (0.004 inches)	0.95	0.037	1.00	0.040	1.35	0.053
T maximum	0.3	0.012	0.3	0.012	0.3	0.012

Top Tape Dimension



The force for tearing of top tape is 20 to 70 grams in the arrow direction.

9914368 0000719 979