



Led Signalleuchten Einbaudurchmesser 6 mm
Led Indicators Body diameter 6 mm

Zweifarbige, mit Innenreflektor
Duo Led, with interior reflector

Bestell-Nr.	Farbe	V _{OP} +10%	I _{OP max.}	V _F	I _{V typ.} (mcd)	I _{F max.}	Abb.	Abmessungen, siehe Zeichnungsnr.	19030-A	A
Part No.	Colour	(V)	(mA)	(V)	*I _F = 20mA	(mA)	Illu.	Dimensions, see Drawing No.		
1903*004	Super red/ Green			2,0/2,2 2,2/2,8	*14/22	30	A			
1903*005	Super red/ Yellow			2,0/2,2 2,2/2,8	*14/14	30	A			
1903*006	Green/ Yellow			2,0/2,2 2,2/2,8	*22/14	30	A			
1903*054	Super red/ Green			2,0/2,2 2,2/2,8	*14/22	30	B			
1903*055	Super red/ Yellow			2,0/2,2 2,2/2,8	*14/14	30	B			
1903*056	Green/ Yellow			2,0/2,2 2,2/2,8	*22/14	30	B			
1903*154	Super red/ Green	6	30		19/34		B			
1903*155	Super red/ Yellow	6	30		19/20		B			
1903*156	Green/ Yellow	6	30		34/20		B			
1903*254	Super red/ Green	12	30		19/34		B	Abmessungen, siehe Zeichnungsnr. Dimensions, see Drawing No.	19030-B	B
1903*255	Super red/ Yellow	12	30		19/20		B			
1903*256	Green/ Yellow	12	30		34/20		B			
1903*354	Super red/ Green	24	18		13/20		B			
1903*355	Super red/ Yellow	24	18		13/13		B			
1903*356	Green/ Yellow	24	18		20/13		B			
										

Arbeits temperatur (T_{OP}): -55°C - +70°C
Lagertemperatur (T_{STG}): -55°C - +100°C

* Die Signalleuchte kann mit Glanzchrom oder Schwarzchrom geliefert werden. Die 5. Stelle der Bestellnummer wird mit 0 oder 1 codiert.

Glanzchrom = 0 Schwarzchrom = 1

Beispiel: 19030004 super rot / grün mit Glanzchrom
19031004 super rot / grün mit Schwarzchrom

Operating temperature (T_{OP}): -55°C - +70°C
Storage temperature (T_{STG}): -55°C - +100°C

* The Led indicator can be delivered in bright or black chrome reflector. The 5. digit has to be coded with 0 or 1.

Bright chrome = 0 Black chrome = 1

Example: 19030004 super red / green with bright chrome
19031004 super red / green with black chrome

Led Signalleuchten mit anderen Spannungen auf Anfrage

Technische Änderungen vorbehalten

Led Indicators with other voltages upon request

Specification subject to change without notice