

COLLECTOR CURRENT = 5 AMPS PNP TYPES - CONTINUED

Device No	Case	VCBO Volts	VCEO (sus) Volts	VEBO Volts	hFE		VCE	IC	VCE (sat)	VBE (sat)	@ IC	@ IB	θ_{JC} °C/W	Ft MHz
					Min	Max								
2N3868	TO-5	65	60	4	30	150	2	1.5	.7	1.4	1.5	.15	25	60
2N4901	TO-3	40	40	5	20	80	2	1	.4	1.2	1	.1	2.3	4
2N4902	TO-3	60	60	5	20	80	5	1	.4	1.2	1	.1	2.3	4
2N4903	TO-3	80	80	5	20	80	2	1	.4	1.2	1	.1	2.3	4
2N4904	TO-3	40	40	5	25	100	2	2.5	1	1.4	2.5	.25	2.3	4
2N4905	TO-3	60	60	5	25	100	2	2.5	1	1.4	2.5	.25	2.3	4
2N4906	TO-3	80	80	5	25	100	2	2.5	1	1.4	2.5	.25	2.3	4
2N4907	TO-3	40	40	5	20	80	4	4	.75	1.5	4	.4	2.3	4
2N4908	TO-3	60	60	5	20	80	4	4	.75	1.5	4	.4	2.3	4
2N4909	TO-3	80	80	5	20	80	4	4	.75	1.5	4	.4	2.3	4
2N4999	TO-111/I	100	80	5.5	30	90	5	1	.85	1.5	2	.2	3.33	60
2N5001	TO-111/I	100	80	5.5	70	200	5	1	.85	1.5	2	.2	3.33	60
2N5003	TO-111/I	100	80	5.5	30	90	5	2.5	1.5	2.2	5	.5	3	50
2N5005	TO-111/I	100	80	5.5	70	200	5	2.5	1.5	2.2	5	.5	3	50
2N5147	TO-5	100	80	5.5	30	90	5	1	.85	1.5	2	.2	25	50
2N5149	TO-5	100	80	5.5	70	200	5	1	.85	1.5	2	.2	25	60
2N5286	TO-111/I	120	100	5.5	30	90	5	2.5	1.5	2.2	5	.5	3	50
2N5287	TO-111/I	120	100	5.5	70	200	5	2.5	1.5	2.2	5	.5	3	50
2N5333	TO-5	100	80	6	30	120	4	1	1	1.5	2	.2	25	60
2N5384	TO-111/I	100	80	6	20	80	4	2	.6	1.5	2	.2	3.33	60
2N5385	TO-111	100	80	6	20	80	4	2	.6	1.5	2	.2	3.3	60
2N5404	TO-5	80	80	6	20	60	5	2	.6	1.2	2	.2	25	60
2N5405	TO-5	100	100	6	20	60	5	2	.6	1.2	2	.2	25	60
2N5406	TO-5	80	80	6	40	120	5	2	.6	1.2	2	.2	25	60
2N5407	TO-5	100	100	6	40	120	5	2	.6	1.2	2	.2	25	60
2N5408	TO-111/I	80	80	6	20	60	5	2	.6	1.2	2	.2	3.33	60
2N5409	TO-111/I	100	100	6	20	60	5	2	.6	1.2	2	.2	3.33	60
2N5410	TO-111/I	80	80	6	40	120	5	2	.6	1.2	2	.2	3.33	60
2N5411	TO-111/I	100	100	6	40	120	5	2	.6	1.2	2	.2	3.33	60
2N5597	TO-66	80	60	5.5	70	200	5	1	.85	1.5	2	.2	6	60
2N5599	TO-66	100	80	5.5	30	90	5	1	.85	1.5	2	.2	6	60
2N5601	TO-66	100	80	5.5	70	200	5	1	.85	1.5	2	.2	6	60
2N5603	TO-66	120	100	5.5	30	90	5	1	.85	1.5	2	.2	6	60
2N5605	TO-66	80	60	5.5	70	200	5	2.5	.75	1.45	2.5	.25	6	60
2N5607	TO-66	100	80	5.5	30	90	5	2.5	.75	1.45	2.5	.25	6	50
2N5609	TO-66	100	80	5.5	70	200	5	2.5	.75	1.45	2.5	.25	6	50
2N5611	TO-66	120	100	5.5	30	90	5	2.5	.75	1.45	2.5	.25	6	50
2N5613	TO-3	80	60	5.5	70	200	5	2.5	1.5	2.2	5	.5	3	50
2N5615	TO-3	100	80	5.5	30	90	5	2.5	1.5	2.2	5	.5	3	50
2N5617	TO-3	100	80	5.5	70	200	5	2.5	1.5	2.2	5	.5	3	50
2N5619	TO-3	120	100	5.5	30	90	5	2.5	1.5	2.2	5	.5	3	50
2N5867	TO-3	60	60	5	20	100	4	1.5	2	2.5	5	1.25	2	4
2N5868	TO-3	80	80	5	20	100	4	1.5	2	2.5	5	1.25	2	4
2N5871	TO-3	60	60	5	20	100	4	2.5	1	2.5	4	.4	3.33	4
2N5872	TO-3	80	80	5	20	100	4	2.5	1	2.5	4	.4	3.33	4
AP1008	TO-3	400	400	4	30	90	5	1	2.5	2	2.5	.5	1.25	4
AP1009	TO-3	500	400	6	15	60	5	3	.5	1.5	3	.6	1.25	4
AP1010	TO-66	500	400	6	15	60	5	3	.5	1.5	3	.6	2.5	4
AP1017	TO-3	375	350	4	10	50	3	2	1.5	2	2	.2	1.75	5
AP1018	TO-3	400	325	4	20	80	5	.5	1	1.2	1.5	.3	1.25	4
AP1019	TO-66	350	325	4	25	125	5	1	.5	1	1	.1	3.5	20
AP1025	TO-3	375	300	4	20	80	10	2	2.5	3	2	.25	1.75	5
AP1026	TO-66	400	300	4	25	75	5	1	.4	1.2	3	.6	3.33	60
AP1027	TO-5	400	300	4	25	75	5	1	.4	1.2	3	.6	20	60
AP1028	TO-3	375	300	4	10	100	4	5	2	2	5	.5	1.6	15
AP1035	TO-3	300	275	4	10	50	3	2	1.5	2	2	.2	1.75	5
AP1036	TO-66	300	275	4	25	125	5	1	.5	1	1	.1	3.5	2
AP1040	TO-5	375	250	4	8	80	2	1	.75	1.4	1	.125	5	1
AP1041	TO-111/I	250	250	4	30	110	5	.5	2	2.2	3	.3	3.33	60
AP1042	TO-111/I	250	250	4	90	250	5	.5	2	2.2	3	.3	3.33	60