


Digitally Programmable Delay Units

SERIES: PDU-1032H
(5-Bit) ECL Interfaced

data delay devices, inc.



Features:


- Low propagation delay
- Input & output ECL buffered
- 5-BIT ECL programmable delay line
- Output same polarity of input
- Completely interfaced
- Compact & low profile

Specifications:

- Delay variation: Monotonic in one direction
- Programmed delay tolerance: $\pm 5\%$ or 2 ns whichever is greater.
- Inherent delay (T_0): 5.5 ns ± 1 ns for PDU-1032H-1 thru -5. Greater for rest of part numbers.
- Propagation delay:
Address to output (T_{SUA}) = 3.6 ns typ.
Enable to output (T_{SUE}) = 1.7 ns typ.
- Power dissipation: 615 mw typ.
- Supply voltage: -5 Vdc $\pm 5\%$.
- Operating temperature: 0-70°C.
- Temperature coefficient: 100 PPM/°C.
- DC parameters: See ECL-10KH Logic Table on Page 6.

Test Conditions

- Input pulse-width: $\geq 150\%$ of Max. delay.
- Input pulse spacing: ≥ 3 times of Max. delay.
- Input pulse voltage: ECL logic.
- Measurements taken @ $T_a = 25^\circ\text{C}$, $V_{EE} = -5\text{V}$.



† or case stand-offs

TRUTH TABLE

Enable ($\bar{E}_0$)	Address					Delay Out
	5	4	3	2	1	
0	0	0	0	0	0	T_0
0	0	0	0	0	1	T_1
0	0	0	0	1	0	T_2
0	0	0	0	1	1	T_3
0	0	0	1	0	0	T_4
0	0	0	1	0	1	T_5
0	0	0	1	1	0	T_6
0	0	0	1	1	1	T_7
0	0	1	0	0	0	T_8
0	0	1	1	1	1	T_{15}
0	1	0	0	0	0	T_{16}
0	1	1	1	1	1	T_{31}
1	0	0	0	0	0	0

0 = Logic 0 1 = Logic 1 ϕ = Don't care.
 T_0 = Reference or inherent delay of unit.
 $T_1 \rightarrow T_{31}$ Multiplier of incremental delay.

Part No.	Incremental Delay Per Step (ns)	Total Programmed Delay (ns)
PDU-1032H-0.5	0.5 ± 0.3	15.5
PDU-1032H-1	1 ± 0.5	31
PDU-1032H-2	2 ± 0.5	62
PDU-1032H-3	3 ± 1.0	93
PDU-1032H-4	4 ± 1.0	124
PDU-1032H-5	5 ± 1.0	155
PDU-1032H-6	6 ± 1.0	186
PDU-1032H-8	8 ± 1.0	248
PDU-1032H-10	10 ± 1.5	310
PDU-1032H-12	12 ± 1.5	371
PDU-1032H-15	15 ± 1.5	465
PDU-1032H-20	20 ± 2.0	620

3 Mt. Prospect Avenue, Clifton, New Jersey 07013 ■ (201) 773-2299 ■ FAX (201) 773-9672

■ 2644382 0001049 106 ■ 50