

NPN-Silizium-Fototransistor
Silicon NPN Phototransistor
Lead (Pb) Free Product - RoHS Compliant

BPX 43



Wesentliche Merkmale

- Speziell geeignet für Anwendungen im Bereich von 450 nm bis 1100 nm
- Hohe Linearität
- Hermetisch dichte Metallbauform (TO-18) mit Basisanschluss, geeignet bis 125 °C
- Gruppierbar

Features

- Especially suitable for applications from 450 nm to 1100 nm
- High linearity
- Hermetically sealed metal package (TO-18) with base connection suitable up to 125 °C
- Available in groups

Anwendungen

- Lichtschranken für Gleich- und Wechsellichtbetrieb
- Industrieelektronik
- „Messen/Steuern/Regeln“

Applications

- Photointerrupters
- Industrial electronics
- For control and drive circuits

| Typ Type | Bestellnummer Ordering Code | Fotostrom , $E_e = 0.5 \text{ mW/cm}^2$, $\lambda = 950 \text{ nm}$, $V_{CE} = 5 \text{ V}$ Photocurrent I_{pce} (mA) |
|--------------------------|--------------------------------|---|
| BPX 43 | Q62702P0016 | > 0.8 |
| BPX 43-3/4 ¹⁾ | Q62702P3581 | 1.25...4.0 |
| BPX 43-4 | Q62702P0016S004 | 2.0...4.0 |
| BPX 43-4/5 ¹⁾ | Q62702P3582 | > 2.0 |
| BPX 43-5 | Q 62702P0016S005 | > 3.2 |

¹⁾ nur eine Gruppe in einer Verpackungseinheit (siehe "Kennwerte") / only one bin within one packing unit (see "Characteristics")

Grenzwerte
Maximum Ratings

| Bezeichnung Parameter | Symbol Symbol | Wert Value | Einheit Unit |
|--|-------------------|----------------|-----------------|
| Betriebs- und Lagertemperatur Operating and storage temperature range | $T_{op}; T_{stg}$ | - 40 ... + 125 | °C |
| Kollektor-Emitterspannung Collector-emitter voltage | V_{CE} | 50 | V |
| Kollektorstrom Collector current | I_C | 50 | mA |
| Kollektorspitzenstrom, $\tau < 10 \mu s$ Collector surge current | I_{CS} | 200 | mA |
| Emitter-Basisspannung Emitter-base voltage | V_{EB} | 7 | V |
| Verlustleistung, $T_A = 25 \text{ °C}$ Total power dissipation | P_{tot} | 220 | mW |
| Wärmewiderstand Thermal resistance | R_{thJA} | 450 | K/W |

Kennwerte ($T_A = 25\text{ °C}$, $\lambda = 950\text{ nm}$)

Characteristics

| Bezeichnung Parameter | Symbol Symbol | Wert Value | Einheit Unit |
|---|---|-------------------|-----------------|
| Wellenlänge der max. Fotoempfindlichkeit Wavelength of max. sensitivity | $\lambda_{S\text{ max}}$ | 880 | nm |
| Spektraler Bereich der Fotoempfindlichkeit $S = 10\%$ von S_{max} Spectral range of sensitivity $S = 10\%$ of S_{max} | λ | 450 ... 1100 | nm |
| Bestrahlungsempfindliche Fläche Radiant sensitive area | A | 0.675 | mm ² |
| Abmessung der Chipfläche Dimensions of chip area | $L \times B$ $L \times W$ | 1 × 1 | mm × mm |
| Halbwinkel Half angle | φ | ± 15 | Grad deg. |
| Fotostrom der Kollektor-Basis-Fotodiode Photocurrent of collector-base photodiode $E_e = 0.5\text{ mW/cm}^2$, $V_{\text{CB}} = 5\text{ V}$ $E_v = 1000\text{ lx}$, Normlicht/standard light A, $V_{\text{CB}} = 5\text{ V}$ | I_{PCB} I_{PCB} | 11 35 | μA μA |
| Kapazität Capacitance $V_{\text{CE}} = 0\text{ V}$, $f = 1\text{ MHz}$, $E = 0$ $V_{\text{CB}} = 0\text{ V}$, $f = 1\text{ MHz}$, $E = 0$ $V_{\text{EB}} = 0\text{ V}$, $f = 1\text{ MHz}$, $E = 0$ | C_{CE} C_{CB} C_{EB} | 23 39 47 | pF pF pF |
| Dunkelstrom Dark current $V_{\text{CE}} = 25\text{ V}$, $E = 0$ | I_{CEO} | 20 (≤ 100) | nA |

Die Fototransistoren werden nach ihrer Fotoempfindlichkeit gruppiert und mit arabischen Ziffern gekennzeichnet.

The phototransistors are grouped according to their spectral sensitivity and distinguished by arabian figures.


| Bezeichnung Parameter | Symbol Symbol | Wert Value | | | | Einheit Unit |
|--|---------------------------|--------------------|---------------------|------------------|--------------------|-----------------|
| | | -2 | -3 | -4 | -5 | |
| Fotostrom, $\lambda = 950 \text{ nm}$ Photocurrent $E_e = 0.5 \text{ mW/cm}^2$, $V_{CE} = 5 \text{ V}$ $E_v = 1000 \text{ lx}$, Normlicht/standard light A, $V_{CE} = 5 \text{ V}$ | I_{PCE} I_{PCE} | 0.8 ... 1.6 3.8 | 1.25 ... 2.5 6.0 | 2.0...4.0 9.5 | ≥ 3.2 15.0 | mA mA |
| Anstiegszeit/Abfallzeit Rise and fall time $I_C = 1 \text{ mA}$, $V_{CC} = 5 \text{ V}$, $R_L = 1 \text{ k}\Omega$ | t_r , t_f | 9 | 12 | 15 | 18 | μs |
| Kollektor-Emitter-Sättigungsspannung Collector-emitter saturation voltage $I_C = I_{PCEmin}^{1)} \times 0.3$ $E_e = 0.5 \text{ mW/cm}^2$ | V_{CEsat} | 200 | 220 | 240 | 260 | mV |
| Stromverstärkung Current gain $E_e = 0.5 \text{ mW/cm}^2$, $V_{CE} = 5 \text{ V}$ | $\frac{I_{PCE}}{I_{PCB}}$ | 110 | 170 | 270 | 430 | – |

1) I_{PCEmin} ist der minimale Fotostrom der jeweiligen Gruppe.

1) I_{PCEmin} is the min. photocurrent of the specified group.


Relative Spectral Sensitivity

$S_{rel} = f(\lambda)$




Photocurrent

$I_{PCE} = f(E_e), V_{CE} = 5 V$




Total Power Dissipation

$P_{tot} = f(T_A)$




Output Characteristics

$I_C = f(V_{CE}), I_B = \text{Parameter}$




Output Characteristics

$I_C = f(V_{CE}), I_B = \text{Parameter}$




Dark Current

$I_{CEO} = f(V_{CE}), E = 0$




Photocurrent

$I_{PCE}/I_{PCE25^\circ} = f(T_A), V_{CE} = 5 V$




Dark Current

$I_{CEO}/I_{CEO25^\circ} = f(T_A), V_{CE} = 25 V, E = 0$




Collector-Emitter Capacitance

$C_{CE} = f(V_{CE}), f = 1 \text{ MHz}, E = 0$




Collector-Base Capacitance

$C_{CB} = f(V_{CB}), f = 1 \text{ MHz}, E = 0$




Emitter-Base Capacitance

$C_{EB} = f(V_{EB}), f = 1 \text{ MHz}, E = 0$




Directional Characteristics

$S_{rel} = f(\varphi)$




Maßzeichnung
Package Outlines



Maße in mm (inch) / Dimensions in mm (inch)

Lötbedingungen
Soldering Conditions
Wellenlöten (TTW)
TTW Soldering

(nach CECC 00802)
 (acc. to CECC 00802)



Published by
OSRAM Opto Semiconductors GmbH
 Wernerwerkstrasse 2, D-93049 Regensburg
www.osram-os.com
 © All Rights Reserved.

EU RoHS and China RoHS compliant product



此产品符合欧盟 RoHS 指令的要求；
 按照中国的相关法规和标准，不含有毒有害物质或元素。

The information describes the type of component and shall not be considered as assured characteristics. Terms of delivery and rights to change design reserved. Due to technical requirements components may contain dangerous substances. For information on the types in question please contact our Sales Organization.

Packing

Please use the recycling operators known to you. We can also help you – get in touch with your nearest sales office. By agreement we will take packing material back, if it is sorted. You must bear the costs of transport. For packing material that is returned to us unsorted or which we are not obliged to accept, we shall have to invoice you for any costs incurred.

Components used in life-support devices or systems must be expressly authorized for such purpose! Critical components ¹, may only be used in life-support devices or systems ² with the express written approval of OSRAM OS.

¹ A critical component is a component used in a life-support device or system whose failure can reasonably be expected to cause the failure of that life-support device or system, or to affect its safety or effectiveness of that device or system.

² Life support devices or systems are intended (a) to be implanted in the human body, or (b) to support and/or maintain and sustain human life. If they fail, it is reasonable to assume that the health of the user may be endangered.