

SKINDICHT®

Accessories and gland components



SKINDICHT® O O-sealing ring Perbunan

O-sealing rings are used for reliable sealing against oil, dust and water on connection thread of gland similar components.

Material: perbunan (NBR) black
Temperature range:
-20 °C to +100 °C

SKINDICHT® OV O-sealing ring Viton

O-sealing rings are used for reliable sealing against oil, dust and water on connection thread of gland similar components.

Material: Viton, green
Temperature range:
-20 °C to +200 °C

Viton® = registered trademark of Du Pont de Nemour

Part Number	Type PG-size	Inside Ø x cord reinforcement Ø mm	Pack size pieces
SKINDICHT® O-Perbunan metric			
5310 2000	O M 12	9 x 2	100
5310 2010	O M 16	13 x 2	100
5310 2020	O M 20	17 x 2	100
5310 2030	O M 25	22 x 2	100
5310 2040	O M 32	28 x 2	50
5310 2050	O M 40	36 x 2	50
5310 2060	O M 50	46 x 2	25
5310 2070	O M 63	57 x 2	25
SKINDICHT® O-Viton metric			
5212 2000	OV M 12	9 x 2	100
5212 2010	OV M 16	13 x 2	100
5212 2020	OV M 20	17 x 2	100
5212 2030	OV M 25	22 x 2	100
5212 2040	OV M 32	28 x 2	50
	OV M 40	36 x 2	50