

135 045

135 057

135 069



236-561 to 236-640



HYLEC-ELETTRO GIBI (UK) LIMITED

Unit 4, Trinity Centre, Park Farm Industrial Estate, Wellingborough, Northants. NN8 3ZB.
Tel: Wellingborough (0933) 677633 Telex: 312620 HYLEC G Fax: (0933) 675771

DATA SHEET FOR 'PERFECT' RANGE OF BRASS CABLE GLANDS

MATERIALS:

Gland Body	Nickel plated brass
Internal seal	Neoprene
External O ring	Buna N

PROTECTION OFFERED:

IP 68 to 5 bar
The gland is also fully insulated by means of an internal plastic insert.

NOTEWORTHY FEATURES:

Superior strain relief which does not damage the cable.
Easy to assemble; large clamping ranges.
Range offering both PG and Metric sizes.

DIMENSIONS

PART NO.	CABLE GLAND				LOCKNUT	
	FOR CABLE DIAMETERS MM	MALE THREAD SIZE	THREAD LENGTH MM	WIDTH ACROSS HEXAGON MM	WIDTH ACROSS FLATS MM	THICKNESS MM
236-561	3.0- 6.5	PG 7	5.0	14.0	15.0	2.8
236-573	4.0- 8.0	PG 9	6.0	17.0	18.0	2.8
236-585	5.0-10.0	PG11	6.0	20.0	21.0	3.0
236-597	6.0-12.0	PG13.5	6.5	22.0	23.0	3.0
236-603	10.0-14.0	PG16	6.5	24.0	26.0	3.0
236-615	3.0- 6.0	M12x1.5	10.0	14.0	15.0	2.8
236-627	5.0-10.0	M16x1.5	10.0	17.0	19.0	2.8
236-639	8.0-13.0	M20x1.5	10.0	22.0	24.0	3.0
236-640	11.0-17.0	M25x1.5	11.0	27.0	30.0	3.5

3/93