

3519569

3519570

Data Sheet

Type Number:	55620
System:	Nickel Metal Hydride / KOH Electrolyte
UL Recognition:	MH 13654 (N)
Nominal Voltage [V]:	1,2
Typical Capacity C [mAh]:	220
Nominal Capacity C [mAh]:	200
at 0.2 CA / 1.00 V	
Weight, approx [g]:	7
Coding:	Manufacturing 5 digit code (123 = day/4 = year/5 = vers)
Temperature Ranges [°C]:	min. max.
Storage:	-40 65
Discharge:	-20 65
Charge:	0 65
Dimensions [mm]:	min. max.
Length [l]:	13,9 14,1
Width Facing [w]:	25,45 25,6
Height [h]:	7,1 7,4
Charging Method:	
Normal Charging:	20 mA for 14-16 h
Accelerated Charging (20°C): ..	40 mA for 7-8 h
Fast Charging :	--- mA for --- h *
Trickle Charging :	6 mA
Overcharge (20°C):	20 mA continuous 40 mA 1 year
Charge Retention [%] at 20°C:	90
Capacity available after 1 month storage at 20 °C	
Internal Resistance [Ohm]:	0,8
at charged cells, 20 °C, DC: 0.2 CA/2 CA, (IEC 285)	
Impedance [Ohm]:	0,14
at charged cells, 20 °C, AC: 1 kHz, (IEC 285)	
Typical Capacities [mAh]:	
at 1 CA / 0.90 V	90
at 2 CA / 0.90 V	30
Max. Discharge Current (cont.) [mA]:	300
Life Expectancy (typical):	
IEC Cycle:	1000 Cycles
Trickle Charge:	up to 6 years (20°C)
Trickle Charge:	up to 3 years (45°C)

* ---

