

REVISIONS																											
LTR	DESCRIPTION	DATE (YR-MO-DA)	APPROVED																								

  

REV																														
SHEET																														
REV																														
SHEET																														
REV STATUS OF SHEETS	REV																													
	SHEET	1	2	3	4	5	6	7	8	9																				

  

PMIC N/A  <b>STANDARDIZED MILITARY DRAWING</b>  THIS DRAWING IS AVAILABLE FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE  AMSC N/A	PREPARED BY <i>Christopher A. Ravel</i> CHECKED BY <i>Ray Monnin</i> APPROVED BY <i>DA Di Enzo</i> DRAWING APPROVAL DATE 26 AUGUST 1988 REVISION LEVEL	DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444  MICROCIRCUITS, LINEAR, VOLTAGE REGULATOR, MONOLITHIC SILICON  <table style="width: 100%;"> <tr> <td style="width: 10%;">SIZE <b>A</b></td> <td style="width: 40%;">CAGE CODE <b>67268</b></td> <td style="width: 50%;"><b>5962-87770</b></td> </tr> <tr> <td colspan="3">SHEET 1 OF 9</td> </tr> </table>	SIZE <b>A</b>	CAGE CODE <b>67268</b>	<b>5962-87770</b>	SHEET 1 OF 9		
SIZE <b>A</b>	CAGE CODE <b>67268</b>	<b>5962-87770</b>						
SHEET 1 OF 9								

DESC FORM 193  
SEP 87

U.S. GOVERNMENT PRINTING OFFICE: 1987 — 748-129/60911

5962-E685

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

# 1. SCOPE

1.1 Scope. This drawing describes device requirements for class B microcircuits in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices".

1.2 Part number. The complete part number shall be as shown in the following example:

5962-87770	01	C	X
-----	-----	-----	-----
Drawing number	Device type (1.2.1)	Case outline (1.2.2)	Lead finish per MIL-M-38510

1.2.1 Device type. The device type shall identify the circuit function as follows:

Device type	Generic number	Circuit function
01	1532	Voltage regulator

1.2.2 Case outlines. The case outlines shall be as designated in appendix C of MIL-M-38510, and as follows:

Outline letter	Case outline
C	D-1 (14-lead, .785" x .310" x .200") dual-in-line package
I	A-2 (10-lead, .370" x .185") can package

## 1.3 Absolute maximum ratings.

Input supply voltage - - - - -	50 V dc
Output current - - - - -	250 mA
Reference current - - - - -	25 mA
Zener current (case C only) - - - - -	100 mA
Storage temperature range - - - - -	-65°C to +150°C
Maximum power dissipation:	
Case I - - - - -	800 mW 1/
Case C - - - - -	1000 mW 2/

## 1.4 Recommended operating conditions.

Supply voltage range (V+) - - - - -	4.5 V dc minimum to 50 V dc maximum.
Ambient operating temperature range (T <sub>A</sub> ) - - - - -	-55°C to +125°C

- 1/ Derate above +25°C, 6.4 mW/°C.  
2/ Derate above +25°C, 8 mW/°C

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE <b>A</b>	5962-87770	
	REVISION LEVEL		SHEET 2

DESC FORM 193A  
SEP 87

U. S. GOVERNMENT PRINTING OFFICE: 1988-549-904

## 2. APPLICABLE DOCUMENTS

2.1 Government specification and standard. Unless otherwise specified, the following specification and standard, of the issue listed in that issue of the Department of Defense Index of Specifications and Standards specified in the solicitation, form a part of this drawing to the extent specified herein.

### SPECIFICATION

#### MILITARY

MIL-M-38510 - Microcircuits, General Specification for.

### STANDARD

#### MILITARY

MIL-STD-883 - Test Methods and Procedures for Microelectronics.

(Copies of the specification and standard required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Order of precedence. In the event of a conflict between the text of this drawing and the references cited herein, the text of this drawing shall take precedence.

## 3. REQUIREMENTS

3.1 Item requirements. The individual item requirements shall be in accordance with 1.2.1 of MIL-STD-883, "Provisions for the use of MIL-STD-883 in conjunction with compliant non-JAN devices" and as specified herein.

3.2 Design, construction, and physical dimensions. The design, construction, and physical dimensions shall be as specified in MIL-M-38510 and herein.

3.2.1 Terminal connections. The terminal connections shall be as specified on figure 1.

3.2.2 Logic diagram. The logic diagram shall be as specified on figure 2.

3.2.3 Case outlines. The case outlines shall be in accordance with 1.2.2 herein.

3.3 Electrical performance characteristics. Unless otherwise specified, the electrical performance characteristics are as specified in table I and apply over the full ambient operating temperature range.

3.4 Marking. Marking shall be in accordance with MIL-STD-883 (see 3.1 herein). The part shall be marked with the part number listed in 1.2 herein. In addition, the manufacturer's part number may also be marked as listed in 6.4 herein.

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	<b>SIZE</b> <b>A</b>		5962-87770
		<b>REVISION LEVEL</b>	<b>SHEET</b> 3

DESC FORM 193A  
SEP 87

☆ U. S. GOVERNMENT PRINTING OFFICE: 1988-549 904

TABLE 1. Electrical performance characteristics.

Test	Symbol	Conditions $-55^{\circ}\text{C} \leq T_A \leq +125^{\circ}\text{C}$ $V_{IN} = 10\text{ V}$ , $V_{OUT} = 5\text{ V}$ $I_{OUT} = 1\text{ mA}$	Group A subgroups	Limits		Unit
				Min	Max	
Output voltage	$V_{OUT}$		1,2,3	2.0	38	V
Maximum output current	$I_{MAX}$	$T_A = +25^{\circ}\text{C}$ ; $V_{OUT} = 0\text{ V}$ $R_{SC} = 0\Omega$	1		-250	mA
Min ( $V_{IN} - V_{OUT}$ )	$V_{MIN}$	$I_{OUT} = 100\text{ mA}$ ; $T_A = +25^{\circ}\text{C}$	1		2	V
Reference voltage	$V_{REF}$		1	2.4	2.6	V
			2,3	2.35	2.65	
Reference short circuit current	$I_{RSC}$	$T_A = +25^{\circ}\text{C}$ $V_{REF} = 0\text{ V}$	1		25	mA
Line regulation	$V_{LR1}$	$8\text{ V} \leq V_{IN} \leq 20\text{ V}$ $I_{OUT} = 25\text{ mA}$	1,2,3		.02	% / V
	$V_{LR2}$	$8\text{ V} \leq V_{IN} \leq 40\text{ V}$			.01	
Load regulation	$I_{LR1}$	$1\text{ mA} \leq I_{OUT} \leq 25\text{ mA}$	1,2,3		.004	% / mA
	$I_{LR2}$	$1\text{ mA} \leq I_{OUT} \leq 100\text{ mA}$			.005	
Current limit sense voltage	$V_{CLS}$	$R_{SC} = 100\Omega$ $V_{OUT} = 0\text{ V}$	1,2,3	.06	.10	V
Shutdown voltage threshold	$V_{SVT}$		1,2,3	.4	1.0	V
Shutdown source current	$I_{SS}$	$V_{OUT} = 38\text{ V}$	1,2,3	100	300	$\mu\text{A}$
Zener voltage	$V_Z$	C package only	1,2,3	6.0	7.0	V

**STANDARDIZED  
MILITARY DRAWING**

DEFENSE ELECTRONICS SUPPLY CENTER  
DAYTON, OHIO 45444

SIZE  
**A**

5962-87770

REVISION LEVEL

SHEET  
4

DESC FORM 193A  
SEP 87

\* U. S. GOVERNMENT PRINTING OFFICE: 1988 - 549 904

TABLE I. Electrical performance characteristics - Continued.

Test	Symbol	Conditions -55°C < T <sub>A</sub> < +125°C V <sub>IN</sub> = 10 V, V <sub>OUT</sub> = 5 V I <sub>OUT</sub> = 1 mA	Group A subgroups	Limits		Unit
				Min	Max	
Standby current	I <sub>SC</sub>	V <sub>IN</sub> = 40 V	1,2,3		3.5	mA
Error amplifier offset voltage	V <sub>I0</sub>		1,2,3		10	mV
Error amplifier input bias current	I <sub>B</sub>		1,2,3		15	μA
Open loop gain	A <sub>VOL</sub>	T <sub>A</sub> = +25°C	4	60	75	dB

3.5 Certificate of compliance. A certificate of compliance shall be required from a manufacturer in order to be listed as an approved source of supply in 6.4. The certificate of compliance submitted to DESC-ECS prior to listing as an approved source of supply shall state that the manufacturer's product meets the requirements of MIL-STD-883 (see 3.1 herein) and the requirements herein.

3.6 Certificate of conformance. A certificate of conformance as required in MIL-STD-883 (see 3.1 herein) shall be provided with each lot of microcircuits delivered to this drawing.

3.7 Notification of change. Notification of change to DESC-ECS shall be required in accordance with MIL-STD-883 (see 3.1 herein).

3.8 Verification and review. DESC, DESC's agent, and the acquiring activity retain the option to review the manufacturer's facility and applicable required documentation. Offshore documentation shall be made available onshore at the option of the reviewer.

#### 4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection procedures shall be in accordance with section 4 of MIL-M-38510 to the extent specified in MIL-STD-883 (see 3.1 herein).

4.2 Screening. Screening shall be in accordance with method 5004 of MIL-STD-883, and shall be conducted on all devices prior to quality conformance inspection. The following additional criteria shall apply:

a. Burn-in test, method 1015 of MIL-STD-883.

(1) Test condition A, B, C or D using the circuit submitted with the certificate of compliance (see 3.5 herein).

(2) T<sub>A</sub> = +125°C, minimum.

b. Interim and final electrical test parameters shall be as specified in table II herein, except interim electrical parameter tests prior to burn-in are optional at the discretion of the manufacturer.

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE <b>A</b>		5962-87770
		REVISION LEVEL	SHEET 5

Case outlines	Case C	Case I
Terminal number	Terminal symbol	
1	NC	I SENSE
2	I LIMIT	INV INPUT
3	I SENSE	NI INPUT
4	INV INPUT	VREF
5	NI INPUT	V-
6	VREF	VOUT
7	V-	SHUTDOWN
8	SHUTDOWN	V <sub>C</sub> AND V <sub>+</sub>
9	V <sub>Z</sub>	FREQ COMP
10	VOUT	I LIMIT
11	V <sub>C</sub>	---
12	V <sub>+</sub>	---
13	FREQ COMP	---
14	NC	---

NC = No connection

FIGURE 1. Terminal connections.

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE <b>A</b>	5962-87770	
		REVISION LEVEL	SHEET 6

DESC FORM 193A  
SEP 87

★ U. S. GOVERNMENT PRINTING OFFICE: 1988-549-904



4.3 Quality conformance inspection. Quality conformance inspection shall be in accordance with method 5005 of MIL-STD-883 including groups A, B, C, and D inspections. The following additional criteria shall apply.

4.3.1 Group A inspection.

- a. Tests shall be as specified in table II herein.
- b. Subgroups 5, 6, 7, 8, 9, 10 and 11 in table I, method 5005 of MIL-STD-883 shall be omitted.

4.3.2 Groups C and D inspections.

- a. End-point electrical parameters shall be as specified in table II herein.
- b. Steady-state life test conditions, method 1005 of MIL-STD-883.
  - (1) Test condition A, B, C, or D using the circuit submitted with the certificate of compliance (see 3.5 herein).
  - (2)  $T_A = +125^{\circ}\text{C}$ , minimum.
  - (3) Test duration: 1,000 hours, except as permitted by method 1005 of MIL-STD-883.

TABLE II. Electrical test requirements.

MIL-STD-883 test requirements	Subgroups (per method 5005, table I)
Interim electrical parameters (method 5004)	---
Final electrical test parameters (method 5004)	*1, 2, 3, 4
Group A test requirements (method 5005)	1, 2, 3, 4
Groups C and D end-point electrical parameters (method 5005)	1, 2, 3

\* PDA applies to subgroup 1.

5. PACKAGING

5.1 Packaging requirements. The requirements for packaging shall be in accordance with MIL-M-38510.

6. NOTES

6.1 Intended use. Microcircuits conforming to this drawing are intended for use when military specifications do not exist and qualified military devices that will perform the required function are not available for OEM application. When a military specification exists and the product covered by this drawing has been qualified for listing on QPL-38510, the device specified herein will be inactivated and will not be used for new design. The QPL-38510 product shall be the preferred item for all applications.

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	<b>SIZE</b> <b>A</b>		5962-87770
		<b>REVISION LEVEL</b>	<b>SHEET</b> 8

6.2 Replaceability. Microcircuits covered by this drawing will replace the same generic device covered by a contractor-prepared specification or drawing.

6.3 Comments. Comments on this drawing should be directed to DESC-ECS, Dayton, Ohio 45444, or telephone 513-296-5375.

6.4 Approved source of supply. An approved source of supply is listed herein. Additional sources will be added as they become available. The vendor listed herein has agreed to this drawing and a certificate of compliance (see 3.5 herein) has been submitted to DESC-ECS.

Military drawing part number	Vendor CAGE number	Vendor similar part number <u>1/</u>
5962-8777001CX	34333	SG1532J/883B
5962-8777001IX	34333	SG1532T/883B

1/ Caution. Do not use this number for item acquisition. Items acquired to this number may not satisfy the performance requirements of this drawing.

Vendor CAGE  
number

34333

Vendor name  
and address

Silicon General  
11861 Western ave  
Garden Grove, CA 92641

<b>STANDARDIZED MILITARY DRAWING</b> DEFENSE ELECTRONICS SUPPLY CENTER DAYTON, OHIO 45444	SIZE <b>A</b>		5962-87770
		REVISION LEVEL	SHEET 9

DESC FORM 193A  
SEP 87

\* U. S. GOVERNMENT PRINTING OFFICE: 1988-549-904