

DESCRIPTION

The HYM572A404A is a 4M x 72-bit EDO mode CMOS DRAM module consisting of eighteen HY5116404A in 24/26 SOJ or TSOP-II and one 2048 bit EEPROM on a 168 pin glass-epoxy printed circuit board. 0.1μF and 0.01μF decoupling capacitors are mounted for each DRAM. The HYM572A404AKG/ATKG/ASLKG/ASLTGK is Gold plated socket type Dual In-line Memory Modules suitable for easy interchange and addition of 32M byte memory.

FEATURES

- Low power dissipation
Max. self-refresh 29.7mW (SL-part)
Max. battery back-up 59.4mW (SL-part)
Max. CMOS standby 39.6mW (SL-part)
99.0mW

Max. TTL standby 198.0mW

Max. operating

Speed	Power
60	8.91W
70	7.92W
80	6.93W

- Single power supply of 5V± 10%
- TTL compatible inputs and outputs
- Fast access time


Speed	tRAC	tCAC	tHPC
60	60ns	15ns	25ns
70	70ns	18ns	30ns
80	80ns	20ns	35ns

- EDO mode operation
- CAS-before-RAS, RAS-only, Hidden refresh and Self-refresh
- 4096 refresh cycles / 256ms (SL-part)
4096 refresh cycles / 64ms
- Serial Presence Detect

PIN DESCRIPTION

RAS0,RAS2	Row Address Strobe
CAS0 - CAS7	Column Address Strobe
WE0,WE2	Write Enable
OE0,OE2	Output Enable
A0-A11	Address Input
DQ0-DQ71	Data Input/Output
SLC	Serial PD Clock Input
SDA	Serial PD Data Input/Output
SA0-SA2	Serial PD Device Add. Input
Vcc	Power (+ 5V)
Vss	Ground

PIN CONNECTION



This document is a general product description and is subject to change without notice. Hyundai electronics does not assume any responsibility for use of circuits described. No patent licences are implied.
1EC07-10-JAN96

4675088 0005834 828

©1996 Hyundai Semiconductor
139

PIN NAME

#	NAME	#	NAME	#	NAME	#	NAME
1	Vss	43	Vss	85	Vss	127	Vss
2	DQ0	44	OE2	86	DQ36	128	NC
3	DQ1	45	RAS2	87	DQ37	129	NC
4	DQ2	46	CAS2	88	DQ38	130	CAS6
5	DQ3	47	CAS3	89	DQ39	131	CAS7
6	Vcc	48	WE2	90	Vcc	132	NC
7	DQ4	49	Vcc	91	DQ40	133	Vcc
8	DQ5	50	NC	92	DQ41	134	NC
9	DQ6	51	NC	93	DQ42	135	NC
10	DQ7	52	DQ18	94	DQ43	136	DQ54
11	DQ8	53	DQ19	95	DQ44	137	DQ55
12	Vss	54	Vss	96	Vss	138	Vss
13	DQ9	55	DQ20	97	DQ45	139	DQ56
14	DQ10	56	DQ21	98	DQ46	140	DQ57
15	DQ11	57	DQ22	99	DQ47	141	DQ58
16	DQ12	58	DQ23	100	DQ48	142	DQ58
17	DQ13	59	Vcc	101	DQ49	143	Vcc
18	Vcc	60	DQ24	102	Vcc	144	DQ60
19	DQ14	61	NC	103	DQ50	145	NC
20	DQ15	62	NC	104	DQ51	146	NC
21	DQ16	63	NC	105	DQ52	147	NC
22	DQ17	64	Vss	106	DQ53	148	Vss
23	Vss	65	DQ25	107	Vss	149	DQ61
24	NC	66	DQ26	108	NC	150	DQ62
25	NC	67	DQ27	109	NC	151	DQ63
26	Vcc	68	Vss	110	Vcc	152	Vss
27	WE0	69	DQ28	111	NC	153	DQ64
28	CAS0	70	DQ29	112	CAS4	154	DQ65
29	CAS1	71	DQ30	113	CAS5	155	DQ66
30	RAS0	72	DQ31	114	NC	156	DQ67
31	OE0	73	Vcc	115	NC	157	Vcc
32	Vss	74	DQ32	116	Vss	158	DQ68
33	A0	75	DQ33	117	A1	159	DQ69
34	A2	76	DQ34	118	A3	160	DQ70
35	A4	77	DQ35	119	A5	161	DQ71
36	A6	78	Vss	120	A7	162	Vss
37	A8	79	NC	121	A9	163	NC
38	A10	80	NC	122	A11	164	NC
39	NC	81	NC	123	NC	165	SA0
40	Vcc	82	SDA	124	Vcc	166	SA1
41	Vcc	83	SCL	125	NC	167	SA2
42	NC	84	Vcc	126	NC	168	Vcc

4675088 0005835 764

SERIAL PD BYTE DEFINITION

BYTE NUMBER	FUNCTION DESCRIBED	FUNCTION	VALUE
Byte 0	Number of Byte written during module production	15 Bytes	0Fh
Byte 1	Total Byte of Serial Presence Detect Device	256 Bytes	08h
Byte 2	Memory Type	EDO	02h
Byte 3	Number of ROW Addresses	12	0Ch
Byte 4	Number of COLUMN Addresses	10	0Ah
Byte 5	Number of Banks	1 Bank	01h
Byte 6	Module Data Width	72bit	48h
Byte 7	Module Data Width(Continued)	Not Used	00h
Byte 8	Module Interface Levels	TTL	00h
Byte 9	tRAC	60ns 70ns 80ns	3Ch 46h 50h
Byte 10	tCAC	15ns 18ns 20ns	0Fh 12h 14h
Byte 11	Module Configuration Type	ECC	02h
Byte 12	Refresh Rate/Type	Normal(15.6 μ s) SL-Part(62.5 μ s)	00h 84h
Byte 13	Primary DRAM Width	x4	04h
Byte 14	Error Checking DRAM Width	x4	04h
Byte 15 - 255	Undefined	Undefined	Undefined

NOTE:

1. Serial PD interface is standard IIC architecture.
2. Pull-up resistors(4.7K typical value) are required on all open collector bus devices (SCL and SDA).
3. Current sink capability on SCL and SDA (IOL max) must be at least 3ma to maintain a valid low level.

IIC BUS INTERFACE


SYMBOL	RATING	NOTE
C _{MAX}	400pF	1
f _{MAX}	80 KHz(3.3V) 100 KHz(5.0V)	2
IOL _{MAX}	3mA	

NOTE:

1. The maximum number of devices connected on the IIC bus is controlled by the maximum allowable capacitance which is 400pF per line.
2. The maximum IIC system clock frequency depends on Vcc.

■ 4675088 0005836 6T0 ■

BLOCK DIAGRAM



4675088 0005837 537

ABSOLUTE MAXIMUM RATINGS

SYMBOL	PARAMETER	RATING	UNIT
TA	Ambient Temperature	0 to 70	°C
TSTG	Storage Temperature	-55 to 125	°C
VIN, VOUT	Voltage on Any Pin Relative to Vss	-1.0 to 7.0	V
VCC	Voltage on Vcc Relative to Vss	-1.0 to 7.0	V
Ios	Short Circuit Output Current	50	mA
Pd	Power Dissipation	18	W

NOTE : Operation at or above Absolute Maximum Ratings can adversely affect device reliability.

RECOMMENDED DC OPERATING CONDITIONS

(TA= 0°C to 70°C)

SYMBOL	PARAMETER	MIN.	TYP.	MAX.	UNIT
VCC	Supply Voltage	4.5	5.0	5.5	V
VIH	Input High Voltage	2.4	-	VCC+ 1.0	V
VIL	Input Low Voltage	-1.0	-	0.8	V

NOTE : All voltages are referenced to Vss.

4675088 0005838 473

DC CHARACTERISTICS

(TA= 0°C to 70°C, VCC= 5V± 10%, VSS= 0V, unless otherwise noted.)

SYMBOL	PARAMETER	TEST CONDITIONS	SPEED/ POWER	MIN.	MAX.	UNIT	NOTE
ILI	Input Leakage Current (Any Input Pin)	VSS ≤ VIN ≤ VCC+ 1.0, other pins not under test= VSS		-180	180	μA	
ILO	Output Leakage Current (High Impedance State)	VSS ≤ VOUT ≤ VCC, RAS & CAS at VIH		-10	10	μA	
ICC1	VCC Supply Current, Operating	trc= trc (min.)	60 70 80	-	1620 1440 1260	mA	1,2,3
ICC2	VCC Supply Current, TTL Standby	RAS & CAS at VIH, other inputs ≥ VSS		-	36	mA	
ICC3	VCC Supply Current, RAS-only refresh	trc= trc (min.)	60 70 80	-	1620 1440 1260	mA	1,3
ICC4	VCC Supply Current, EDO mode	thpc= thpc (min.)	60 70 80	-	1800 1620 1440	mA	1,2,3
ICC5	VCC Supply Current, CMOS Standby	RAS & CAS ≥ VCC-0.2V	SL-part	-	18 7.2	mA	
ICC6	VCC Supply Current, CAS-before-RAS refresh	trc= trc (min.)	60 70 80	-	1620 1440 1260	mA	1,3
ICC7	VCC Supply Current, Battery Back Up (SL-part only)	trc= 62.5μs CAS= CBR cycling or 0.2V WE= VCC-0.2V, A0-A11= VCC - 0.2V or 0.2V DQ0-DQ71= VCC - 0.2V, 0.2V or open	trAS ≤ 300ns	-	6.3	mA	1,4,5
			trAS ≤ 1μs	-	10.8		
ICC8	VCC Supply Current, Self Refresh (SL-part)	RAS & CAS= VIL OE & WE & A0-A11= VCC-0.2V or 0.2V DQ0-DQ71= VCC - 0.2V, 0.2V or open		-	5.4	mA	5
VOL	Output Low Voltage	IOL= 4.2mA		-	0.4	V	
VOH	Output High Voltage	IOH= -5mA		2.4	-	V	

NOTE :

1. ICC1, ICC3, ICC4, ICC6 and ICC7 depend on cycle rate.
2. ICC1, ICC3, ICC4, and ICC6 depend on output loading. Specified values are obtained with the output open.
3. ICC is specified as average current. For ICC1, ICC3 and ICC6, address can be changed maximum two times while RAS= VIL. For ICC4, address can be changed maximum once while CAS= VIH.
4. trAS(max.)= 1μs is only applied to refresh of battery backup but trAS(max.)= 10μs is applied to normal functional operatin.
5. ICC5(max.)= 7.2mA, ICC7 and ICC8 are applied to SL-part only (HYM572A404ASLKG/ASLTKG).

■ 4675088 0005839 30T ■

AC CHARACTERISTICS

(TA= 0°C to 70°C, VCC= 5V± 10%, VSS = 0V, unless otherwise noted.) NOTE : 1, 2, 3

#	SYMBOL	PARAMETER	HYM572A404A K-Series						UNIT	NOTE
			-60		-70		-80			
			MIN.	MAX.	MIN.	MAX.	MIN.	MAX.		
1	tRC	Random Read or Write Cycle Time	110	-	130	-	150	-	ns	
2	tRWC	Read-Modify-Write Cycle Time	155	-	180	-	200	-	ns	
3	tHPC	EDO Mode Cycle Time	25	-	30	-	35	-	ns	
4	tHPRWC	EDO Mode Read-Modify-Write Cycle Time	75	-	85	-	95	-	ns	
5	tRAC	Access Time from RAS	-	60	-	70	-	80	ns	4,9,10
6	tCAC	Access Time from CAS	-	15	-	18	-	20	ns	4,9
7	tAA	Access Time from Column Address	-	30	-	35	-	40	ns	4,10
8	tCPA	Access Time from CAS Precharge	-	35	-	40	-	45	ns	4
9	tOLZ	CAS to Output Low Impedance	3	-	3	-	3	-	ns	4
10	tCEZ	Output Buffer Turn-off Delay	3	15	3	18	3	20	ns	5
11	tT	Transition Time (Rise and Fall)	2	50	2	50	2	50	ns	3
12	tRP	RAS Precharge Time	40	-	50	-	60	-	ns	
13	tRAS	RAS Pulse Width	60	10K	70	10K	80	10K	ns	
14	tRASP	RAS Pulse Width (EDO Mode)	60	200K	70	200K	80	200K	ns	
15	tRSH	RAS Hold Time	15	-	18	-	20	-	ns	
16	tCSH	CAS Hold Time	45	-	50	-	55	-	ns	
17	tCAS	CAS Pulse Width	11	10K	14	10K	17	10K	ns	
18	tRCD	RAS to CAS Delay	20	45	20	52	20	60	ns	9
19	tRAD	RAS to Column Address Delay Time	15	30	15	35	17	40	ns	10
20	tCRP	CAS to RAS Precharge Time	5	-	5	-	5	-	ns	
21	tCP	CAS Precharge Time	10	-	12	-	14	-	ns	
22	tASR	Row Address Set-up Time	0	-	0	-	0	-	ns	
23	tRAH	Row Address Hold Time	10	-	10	-	12	-	ns	
24	tASC	Column Address Set-up Time	0	-	0	-	0	-	ns	
25	tCAH	Column Address Hold Time	10	-	10	-	15	-	ns	
26	tAR	Column Address Hold Time from RAS	50	-	55	-	60	-	ns	
27	tRAL	Column Address to RAS Lead Time	30	-	35	-	40	-	ns	
28	tRCS	Read Command Set-up Time	0	-	0	-	0	-	ns	
29	tRCH	Read Command Hold Time Referenced to CAS	0	-	0	-	0	-	ns	6
30	tRRH	Read Command Hold Time Referenced to RAS	0	-	0	-	0	-	ns	6
31	tWCH	Write Command Hold Time	10	-	10	-	15	-	ns	
32	tWCR	Write Command Hold Time from RAS	50	-	55	-	60	-	ns	
33	tWP	Write Command Pulse Width	10	-	10	-	15	-	ns	
34	tRWL	Write Command to RAS Lead Time	15	-	18	-	20	-	ns	
35	tCWL	Write Command to CAS Lead Time	15	-	18	-	20	-	ns	
36	tDS	Data-In Set-up Time	0	-	0	-	0	-	ns	7
37	tDH	Data-In Hold Time	10	-	10	-	10	-	ns	7
38	tDHR	Data-In Hold Time Referenced to RAS	50	-	50	-	55	-	ns	
39	tREF	Refresh Period (4096 cycles)	SL-part	- 64	- 64	- 64	- 64	- 64	ms	12
				256	256	256	256	256	ms	
40	tWCS	Write Command Set-up Time	0	-	0	-	0	-	ns	8

4675088 0005840 021

AC CHARACTERISTICS

(continued)

Continued

#	SYMBOL	PARAMETER	HYM572A404A K-Series						UNIT	NOTE
			-60		-70		-80			
			MIN.	MAX.	MIN.	MAX.	MIN.	MAX.		
41	tCWD	CAS to WE Delay Time	40	-	45	-	50	-	ns	8
42	tRWD	RAS to WE Delay Time	80	-	95	-	105	-	ns	8
43	tAWD	Column Address to WE Delay Time	50	-	60	-	65	-	ns	8
44	tCSR	CAS Set-up Time (CBR Cycle)	5	-	5	-	5	-	ns	
45	tCHR	CAS Hold Time (CBR Cycle)	10	-	10	-	10	-	ns	
46	tRPC	RAS to CAS Precharge Time	5	-	5	-	5	-	ns	
47	tCPT	CAS Precharge Time (CBR Counter Test)	20	-	25	-	25	-	ns	
48	tROH	RAS Hold Time Reference to OE	10	-	10	-	10	-	ns	
49	tOEA	OE Access Time	-	15	-	18	-	20	ns	
50	tOED	OE to Data Delay	15	-	18	-	20	-	ns	
51	tOEZ	Output Buffer Turn Off Delay Time from OE	3	15	3	18	3	20	ns	5
52	tOEH	OE Command Hold Time	15	-	18	-	20	-	ns	
53	tCPWD	WE Delay Time from CAS Precharge	55	-	65	-	70	-	ns	8
54	tRHCP	RAS Hold Time from CAS Precharge	35	-	40	-	45	-	ns	
55	tWRP	WE to RAS Precharge Time (CBR Cycle)	10	-	10	-	10	-	ns	
56	tWRH	WE to RAS Hold time (CBR Cycle)	10	-	10	-	10	-	ns	
57	tRASS	RAS Pulse Width (Self Refresh Cycle)	100	-	100	-	100	-	μs	
58	tRPS	RAS Precharge Time (Self Refresh Cycle)	90	-	110	-	130	-	ns	
59	tCHS	CAS Hold Time (Self Refresh Cycle)	-50	-	-50	-	-50	-	ns	
60	tDOH	Output Data Hold Time	5	-	5	-	5	-	ns	
61	tREZ	Output Buffer Turn-off Delay (RAS)	3	15	3	18	3	20	ns	5,15
62	tWEZ	Output Buffer Turn-off Delay (WE)	3	15	3	18	3	20	ns	5
63	tWPE	WE Pulse Width for Output Disable	5	-	8	-	10	-	ns	
64	tOEP	OE Pulse Width for Output Disable	5	-	8	-	10	-	ns	
65	tOCH	OE Low to CAS High Delay Time	0	-	0	-	0	-	ns	
66	tCHO	CAS High to OE High Hold Time	5	-	8	-	10	-	ns	
67	tWED	WE to Data Delay Time	15	-	18	-	20	-	ns	

4675088 0005841 T68

NOTE :

1. An initial pause of 200 μ s is required after power-up followed by 8 RAS cycles before proper device operation is achieved. In case of using internal refresh counter, a minimum of 8 CAS-before-RAS initialization cycles instead of 8 RAS-only refresh cycles are required. The device should be carefully initialized to be prevented from being entered into multi bit test mode.
2. If RAS= Vss during power-up, the HYM572A404A could begin an active cycle. This condition results in higher power-up current than necessary demands from the power-up. It is recommended that RAS and CAS track with Vcc during power-up or be held at a valid VIH in order to minimize the power-up current.
3. Refer to the HYS116404A data sheet for detailed information.
4. Measured with a load equivalent to 2 TTL loads and 100pF. (VOH= 2.0V,VOL= 0.8V)
5. tCEZ(max.), tOEZ(MAX), tREZ(MAX) and tWEZ(MAX) define the time at which the output achieves the open circuit condition and is not referenced to output voltage levels.
6. Either tRCH or tRRH must be satisfied for a read cycle.
7. These parameters are referenced to CAS leading edge in early write cycles and to WE leading edge in late write or read-modify-write cycles.
8. twCS is not a restrictive operating parameter. It is included in the data sheet as electrical characteristics only. If twCS $\geq$ twCS(min.), the cycle is an early write cycle and data out pin will remain open circuit (high impedance) through the entire cycle.
9. Operation within the tRCD(max.) limit insures that tRAQ(max.) can be met. tRCD(max.) is specified as a reference point only. If tRCD is greater than the specified tRCD(max.) limit, then access time is controlled by tCAC.
10. Operation within the tRAD(max.) limit insures that tRAQ(max.) can be met. tRAD(max.) is specified as a reference point only. If tRAD is greater than the specified tRAD(max.) limit, then access time is controlled by tAA.
11. Measured with the specified current load and 100pF.
12. A burst of 4096 CAS-before-RAS refresh cycles must be executed within 64ms after exiting self refresh (for SL-part).
13. If tCWD $\geq$ twCS(MIN.), tRWD $\geq$ tRWD(MIN.), tAWD $\geq$ tAWD(MIN.) and tCPWD $\geq$ tCPWD(MIN.), the cycle is a read modify write cycle and the data output will contain data read from the selected cell. If neither of the above conditions are met, the condition of the data out (at access time and until CAS goes back to VIH) is indeterminated.
14. In CAS before RAS self refresh mode.
In case of using distributed CAS before RAS refresh, refresh 4096 times during a 256ms after reset
In case of using burst CAS before RAS refresh, refresh 4096 times during a 64ms after reset
In case of using RAS only refresh, refresh against all refresh address during a 64ms after reset
15. If RAS goes to high before CAS high going, the open circuit condition of the output is achieved by CAS high going. If CAS goes to high before RAS high going, the open circuit condition of the output is achieved by RAS high going.

CAPACITANCE


(TA= 25°C, VCC= 5V $\pm$ 10%, VSS= 0V, f= 1MHz, unless otherwise noted.)

SYMBOL	PARAMETER	TYP.	MAX.	UNIT
CIN1	Input Capacitance (A0-A11)	-	139	pF
CIN2	Input Capacitance (WE0,WE2,OE0,OE2)	-	70	pF
CIN3	Input Capacitance (RAS0, RAS2)	-	70	pF
CIN4	Input Capacitance (CAS0-CAS7)	-	25	pF
CDQ	Data Input/output Capacitance (DQ0-DQ71)	-	15	pF

4675088 0005842 9T4

PACKAGE INFORMATION

168 pin Unbuffered Dual In-line Memory Module (KG ; Gold plated)



4675088 0005843 830

ORDERING INFORMATION

PART NUMBER	SPEED	POWER	PACKAGE	PLATING
HYM572A404AKG	60/70/80		DIMM	Gold
HYM572A404ASLKG	60/70/80	SL-part	DIMM	Gold
HYM572A404ATKG	60/70/80		DIMM	Gold
HYM572A404ASLTG	60/70/80	SL-part	DIMM	Gold

■ 4675088 0005844 777 ■