



DM75S68/DM85S68/DM75S68A/DM85S68A

16 x 4 Edge Triggered Registers

General Description


These Schottky memories are addressable "D" register files. Any of its 16 four-bit words may be asynchronously read or may be written into on the next clock transition. An input terminal is provided to enable or disable the synchronous writing of the input data into the location specified by the address terminals. An output disable terminal operates only as a TRI-STATE® output control terminal. The addressable register data may be latched at the outputs and retained as long as the output store terminal is held in a low state. This memory storage condition is independent of the state of the output disable terminal.

All input terminals are high impedance at all times, and all outputs have low impedance active drive logic states and the high impedance TRI-STATE condition.

Features

- On-chip output register
- PNP inputs reduce input loading
- Edge triggered write
- High speed—20 ns typ
- All parameters guaranteed over temperature
- TRI-STATE output
- Schottky-clamped for high speed
- Optimized for register stack applications
- Typical power dissipation—350 mW

Logic and Block Diagram



Pin Names

A ₀ –A ₃	Address Inputs
D ₁ –D ₄	Data Inputs
O ₁ –O ₄	Data Outputs
WE	Write Enable
CLK	Write Clock Input
OS	Output Store
OD	Output Disable

O _D	WE	CLK	O _S	MODE	OUTPUTS
0	X	X	0	Output Store	Data From Last Addressed Location
X	0	—	X	Write Data	Dependent on State of OD and OS
0	X	X	1	Read Data	Data Stored in Addressed Location
1	X	X	0	Output Store	High Impedance State
1	X	X	1	Output Disable	High Impedance State

0 = Low Level
1 = High Level
X = Don't Care

TL/F/9233-1

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.

Supply Voltage	7.0V
Input Voltage	5.5V
Output Voltage	5.5V
Storage Temperature Range	-65°C to +150°C
Temperature (Soldering, 10 sec.)	300°C

Operating Conditions

	Min	Max	Units
Supply Voltage, V_{CC}			
DM85S68/DM85S68A	4.75	5.25	V
DM75S68/DM75S68A	4.5	5.5	V
Temperature, T_A			
DM85S68/DM85S68A	0	70	°C
DM75S68/DM75S68A	-55	+125	°C

Electrical Characteristics

over recommended operating free-air temperature range unless otherwise noted (Notes 2 and 3)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
V_{IH}	High Level Input Voltage		2			V
V_{IL}	Low Level Input Voltage				0.8	V
V_{OH}	High Level Output Voltage	$V_{CC} = \text{Min}$				
		$I_{OH} = -2.0 \text{ mA}$, DM75S68/DM75S68A	2.4			V
V_{OL}	Low Level Output Voltage	$V_{CC} = \text{Min}$, $I_{OL} = 16 \text{ mA}$			0.5	V
		DM75S68/DM75S68A			0.45	V
I_{IH}	High Level Input Current	$V_{CC} = \text{Max}$, $V_{IH} = 2.4 \text{ V}$			25	μA
I_I	High Level Input Current at Maximum Voltage	$V_{CC} = \text{Max}$, $V_{IH} = 5.5 \text{ V}$			50	μA
I_{IL}	Low Level Input Current	$V_{CC} = \text{Max}$, $V_{IL} = 0.5 \text{ V}$			-500	μA
		Clock Input			-250	μA
I_{OS}	Short Circuit Output Current (Note 4)	$V_{CC} = \text{Max}$, $V_{OL} = 0 \text{ V}$	-20		-55	mA
I_{CC}	Supply Current	$V_{CC} = \text{Max}$		70	100	mA
V_{IC}	Input Clamp Voltage	$V_{CC} = \text{Min}$, $I_{IN} = -18 \text{ mA}$			-1.2	V
I_{OZ}	TRI-STATE Output Current	$V_{CC} = \text{Max}$			+40	μA
		$V_O = 2.4 \text{ V}$			-40	μA
		$V_O = 0.5 \text{ V}$				

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. Except for "Operating Temperature Range" they are not meant to imply that the devices should be operated at these limits. The table of "Electrical Characteristics" provides conditions for actual device operation.

Note 2: Unless otherwise specified min/max limits apply across the -55°C to +125°C temperature range for the DM75S68/DM75S68A and across the 0°C to +70°C range for the DM85S68/DM85S68A. All typicals are given for $V_{CC} = 5.0 \text{ V}$ and $T_A = 25^\circ\text{C}$.

Note 3: All currents into device pins shown as positive, out of device pins as negative, all voltages referenced to ground unless otherwise noted. All values shown as max or min on absolute value basis.

Note 4: Only one output at a time should be shorted.

Switching Characteristics over recommended operating range of T_A and V_{CC} unless otherwise noted


Symbol	Parameter	DM75S68		DM85S68		DM75S68A		DM85S68A		Units
		Min	Max	Min	Max	Min	Max	Min	Max	
t_{ZH}	Output Enable to High Level		40		35		40		35	ns
t_{ZL}	Output Enable to Low Level		30		24		30		24	ns
t_{HZ}	Output Disable Time from High Level		35		15		35		15	ns
t_{LZ}	Output Disable Time from Low Level		35		18		35		18	ns
t_{AA}	Access Time	Address to Output			55		40		45	ns
t_{OSA}		Output Store to Output			35		30		35	ns
t_{CA}		Clock to Output			50		40		50	ns

Switching Characteristics

over recommended operating range of T_A and V_{CC} unless otherwise noted (Continued)

Symbol	Parameter	DM75S68		DM85S68		DM75S68A		DM85S68A		Units
		Min	Max	Min	Max	Min	Max	Min	Max	
t_{ASC}	Set-Up Time	Address to Clock	25		15		25		15	ns
t_{DSC}		Data to Clock	15		5		15		5	ns
t_{ASOS}		Address to Output Store	40		30		40		10	ns
t_{WESC}		Write Enable Set-Up Time	10		5		10		5	ns
t_{OSSC}		Store before Write	15		10		15		10	ns
t_{AHC}	Hold Time	Address from Clock	15		10		15		10	ns
t_{DHC}		Data from Clock	20		15		20		15	ns
t_{AHOS}		Address from Output Store	10		5		10		2	ns
t_{WEHC}		Write Enable Hold Time	20		15		20		10	ns

Connection Diagram




TL/F/9233-2

Top View

Order Number DM75S68J, DM85S68J,
DM85S68N, DM75S68AJ,
DM85S68AJ or DM85S68AN
See NS Package
Number J18A or N18A

DM75S68/DM85S68/DM75S68A/DM85S68A


AC Test Circuit and Switching Time Waveforms



$C_L = 5.0$ pF for t_{HZ} , t_{LZ}
 $C_L = 30$ pF for all others
 C_L includes probe and jig capacitance
 All diodes are 1N3064


Write Cycle

Clock Set-Up and Hold Time




Read Cycle


Address to Output Access Time




Output Store Access, Set-Up and Hold Time



Clock to Output Access



Output Disable and Enable Time



Note: Input waveforms supplied by pulse generator having the following characteristics: $V = 3.0V$, $t_R \leq 2.5$ ns, $PRR \leq 1.0$ MHz and $Z_{OUT} = 50M$.