


## FEATURES

- \* SELECTED TO SPECIFIC ON-LINE INTENSITY AND RADIANT INTENSITY RANGES
- \* LOW COST MINIATURE PLASTIC END LOOKING PACKAGE
- \* MECHANICALLY AND SPECTRALLY MATCHED TO THE LTR-4206 SERIES OF PHOTOTRANSISTOR
- \* CLEAR TRANSPARENT COLOR PACKAGE

## PACKAGE DIMENSIONS



### NOTES:

1. All dimensions are in millimeters (inches).
2. Tolerance is  $\pm 0.25\text{mm} (.010\text{'})$  unless otherwise noted.
3. Protruded resin under flange is 1.0mm(.039") max.
4. Lead spacing is measured where the leads emerge from the package.
5. Specifications are subject to change without notice.



# LITE-ON TECHNOLOGY CORPORATION

Property of Lite-On Only

## ABSOLUTE MAXIMUM RATINGS AT TA=25°C

PARAMETER	MAXIMUM RATING	UNIT
Power Dissipation	90	mW
Peak Forward Current (300pps, 10 μs pulse)	1	A
Continuous Forward Current	60	mA
Reverse Voltage	5	V
Operating Temperature Range	-40°C to + 85°C	
Storage Temperature Range	-55°C to + 100°C	
Lead Soldering Temperature [1.6mm(.063") From Body]	260°C for 5 Seconds	

## ELECTRICAL OPTICAL CHARACTERISTICS AT TA=25°C

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	TEST CONDITION	BIN NO.
Aperture Radiant Incidence	Ee	3.2	--	6.6	mW/cm <sup>2</sup>	I <sub>F</sub> = 50mA	BIN A
		4.4	--	--			BIN B
Radiant Intensity	I <sub>E</sub>	24.0	--	49.5	mW/sr	I <sub>F</sub> = 50mA	BIN A
		33.0	--	--			BIN B
Peak Emission Wavelength	λ <sub>Peak</sub>	--	850	--	nm	I <sub>F</sub> = 50mA.	
Spectral Line Half-Width	Δλ	--	40	--	nm	I <sub>F</sub> = 50mA	
Forward Voltage	V <sub>F</sub>	--	1.5	1.8	V	I <sub>F</sub> = 50mA	
	V <sub>F</sub>	--	1.8	2.3	V	I <sub>F</sub> = 200mA	
Reverse Current	V <sub>R</sub>	5	--	--	V	I <sub>R</sub> = 10 μA	
Viewing Angle (See FIG.6)	2θ <sub>1/2</sub>	--	25	--	deg.		

## TYPICAL ELECTRICAL / OPTICAL CHARACTERISTICS CURVES

(25°C Ambient Temperature Unless Otherwise Noted)




FIG.1 SPECTRAL DISTRIBUTION




FIG.2 FORWARD CURRENT VS. AMBIENT TEMPERATURE




FIG.3 FORWARD CURRENT VS. FORWARD VOLTAGE




FIG.4 RELATIVE RADIANT INTENSITY VS. AMBIENT TEMPERATURE




FIG.5 RELATIVE RADIANT INTENSITY VS. FORWARD CURRENT




FIG.6 RADIATION DIAGRAM