


N- and P-Channel 30 V (D-S) MOSFET

PRODUCT SUMMARY				
	V _{DS} (V)	R _{DS(on)} (Ω)	I _D (A)	Q _g (Typ)
N-Channel	30	0.065 at V _{GS} = 10 V	4 ^a	2 nC
		0.100 at V _{GS} = 4.5 V	4 ^a	
P-Channel	- 30	0.140 at V _{GS} = - 10 V	- 3.7	2.2 nC
		0.235 at V _{GS} = - 4.5 V	- 2.8	




FEATURES

- Halogen-free According to IEC 61249-2-21 Definition
- TrenchFET® Power MOSFETs
- Compliant to RoHS Directive 2002/95/EC



APPLICATIONS

- DC/DC for Portable Applications
- Load Switch



N-Channel MOSFET P-Channel MOSFET

Ordering Information: Si5504BDC-T1-E3 (Lead (Pb)-free)
Si5504BDC-T1-GE3 (Lead (Pb)-free and Halogen-free)

ABSOLUTE MAXIMUM RATINGS T_A = 25 °C, unless otherwise noted

Parameter	Symbol	N-Channel	P-Channel	Unit
Drain-Source Voltage	V _{DS}	30	- 30	V
Gate-Source Voltage	V _{GS}	± 20		
Continuous Drain Current (T _J = 150 °C)	I _D	4 ^a	- 3.7	A
		3.8	- 2.7	
		3.7 ^{b, c}	- 2.5 ^{b, c}	
		2.6 ^{b, c}	- 1.8 ^{b, c}	
Pulsed Drain Current	I _{DM}	10	- 10	
Source Drain Current Diode Current	I _S	2.5	- 2.5	W
		1.3 ^{b, c}	- 1.3 ^{b, c}	
Maximum Power Dissipation	P _D	3.12	3.1	
		2	2	
		1.5 ^{b, c}	1.5 ^{b, c}	
		0.8 ^{b, c}	0.8 ^{b, c}	
Operating Junction and Storage Temperature Range	T _J , T _{stg}	- 55 to 150		°C
Soldering Recommendations (Peak Temperature) ^{d, e}		260		

THERMAL RESISTANCE RATINGS

Parameter	Symbol	N-Channel		P-Channel		Unit
		Typ.	Max.	Typ.	Max.	
Maximum Junction-to-Ambient ^{b, f}	t ≤ 5 s	R _{thJA}	70	85	70	85
Maximum Junction-to-Foot (Drain)	Steady State	R _{thJF}	33	40	33	40

Notes:

- Package limited.
- Surface mounted on 1" x 1" FR4 board.
- t = 5 s.
- See Reliability Manual for profile. The ChipFET is a leadless package. The end of the lead terminal is exposed copper (not plated) as a result of the singulation process in manufacturing. A solder fillet at the exposed copper tip cannot be guaranteed and is not required to ensure adequate bottom side solder interconnection.
- Rework conditions: manual soldering with a soldering iron is not recommended for leadless components.
- Maximum under steady state conditions is 120 °C/W.

SPECIFICATIONS $T_J = 25^\circ\text{C}$, unless otherwise noted

Parameter	Symbol	Test Conditions	Min.	Typ.	Max.	Unit
Static						
Drain-Source Breakdown Voltage	V_{DS}	$V_{GS} = 0 \text{ V}, I_D = 250 \mu\text{A}$	N-Ch	30		
		$V_{GS} = 0 \text{ V}, I_D = -250 \mu\text{A}$	P-Ch	- 30		
V_{DS} Temperature Coefficient	$\Delta V_{DS}/T_J$	$I_D = 250 \mu\text{A}$	N-Ch		27	
		$I_D = -250 \mu\text{A}$	P-Ch		- 30	
$V_{GS(\text{th})}$ Temperature Coefficient	$\Delta V_{GS(\text{th})}/T_J$	$I_D = 250 \mu\text{A}$	N-Ch		- 5	
		$I_D = -250 \mu\text{A}$	P-Ch		3.5	
Gate Threshold Voltage	$V_{GS(\text{th})}$	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$	N-Ch	1.5		
		$V_{DS} = V_{GS}, I_D = -250 \mu\text{A}$	P-Ch	- 1.5		- 3
Gate-Body Leakage	I_{GSS}	$V_{DS} = 0 \text{ V}, V_{GS} = \pm 20 \text{ V}$	N-Ch		100	
			P-Ch		- 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 30 \text{ V}, V_{GS} = 0 \text{ V}$	N-Ch		1	
		$V_{DS} = -30 \text{ V}, V_{GS} = 0 \text{ V}$	P-Ch		- 1	
		$V_{DS} = 30 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 85^\circ\text{C}$	N-Ch		5	
		$V_{DS} = -30 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 85^\circ\text{C}$	P-Ch		- 5	
On-State Drain Current ^b	$I_{D(\text{on})}$	$V_{DS} \geq 5 \text{ V}, V_{GS} = 10 \text{ V}$	N-Ch	10		
		$V_{DS} \leq -5 \text{ V}, V_{GS} = -10 \text{ V}$	P-Ch	- 10		A
Drain-Source On-State Resistance ^b	$R_{DS(\text{on})}$	$V_{GS} = 10 \text{ V}, I_D = 3.1 \text{ A}$	N-Ch		0.053	0.065
		$V_{GS} = -10 \text{ V}, I_D = -2.1 \text{ A}$	P-Ch		0.112	0.140
		$V_{GS} = 4.5 \text{ V}, I_D = 1 \text{ A}$	N-Ch		0.081	0.100
		$V_{GS} = -4.5 \text{ V}, I_D = -0.43 \text{ A}$	P-Ch		0.188	0.235
Forward Transconductance ^b	g_{fs}	$V_{DS} = 15 \text{ V}, I_D = 3.1 \text{ A}$	N-Ch		5	
		$V_{DS} = -15 \text{ V}, I_D = -2.1 \text{ A}$	P-Ch		3.5	S
Dynamic^a						
Input Capacitance	C_{iss}	N-Channel $V_{DS} = 15 \text{ V}, V_{GS} = 0 \text{ V}, f = 1 \text{ MHz}$	N-Ch		220	
			P-Ch		170	
Output Capacitance	C_{oss}		N-Ch		50	
			P-Ch		50	pF
Reverse Transfer Capacitance	C_{rss}	P-Channel $V_{DS} = -15 \text{ V}, V_{GS} = 0 \text{ V}, f = 1 \text{ MHz}$	N-Ch		25	
			P-Ch		31	
Total Gate Charge	Q_g	$V_{DS} = 15 \text{ V}, V_{GS} = 10 \text{ V}, I_D = 3.6 \text{ A}$	N-Ch		4.5	7
		$V_{DS} = -15 \text{ V}, V_{GS} = -10 \text{ V}, I_D = -2.5 \text{ A}$	P-Ch		4.5	7
Gate-Source Charge	Q_{gs}	N-Channel $V_{DS} = 15 \text{ V}, V_{GS} = 4.5 \text{ V}, I_D = 3.6 \text{ A}$	N-Ch		2	3
			P-Ch		2.2	3.5
		P-Channel $V_{DS} = -15 \text{ V}, V_{GS} = -4.5 \text{ V}, I_D = -2.5 \text{ A}$	N-Ch		0.7	
			P-Ch		0.7	
Gate-Drain Charge	Q_{gd}	$f = 1 \text{ MHz}$	N-Ch		0.7	
			P-Ch		1	
Gate Resistance	R_g	$f = 1 \text{ MHz}$	N-Ch		3	
			P-Ch		13	Ω

Notes:

a. Guaranteed by design, not subject to production testing.







b. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2\%$.






SPECIFICATIONS $T_J = 25^\circ\text{C}$, unless otherwise noted							
Parameter	Symbol	Test Conditions			Min.	Typ.	Max.
Dynamic^a							
Turn-On Delay Time	$t_{d(on)}$	N-Channel $V_{DD} = 15 \text{ V}$, $R_L = 5.8 \Omega$ $I_D \geq 2.6 \text{ A}$, $V_{GEN} = 4.5 \text{ V}$, $R_g = 1 \Omega$ P-Channel $V_{DD} = -15 \text{ V}$, $R_L = 7.5 \Omega$ $I_D \geq -2 \text{ A}$, $V_{GEN} = -4.5 \text{ V}$, $R_g = 1 \Omega$	N-Ch		15	25	ns
Rise Time	t_r		P-Ch		30	45	
Turn-Off Delay Time	$t_{d(off)}$		N-Ch		80	120	
Fall Time	t_f		P-Ch		60	90	
Turn-On Delay Time	$t_{d(on)}$		N-Ch		12	20	
Rise Time	t_r		P-Ch		10	15	
Turn-Off Delay Time	$t_{d(off)}$		N-Ch		25	40	
Fall Time	t_f		P-Ch		10	15	
Drain-Source Body Diode Characteristics							
Continuous Source-Drain Diode Current	I_S	$T_C = 25^\circ\text{C}$ Pulse Diode Forward Current ^a I_{SM} Body Diode Voltage V_{SD} $I_S = 2.6 \text{ A}$, $V_{GS} = 0 \text{ V}$ $I_S = -2 \text{ A}$, $V_{GS} = 0 \text{ V}$ Body Diode Reverse Recovery Time t_{rr} $I_F = 2.6 \text{ A}$, $dI/dt = 100 \text{ A}/\mu\text{s}$, $T_J = 25^\circ\text{C}$ Body Diode Reverse Recovery Charge Q_{rr} $I_F = -2 \text{ A}$, $dI/dt = -100 \text{ A}/\mu\text{s}$, $T_J = 25^\circ\text{C}$ Reverse Recovery Fall Time t_a $I_F = -2 \text{ A}$, $dI/dt = -100 \text{ A}/\mu\text{s}$, $T_J = 25^\circ\text{C}$ Reverse Recovery Rise Time t_b	N-Ch		2.5	A	
			P-Ch		-2.5		
			N-Ch		10	V	
			P-Ch		-10		
			N-Ch		0.8	1.2	nC
			P-Ch		-0.8	-1.2	
			N-Ch		30	50	ns
			P-Ch		20	40	
			N-Ch		20	40	ns
			P-Ch		10	20	
			N-Ch		23		ns
			P-Ch		13		
			N-Ch		7		ns
			P-Ch		7		



Notes:

- a. Guaranteed by design, not subject to production testing.
- b. Pulse test; pulse width $\leq 300 \mu\text{s}$, duty cycle $\leq 2\%$.



Stresses beyond those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.







N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted






N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Source-Drain Diode Forward Voltage

On-Resistance vs. Gate-to-Source Voltage

Threshold Voltage

Single Pulse Power

Safe Operating Area, Junction-to-Ambient

N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted



* The power dissipation P_D is based on $T_{J(\max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

N-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted




P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

Source-Drain Diode Forward Voltage

On-Resistance vs. Gate-to-Source Voltage

Threshold Voltage

Single Pulse Power

* $V_{GS} >$ minimum V_{GS} at which $R_{DS(on)}$ is specified

Safe Operating Area, Junction-to-Ambient

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted

* The power dissipation P_D is based on $T_{J(\max)} = 150$ °C, using junction-to-case thermal resistance, and is more useful in settling the upper dissipation limit for cases where additional heatsinking is used. It is used to determine the current rating, when this rating falls below the package limit.

P-CHANNEL TYPICAL CHARACTERISTICS 25 °C, unless otherwise noted


Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see www.vishay.com/ppg?74483.



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.