



Micro Commercial Components



Micro Commercial Components  
20736 Marilla Street Chatsworth  
CA 91311

Phone: (818) 701-4933  
Fax: (818) 701-4939

# BAV19 THRU BAV21

**500mW  
Small Signal  
Diodes  
120 to 250 Volts**

**DO-35 GLASS**

## Features


- Silicon Epitaxial Planar Diodes
- For General Purpose
- This diode is also available in other case.
- Lead Free Finish/Rohs Compliant (Note1) ("P" Suffix designates Compliant. See ordering information)

## Mechanical Data

- Case: DO-35 Glass Case
- Weight: approx. 0.13g
- Marking : Cathode band and type number
- Moisture Sensitivity Level 1

## Maximum Ratings

Symbol	Rating	Rating	Unit
$V_R$	Continuous Reverse Voltage	BAV19 100 BAV20 150 BAV21 200	V
$V_{RRM}$	Repetitive Peak Reverse Voltage	BAV19 120 BAV20 200 BAV21 250	V
$I_F$	Forward DC Current at $T_{amb}=25^{\circ}C^{(1)}$	250	mA
$I_{F(AV)}$	Rectified Current (Average) Half Wave Rectification with Resist. Load at $T_{amb}=25^{\circ}C^{(1)}$	200	mA
$I_{FRM}$	Repetitive Peak Forward Current at $f > 50Hz, T_{amb}=25^{\circ}C^{(1)}$	625	mA
$I_{FSM}$	Surge Forward Current at $t < 1s, T_j=25^{\circ}C$	1.0	A
$P_{tot}$	Power Dissipation at $T_{amb}=25^{\circ}C^{(2)}$	500	mW
$T_j$	Junction Temperature	-55 to +150	$^{\circ}C$
$T_{STG}$	Storage Temperature	-55 to +150	$^{\circ}C$




## Electrical Characteristics @ 25°C Unless Otherwise Specified

Symbol	Parameter	Min	Typ	Max	Units
$V_F$	Forward Voltage ( $I_F=100mA$ ) ( $I_F=200mA$ )	---	---	1.00 1.25	V
$I_R$	Leakage Current ( $V_R=100V$ ) ( $V_R=100V, T_j=100^{\circ}C$ ) ( $V_R=150V$ ) ( $V_R=150V, T_j=100^{\circ}C$ ) ( $V_R=200V$ ) ( $V_R=200V, T_j=100^{\circ}C$ )	---	---	100 15 100 15 100 15	nA uA nA uA nA uA
$r_f$	Dynamic Forward Resistance ( $I_F=10mA$ )	---	5.0	---	OHM
$C_{tot}$	Capacitance ( $V_R=0, f=1.0MHz$ )	---	1.5	---	pF
$t_{rr}$	Reverse Recovery Time ( $I_F=30mA, I_R=30mA$ ) ( $I_{rr}=3.0mA, R_L=100OHMS$ )	---	---	50	ns

- Note: 1. Lead in Glass Exemption Applied, see EU Directive Annex 5.  
2. Valid provided that leads are kept at ambient temperature at a distance of 8mm from case.


DIM	DIMENSIONS				NOTE
	INCHES		MM		
	MIN	MAX	MIN	MAX	
A	---	.166	---	4.2	
B	---	.079	---	2.00	
C	---	.020	---	.52	
D	1.000	---	25.40	---	

**Forward characteristics**




**Admissible forward current versus ambient temperature**

Valid provided that electrodes are kept at ambient temperature




**Admissible power dissipation versus ambient temperature**

Valid provided that electrodes are kept at ambient temperature




**Leakage current versus junction temperature**




# BAV19 thru BAV21

Dynamic forward resistance versus forward current



Capacitance versus reverse voltage



**Ordering Information :**

Device	Packing
Part Number-TP	Tape&Reel: 10Kpcs/Reel
Part Number-AP	Ammo Packing: 5Kpcs/Ammo Box
Part Number-BP	Bulk: 100Kpcs/Carton

**\*\*\*IMPORTANT NOTICE\*\*\***

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp .** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp .** and all the companies whose products are represented on our website, harmless against all damages.

**\*\*\*LIFE SUPPORT\*\*\***

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

**\*\*\*CUSTOMER AWARENESS\*\*\***

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.