

Am25LS2521

Eight-Bit Equal-to Comparator

DISTINCTIVE CHARACTERISTICS

- 8-bit byte oriented equal comparator
- Cascadable using \bar{E}_{IN}
- High-speed, Low-Power Schottky technology
- $t_{pd} A \cdot B$ to \bar{E}_{OUT} in 9ns
- Standard 20-pin package


GENERAL DESCRIPTION

The Am25LS2521 is an 8-bit "equal to" comparator capable of comparing two 8-bit words for "equal to" with provision for expansion or external enabling. The matching of the two 8-bit inputs plus a logic LOW on the \bar{E}_{IN} produces an active LOW on the output \bar{E}_{OUT} .

The logic expression for the device can be expressed as:
 $\bar{E}_{OUT} = (\bar{A}_0 \odot \bar{B}_0) (\bar{A}_1 \odot \bar{B}_1) (\bar{A}_2 \odot \bar{B}_2) (\bar{A}_3 \odot \bar{B}_3) (\bar{A}_4 \odot \bar{B}_4)$

$(\bar{A}_5 \odot \bar{B}_5) (\bar{A}_6 \odot \bar{B}_6) (\bar{A}_7 \odot \bar{B}_7) \bar{E}_{IN}$. It is obvious that the expression is valid where $A_0 - A_7$ and $B_0 - B_7$ are expressed as either assertions or negations. This is also true for pair of terms i.e. A_0 can be compared with B_0 at the same time \bar{A}_1 is compared with \bar{B}_1 . It is only essential that the polarity of the paired terms be maintained.

BLOCK DIAGRAM





BD001390

RELATED PRODUCTS


Part No.	Description
Am29806	Chip Select Decoder
Am29809	9-Bit Comparator

CONNECTION DIAGRAM Top View




Note: Pin 1 is marked for orientation

LOGIC SYMBOL



METALLIZATION AND PAD LAYOUT



ORDERING INFORMATION

AMD products are available in several packages and operating ranges. The order number is formed by a combination of the following: Device number, speed option (if applicable), package type, operating range and screening option (if desired).

Am25LS2521

D

C

B

Screening Option
Blank - Standard processing
B - Burn-in

Temperature (See Operating Range)
C - Commercial (0°C to +70°C)
M - Military (-55°C to +125°C)

Package
D - 20-pin Cerdip
F - 20-pin flatpak
L - 20-pin leadless chip carrier
P - 20-pin plastic DIP
X - Dice

Device type
8-Bit Equal-to-Comparator

Valid Combinations

Am25LS2521	PC DC, DM FM LC, LM XC, XM
------------	--


Valid Combinations

Consult the AMD sales office in your area to determine if a device is currently available in the combination you wish.

PIN DESCRIPTION

Pin No.	Name	I/O	Description
	A ₀ -A ₇	I	A input to comparator.
	B ₀ -B ₇	I	B input to comparator.
1	\overline{E}_{IN}	I	Enable active LOW.
19	\overline{E}_{OUT}	O	\overline{E}_{EQUAL} output active LOW.

APPLICATION



AF000651

**MAX, \overline{E}_{ENABLE} (HIGH-to-LOW) DELAY
OVER 16-BITS
(Commercial Range)**

t _{PHL}	A _i or B _i to \overline{E}_{OUT}	19ns
t _{PHL}	\overline{E}_{IN} to \overline{E}_{OUT}	12.5ns
Total		31.5ns

Note: This part does not have internal pull up resistors. In this application external pull ups should be added to the 16 ports.

**MICROPROCESSOR ENABLE CONTROLLED,
SELECTABLE, ADDRESS DECODER**

ABSOLUTE MAXIMUM RATINGS

Storage Temperature -65°C to +150°C
 (Ambient) Temperature Under Bias -55°C to +125°C
 Supply Voltage to Ground Potential
 Continuous -0.5V to +7.0V
 DC Voltage Applied to Outputs For
 High Output State -0.5V to +V_{CC} max
 DC Input Voltage -0.5V to +7.0V
 DC Output Current, Into Outputs 30mA
 DC Input Current -30mA to +5.0mA

Stresses above those listed under ABSOLUTE MAXIMUM RATINGS may cause permanent device failure. Functionality at or above these limits is not implied. Exposure to absolute maximum ratings for extended periods may affect device reliability.

OPERATING RANGES**Commercial (C) Devices**

Temperature 0°C to +70°C
 Supply Voltage +4.75V to +5.25V

Military (M) Devices

Temperature -55°C to +125°C
 Supply Voltage +4.5V to +5.5V
Operating ranges define those limits over which the functionality of the device is guaranteed.

DC CHARACTERISTICS over operating range unless otherwise specified

Parameters	Description	Test Conditions (Note 2)	Min	Typ (Note 1)	Max	Units
V _{OH}	Output HIGH Voltage	V _{CC} = MIN V _{IN} = V _{IH} or V _{IL} I _{OH} = -440μA	MIL 2.5 COM'L 2.7			Volts
V _{OL}	Output LOW Voltage	V _{CC} = MIN V _{IN} = V _{IH} or V _{IL}	I _{OL} = 4.0 mA I _{OL} = 8.0mA I _{OL} = 12mA		0.4 0.45 0.5	Volts
V _{IH}	Input HIGH Level	Guaranteed input logical HIGH voltage for all inputs	2.0			Volts
V _{IL}	Input LOW Level	Guaranteed input logical LOW voltage for all inputs.	MIL COM'L		0.7 0.8	Volts
V _I	Input Clamp Voltage	V _{CC} = MIN, I _{IN} = -18mA			-1.5	Volts
I _{IL}	Input LOW Current	V _{CC} = MAX, V _{IN} = 0.4V	A _I , B _I E		-0.36 -0.72	mA
I _{IH}	Input HIGH Current	V _{CC} = MAX, V _{IN} = 2.7V	A _I , B _I E		20 40	μA
I _I	Input HIGH Current	V _{CC} = MAX, V _{IN} = 7.0V	A _I , B _I E		0.1 0.2	mA
I _{SC}	Output Short Circuit Current (Note 3)	V _{CC} = MAX	-15		-85	mA
I _{CC}	Power Supply Current (Note 4)	V _{CC} = MAX		27	40	mA

- Notes: 1. Typical limits are at V_{CC} = 5.0V, 25°C ambient and maximum loading.
 2. For conditions shown as MIN or MAX, use the appropriate value specified under Operating Ranges for the applicable device type.
 3. Not more than one output should be shorted at a time. Duration of the short circuit test should not exceed one second.
 4. E = GND, all other inputs and outputs open.

SWITCHING CHARACTERISTICS ($T_A = +25^\circ\text{C}$, $V_{CC} = 5.0\text{V}$)


Parameters	Description	Test Conditions	Min	Typ	Max	Units
t _{PLH}	A _i or B _i to $\overline{\text{Equal}}$	C _L = 15pF R _L = 2.0kΩ		9	15	ns
t _{PHL}				9	15	
t _{PLH}	$\overline{\text{E}}$ to $\overline{\text{Equal}}$			5	7	ns
t _{PHL}				6	8	

SWITCHING CHARACTERISTICS over operating range unless otherwise specified*

Parameters	Description	Test Conditions	COMMERCIAL		MILITARY		Units
			Am25LS2521		Am25LS2521		
			Min	Max	Min	Max	
tPLH	A _i or B _i to	C _L = 50pF R _L = 2.0kΩ		20		22	ns
tPHL	Equal Output			19		21	
tPLH	E to Equal Output			10.5		12	ns
tPHL				12.5		15	

*AC performance over the operating temperature range is guaranteed by testing defined in Group A, Subgroup 9.

Am25LS2521
LOW-POWER SCHOTTKY INPUT/OUTPUT
CURRENT INTERFACE CONDITIONS



IC000180

Note: Actual current flow direction shown.