



T1³/₄ (5mm) PC BOARD LEDs

DIFFUSED, CLEAR & WATER CLEAR

PART NO: **PCT200 TR5-**

MODEL	LENS, COLOR, BRIGHT	LED COLOR	LED SPECS USED	ELECTRO-OPTICAL CHARACTERISTICS T _a =25°C I _r =100µA(MAX)				FEATURES
				I _f typ	I _v med min/typ	V _f typ/max	λ P nm	
T1-3/4 (5mm) RT. ANGLE & VERTICAL DIFFUSED INDICATOR PCB LEDs								
PC190	TR1	STD RED	L200TR1	20	0.6/1.5	1.7/2.2	655	STD PRODUCT
PC200	TR5 (A)	H-EFF RED	L200TR5A	20	12/38	2.0/2.8	635	LEAVE BLANK
PCT190	TR6	ULTRA RED	L200TR6A	20	19/60	1.8/2.4	660	SI- SNAP IN
PCT200	T05 (A)	ORANGE	L200T05A	20	16/24	2.2/2.5	610	OS-OFFSET LEADS
PCV190	TY3K	3Kmed YELLOW	L200TY3K	20	130/400	1.9/2.8	590	140=LEADS CUT .140 UNDER CASE
PCV200	TY5 (A)	AMBER YELLOW	L200TY5A	20	8/25	2.1/2.8	585	PLASTIC CASE
PCT220	TY5	TIME YELLOW	L200TY5S	20	30/45	2.1/2.5	570	50-STAND OFF
PCT230	TC5 (A)	H-EFF GREEN	L200TC5A	20	8/25	2.1/2.8	565	
PCT240	TPG5 (A)	PURE GREEN	L200TPG5A	20	8/12	2.2/2.5	555	
	IB4	BLUE	L200IB4	20	4/8	2.9/3.7	470	

T1-3/4 (5mm) RT. ANGLE & VERTICAL CLEAR ILLUMINATOR PCB LEDs								
PC190	CWR6	ULTRA RED	L200CWR6	20	80/160	1.7/2.0	660	STD PRODUCT
PC200	CWR5 (A)	H-EFF RED	L200CWR5A	20	10/40	2.2/3.0	635	LEAVE BLANK
PCT190	CR5 (A)	H-EFF RED	L200CR5A	20	10/40	2.0/2.8	635	SI- SNAP IN
PCT200	CW05 (A)	ORANGE	L200CW05A	20	60/90	2.2/2.5	610	OS-OFFSET LEADS
PCV190	CWY3K	3Kmed YELLOW	L200CWY3K	20	850/2500	1.9/2.6	590	140=LEADS CUT .140 UNDER CASE
PCV200	CWY5 (A)	AMBER YELLOW	L200CWY5A	20	80/160	2.2/3.0	585	PLASTIC CASE
PCT220	CY5 (A)	AMBER YELLOW	L200CY5A	20	10/40	2.1/2.8	585	50-STAND OFF
PCT250	CWY5S	TIME YELLOW	L200CWY5S	20	80/160	2.1/2.5	570	
PCT240	CWG6	ULTRA GREEN	L200CWG6	20	320/700	2.1/2.8	565	
	CWC5 (A)	H-EFF GREEN	L200CWC5A	20	80/120	2.1/2.8	565	
	CC5 (A)	H-EFF GREEN	L200CC5A	20	10/40	2.1/2.8	565	
	CWPG5(A)	PURE GREEN	L200CWPG5A	20	50/80	2.1/2.5	555	
	CPC6S	PURE GREEN	L200CPC6S	20	100/150	2.1/2.8	555	
	CWB5	BLUE	L200CWB5	20	15/25	3.2/3.7	470	

SPECIALS:

- 5V & 12V INTEGRATED RESISTOR LEDS
- BLINKING/FLASHING LEDS
- LOW CURRENT 2mA LEDS
- BICOLOR/TRICOLOR LEDS
- (6-CHIP) WIDE ANGLE ILLUMINATORS
- SURFACE MOUNT PCBs W/HI-TEMP CASE
- INFRARED LEDS
- MULTIPLE LED ARRAYS

TX5A & CX5A DIRECTLY REPLACES TX5 & CX5

MECHANICAL SPECIFICATIONS

MODEL	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)
PC190	.248" (6.30)	.248" (6.30)	.500" (12.7)	.100" (2.54)	.020" (0.51)	.135" (3.43)	.248" (6.30)	.200" (5.08)
PC200	.248" (6.30)	.248" (6.30)	.500" (12.7)	.100" (2.54)	.020" (0.51)	.190" (4.83)	.248" (6.30)	.200" (5.08)
PCT190	.248" (6.30)	.248" (6.30)	.500" (12.7)	.100" (2.54)	.020" (0.51)	.135" (3.43)	.355" (9.02)	.200" (5.08)
PCT200	.248" (6.230)	.248" (6.30)	.500" (12.7)	.100" (2.54)	.020" (0.51)	.187" (4.75)	.355" (9.02)	.200" (5.08)
PCV190	.248" (6.30)	.248" (6.30)	.500" (12.7)	.100" (2.54)	.020" (0.51)	.135" (3.43)	.248" (6.30)	
PCV200	.248" (6.30)	.248" (6.30)	.500" (12.7)	.100" (2.54)	.020" (0.51)	.190" (4.83)	.248" (6.30)	
PCT220	.324" (8.23)	.245" (6.22)	.500" (12.7)	.100" (2.54)	.020" (0.51)	.214" (5.44)	.356" (9.04)	.211" (5.36)
PCT250	.430" (10.92)	.245" (6.22)	.500" (12.7)	.100" (2.54)	.020" (0.51)	.210" (5.33)	.360" (9.14)	.200" (5.08)
PCT240	.520" (13.20)	.300" (7.62)	.500" (12.7)	.100" (2.54)	.020" (0.51)	.230" (5.84)	.470" (11.94)	.300" (7.62)

