

DTC143Z


NPN SILICON TRANSISTOR

NPN DIGITAL TRANSISTOR
(BUILT-IN RESISTORS)

■ FEATURES

- * Built-in bias resistors that implies easy ON/OFF applications.
- * The bias resistors are thin-film resistors with complete isolation to allow negative input.

■ EQUIVALENT CIRCUIT



■ ORDERING INFORMATION

Order Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
DTC143ZL-AE3-R	DTC143ZG-AE3-R	SOT-23	G	I	O	Tape Reel
DTC143ZL-AL3-R	DTC143ZG-AL3-R	SOT-323	G	I	O	Tape Reel
DTC143ZL-AN3-R	DTC143ZG-AN3-R	SOT-523	G	I	O	Tape Reel
DTC143ZL-T92-B	DTC143ZG-T92-B	TO-92	G	O	I	Tape Box
DTC143ZL-T92-K	DTC143ZG-T92-K	TO-92	G	O	I	Bulk
DTC143ZL-T9S-K	DTC143ZG-T9S-K	TO-92SP	G	O	I	Bulk

 DTC143ZL-AE3-R	(1) B: Tape Box, K: Bulk, R: Tape Reel (2) AE3: SOT-23, AL3: SOT-323, AN3: SOT-523, T92: TO-92, T9S: TO-92SP (3) G: Halogen Free, L: Lead Free
--------------------	---

■ MARKING

SOT-23	SOT-323/SOT-523
 CE3Z	 CE3Z

■ ABSOLUTE MAXIMUM RATINGS ($T_a = 25^\circ\text{C}$)

PARAMETER		SYMBOL	RATINGS	UNIT
Supply Voltage		V_{CC}	50	V
Input Voltage		V_{IN}	-5 ~ +30	V
Output Current	SOT-523	I_{OUT}	100	mA
	SOT-23/SOT-323	I_C (MAX)	100	
Power Dissipation	TO-92/TO-92SP	P_D	150 200 300	mW mW mW
			+150	°C
			-55 ~ +150	°C
Junction Temperature		T_J		
Storage Temperature		T_{STG}		

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.





Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ ELECTRICAL CHARACTERISTICS ($T_a = 25^\circ\text{C}$)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Input Voltage	V_{IN} (OFF)	$V_{CC}=5\text{V}$, $I_{OUT}=100\mu\text{A}$			0.5	V
	V_{IN} (ON)	$V_{OUT}=0.3\text{V}$, $I_{OUT}=5\text{mA}$	1.3			
Output Voltage	V_{OUT} (ON)	$I_{OUT}/I_{IN}=5\text{mA}/0.25\text{mA}$		0.1	0.3	V
Input Current	I_{IN}	$V_{IN}=5\text{V}$			1.8	mA
Output Current	I_O (OFF)	$V_{CC}=50\text{V}$, $V_{IN}=0\text{V}$			0.5	μA
DC Current Gain	h_{FE}	$V_{OUT}=5\text{V}$, $I_{OUT}=10\text{mA}$	80			
Input Resistance	R_1		3.29	4.7	6.11	KΩ
Resistance Ratio	R_2/R_1		8	10	12	
Transition Frequency	f_T	$V_{CE}=10\text{V}$, $I_E=-5\text{mA}$, $f=100\text{MHz}$ *		250		MHz

* Transition frequency of the device

■ TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.