



FEATURES

DIRECTLY REPLACES STANDARD INCANDESCENTS

- LONG LIFE, 100,000 HOURS
- HIGH SHOCK / VIBRATION RESISTANCE SOLID STATE
- BUILT-IN RESISTOR FOR DIRECT 6V TO 130 VAC / DC
- POWER SAVINGS UP TO 500%
- IDEAL FOR MARKER LIGHTS, LARGE MOVING DISPLAYS, SIGNS, PILOT LIGHTS & AUTOMOTIVE LIGHTS...

REPLACES FOLLOWING INCANDESCENTS

PART NO:

S624 CW6-28V/30-P

MODEL #	LENS/COLOR/BRIGHT	VOLTS/mAmps Typ	POLARITY
MULTICHIP (24-CHIP) S624 (MOL 1.38) SM624 (MOL 1.75) SL624 (MOL 2.20)	CR3K,CR7,CR6,CO6, CY6,CLY6,CG6,CPG6, CB6,CW6	S/SM/SL624: 16Vf/50,24Vf/30,48Vf/15= EXT. RES. REQD. 24V/50,28V/30,36V/30,48V/30, 60V/15,72V/15,120VAC/15...	CENTER CONTACT: SAME AS BELOW
CLUSTERS 6-7 LEDs (15mm) S606/607 (MOL 1.38) SM606/607 (MOL 1.75) SL606/607 (MOL 2.20)	CR5K,CR3K, CR900,CR6,CR5,CR3, CO5,CY5,CY3,CLY5, CG5,CG3,CPG5,CB5, CW5 INFRARED CLUSTERS: CIR850 (850nm) CIR880 (880nm) CIR940 (940nm)	S/SM/SL606: 4Vf/90,6Vf/60=EXT. RES. REQD. 5V/90,6V/90,12V/60 S/SM/SL607: 14Vf/30=EXT. RES. REQD. 18V/30,24V/30,28V/30,36V/30, 48V/20,60V/20,120VAC/10...	CENTER CONTACT: P = POS. + N = NEG. - BP = BIPOLAR NR = NO RES. AC = VAC
CLUSTERS 8-9 LEDs (15mm) S608/609 (MOL 1.38) SM608/609 (MOL 1.75) SL608/609 (MOL 2.20)	CR5K,CR3K, CR900,CR6,CR5,CR3, CO5,CY5,CY3,CLY5, CG5,CG3,CPG5,CB5, CW5 INFRARED CLUSTERS: CIR850 (850nm) CIR880 (880nm) CIR940 (940nm)	S/SM/SL608: 4Vf/120,8Vf/60=EXT. RES. REQD. 5V/120,6V/120,12V/60 S/SM/SL609: 18Vf/30=EXT. RES. REQD. 24V/30,28V/30,36V/30,48V/20, 60V/20,120VAC/10...	CENTER CONTACT: P = POS. + N = NEG. - BP = BIPOLAR NR = NO RES. AC = VAC
CLUSTERS 18-19 LEDs (15mm) S618/619 (MOL 1.38) SM618/619 (MOL 1.75) SL618/619 (MOL 2.20)	CR5K,CR3K, CR900,CR6,CR5,CR3, CO5,CY5,CY3,CLY5, CG5,CG3,CPG5,CB5, CW5 INFRARED CLUSTERS: CIR850 (850nm) CIR880 (880nm) CIR940 (940nm)	S/SM/SL618: 18Vf/60=EXT. RES. REQD. 24V/60,28V/60,36V/40 S/SM/SL619: 38Vf/30=EXT. RES. REQD. 48V/20,60V/20,72V/20, 120VAC/10...	CENTER CONTACT: P = POS. + N = NEG. - BP = BIPOLAR NR = NO RES. AC = VAC
CLUSTERS 40 LEDs (15mm) S640 (MOL 1.38) SM640 (MOL 1.75) SL640 (MOL 2.20)	CR5K,CR3K, CR900,CR6,CR5,CR3, CO5,CY5,CY3,CLY5, CG5,CG3,CPG5,CB5, CW5 INFRARED CLUSTERS: CIR850 (850nm) CIR880 (880nm) CIR940 (940nm)	S/SM/SL640: 20Vf/120,40Vf/60,80Vf/30= EXT. RES. REQD. 24V/120,28V/120,36V/80,48V/80, 60V/80,72V/80,120VAC/20...	CENTER CONTACT: P = POS. + N = NEG. - BP = BIPOLAR NR = NO RES. AC = VAC

SPECIALS:

- FLASHING/BLINKING MULTI-LED CLUSTERS
- BICOLOR MULTI-LED CLUSTERS
- DUAL CHIP LEDs IN MULTI-LED CLUSTERS
- INFRARED 850, 880 & 940nm
- MULTI-LED 360° CLUSTERS
- CUSTOM LED CLUSTERS

LENS TYPE: C=CLEAR
 COLOR CODES: R=RED, O=ORANGE, A=AMBER YELLOW, LY=LIME YELLOW, G=GREEN,
 PG=PURE GREEN, B=BLUE, W=WHITE (RED/GREEN)

BRIGHTNESS CODES: 900=900mcd WIDE RED, 3K=3KmcNARROW RED, 5K=5KmcNARROW RED,
 7=HI ULTRA RED ONLY, 6=ULTRA, 5=SUPER BRIGHT, 3/4= HI EFFICIENCY.

NOTE: WHEN PLACING ORDERS OR REQUESTING SAMPLES, PLEASE INDICATE INCANDESCENT LAMP
 NUMBER BEING REPLACED. WHEN SELECTING THE LED COLOR, MATCH EXISTING LENS COLOR TO
 LED COLOR.

