

GLASS PASSIVATED BRIDGE RECTIFIERS

REVERSE VOLTAGE - **400 to 800** Volts
FORWARD CURRENT - **20** Amperes


FEATURES

- Rating to 800V PRV
- Ideal for printed circuit board
- Low forward voltage drop, high current capability.
- Reliable low cost construction utilizing molded plastic technique results in inexpensive product
- The plastic material has UL flammability classification 94V-0
- UL Recognition File # E95060

MECHANICAL DATA

- Polarity : Symbols molded on body
- Weight : 0.16 ounces, 4.6 grams
- Mounting position : Any

KBJ



KBJ		
DIM.	MIN.	MAX.
A	24.80	25.20
B	14.70	15.30
C	3.90	4.10
D	4.40	4.80
E	3.40	3.80
F	3.10 \varnothing	3.40 \varnothing
G	3.30	3.70
H	0.90	1.10
I	1.50	1.90
J	17.2	17.80
K	7.30	7.70
L	2.50	2.90
M	0.60	0.80
N	9.30	9.70
O	3.0 x 45°	
Q	1.05	1.45
R	1.70	2.10

All Dimensions in millimeter

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25°C ambient temperature unless otherwise specified.

CHARACTERISTICS	SYMBOL	KBJ2004G	KBJ2006G	KBJ2008G	UNIT
Maximum Recurrent Peak Reverse Voltage	V _{RRM}	400	600	800	V
Maximum RMS Voltage	V _{RMS}	280	420	560	V
Maximum DC Blocking Voltage	V _{DC}	400	600	800	V
Maximum Average Forward (with heatsink Note 2) Rectified Current @T _c =110°C (without heatsink)	I _(AV)		20.0 3.0		A
Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I _{FSM}		200		A
Maximum forward Voltage at 10.0A DC	V _F		1.1		V
Maximum DC Reverse Current @T _J =25°C at Rated DC Blocking Voltage @T _J =125°C	I _R		10 500		uA
I ² t Rating for fusing (t < 8.3ms)	I ² t		166		A ² S
Typical Junction Capacitance per element (Note 1)	C _J		70		pF
Typical Thermal Resistance (Note 2)	R _{θJC}		0.8		°C/W
Operating Temperature Range	T _J		-55 to +150		°C
Storage Temperature Range	T _{STG}		-55 to +150		°C

NOTES : 1.Measured at 1.0MHz and applied reverse voltage of 4.0V DC.

2.Device mounted on 250mm x 250mm x 20mm Alumunin Plate Heatsink, Ta=25°C .

REV. 2, Sep-2010, KBDF07

FIG.1 - FORWARD CURRENT DERATING CURVE




FIG.2 - MAXIMUM NON-REPETITIVE SURGE CURRENT




FIG.3 - TYPICAL JUNCTION CAPACITANCE




FIG.4 - TYPICAL FORWARD CHARACTERISTICS





FIG.5 - TYPICAL REVERSE CHARACTERISTICS



Important Notice and Disclaimer

LSC reserves the right to make changes to this document and its products and specifications at any time without notice. Customers should obtain and confirm the latest product information and specifications before final design, purchase or use.

LSC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does LSC assume any liability for application assistance or customer product design. LSC does not warrant or accept any liability with products which are purchased or used for any unintended or unauthorized application.

No license is granted by implication or otherwise under any intellectual property rights of LSC.

LSC products are not authorized for use as critical components in life support devices or systems without express written approval of LSC.