


## Typical Applications

PCS Base Stations  
 Land Mobile Radio  
 Cellular Telephony  
 Radio in the Local Loop

## Features

Wide Frequency range  
 EFC Standard  
 Standard Surface Mount Package  
 Meets Stratum 3



## Previous Corning Model Numbers

STO200

## Frequency range

30 MHz – 900 MHz

## Standard frequencies

67.584; 69.12; 79.488; 155.52, 242.733, 278.08 MHz

## Frequency stabilities<sup>1</sup> [ Standard TCXO]

Parameter	Min	Typ	Max.	Units	Operating temp range	Ordering Code <sup>5</sup>
vs. operating temperature range (Referenced to +25°C)	-2.0		+2.0	ppm	-20 ... +70°C	D206
	-1.0		+1.0	ppm	-20 ... +70°C	D106
	-1.0		+1.0	ppm	0 ... +50°C	B106
	-0.5		+0.5	ppm	0 ... +50°C	B507
Parameter	Min	Typ	Max.	Units	Condition	
Initial tolerance	- 1.0		+1.0	ppm	at time of shipment, nominal EFC	
vs. supply voltage change	- 0.2		+0.2	ppm	V <sub>S</sub> ± 5%	
vs. load change	- 0.2		+0.2	ppm	Load ± 10%	
vs aging /1. Year	- 1.0		+1.0	ppm		

## Frequency stabilities<sup>1</sup> [ Stratum 3 TCXO]

Parameter	Min	Typ	Max.	Units	Operating temp range	Ordering Code <sup>5</sup>
vs. operating temperature range (Referenced to +25°C)	-0.8		+0.8	ppm	-40 ... +85°C	F807
	-0.28		+0.28	ppm	-30 ... +85°C	G287
	-0.8		+0.8	ppm	-20 ... +70°C	D807
	-0.28		+0.28	ppm	-20 ... +70°C	D287
	-0.28		+0.28	ppm	0 ... +50°C	B287
Parameter	Min	Typ	Max.	Units	Condition	
Initial tolerance	- 1.0		+1.0	ppm	at time of shipment, nominal EFC	
vs. supply voltage change	- 0.2		+0.2	ppm	V <sub>S</sub> ± 5%	
vs. load change	- 0.1		+0.1	ppm	Load ± 10%	
vs aging /15 Years	- 2.5		+2.5	ppm		
overall tolerance	-4.6		-4.6	ppm		
(*Stratum 3 per GR-1244-CORE: <±4.6 ppm for all causes and 20 years aging, Holdover: <±0.37 ppm over 24 hours (Code: D287 & B287)						

## Supply voltage (Vs)

Parameter	Min	Typ	Max.	Units	Condition	Ordering Code <sup>5</sup>
Supply voltage [Standard]	3.135	3.3	3.465	VDC		SV033
Current consumption (Freq < 100MHz)			50	mA	steady state @ +25°C & 3.3VDC & CMOS	
			90	mA	steady state @ +25°C & 3.3VDC & PECL	

## RF output

Parameter	Min	Typ	Max.	Units	Condition	Ordering Code <sup>5</sup>
Signal [Standard]	HCMOS					RFH
Load	13.5	16.5		pF	with Vs=3.3V and 15pF load with Vs=3.3V and 15pF load  @ (Voh-Vol)/2	
Signal Level (Vol)			0.3	VDC		
Signal Level (Voh)	3.0			VDC		
Rise and Fall time			5	ns		
Duty cycle	40	50	60	%		
Subharmonics	-45			dBc		
Signal [Standard]	PECL					RFP
Load		50		Ω	to Vs-2V 20 to 80%	
Rise and Fall time			1	ns		
Duty cycle	45	50	55	%		
Subharmonics	-45			dBc		

## Frequency Tuning (EFC)



Parameter	Min	Typ	Max.	Units	Condition
Tuning Range	± 8.0	±14.0	± 20.0	ppm	Standard Version
Tuning Range	± 5.0	±12.0	± 20.0	ppm	Stratum 3 Version
Linearity			10	%	
Tuning Slope	Positive				
Control Voltage Range	0.3	1.65	3.0	VDC	with Vs=3.3VDC
Freq. control input impedance	10			kΩ	

## Additional parameters


Parameter	Min	Typ	Max.	Units	Condition	
Phase Noise <sup>3</sup>		-70		dBc/Hz	10 Hz	Standard TCXO @ 79.483 MHz
		-100		dBc/Hz	100 Hz	
		-120		dBc/Hz	1 kHz	
		-128		dBc/Hz	10 kHz	
		-135		dBc/Hz	100 kHz	
Phase Noise <sup>3</sup>		-60		dBc/Hz	10 Hz	Stratum3 TCXO @ 155.52MHz
		-96		dBc/Hz	100 Hz	
		-115		dBc/Hz	1 kHz	
		-122		dBc/Hz	10 kHz	
		-129		dBc/Hz	100 kHz	
Weight			9	g		
Processing & Packing	Handling & processing note					

## Absolute Maximum Ratings


Parameter	Min	Typ	Max.	Units	Condition
Supply voltage (Vs)			6.0	V	
Control Voltage	0		Vs	V	
Maximum output load @ CMOS			40	pF	
Operable temperature range	-40		+85	°C	
Storage temperature range	-55		+125	°C	

Type G185B				Type G185B (PECL)			
Package Codes :				Package Codes :			
Code A1	Height "H" 7.0	Pin Length "L" NA		Code B1	Height "H" 7.0	Pin Length "L" NA	
							
Pin Connections				Pin Connections			
1 Voltage Control 2 I.C 3 Vs (supply voltage) 4 RF-Output 5 I.C. 6 I.C. 7 GND				1 Vs (supply voltage) 2 I.C 3 GND 4 I.C. 5 RF-Output 6 RF-Output compl. 7 GND			

## Typical measurement data




**Standard Shipping Method**



Production tolerance complying DIN IEC 286-3

Enclosure Type	Tape width W [mm]	Quantity per meter	Quantity per reel	Dimension P
G185B	44	37.5	230	32

**Recommended Reflow Profile**



Profile Feature	Pb-Free Assembly /Sn-Pb Assembly	Profile Feature	Pb-Free Assembly /Sn-Pb Assembly
Average ramp-up rate ( $T_L$ to $T_p$ )	3°C/second max.	Time 25°C to Peak Temperature	8 minutes max.
Preheat -Temperature Min $T_{S_{min}}$ -Temperature Min $T_{S_{max}}$ -Time (min to max) (ts)	150°C 200°C 60-180 seconds	Time maintained above - Temperature ( $T_L$ ) - Time ( $t_L$ )	217°C 60-150 seconds
$T_{S_{max}}$ to $T_L$ - Ramp-up Rate	3°C/second max.		
Time maintained above - Temperature ( $T_L$ ) - Time ( $t_L$ )	217°C 60-150 seconds	Time within 5°C of actual Peak Temperature ( $t_p$ )	20-40 seconds
Peak Temperature ( $T_p$ )	max 260°C	Ramp-down Rate	6°C/second max.

Note: All temperatures refer to topside of the package, measured on the package body surface.

## How to order this product:

Model	Stability Code	Supply Voltage Code	RF Output Code	Package Code	Frequency
C2530	D206	SV033	RFH	A1	30MHz

↓	↓	↓	↓
<b>Vs.operat. Temp. Range</b>	<b>Supply:</b>	<b>Signal:</b>	<b>Enclosure:</b>
D206 ±2.0ppm -20 ... +70°C	SV033: 3.3V	RFP: PECL	A1: G185B
D106 ±1.0ppm -20 ... +70°C		RFH: HCMOS	B1: G185B
B106 ±1.0ppm 0 ... +50°C			
B507 ±0.5ppm 0 ... +50°C			
F807 ±0.8ppm -40 ... +85°C			
B287 ±0.28ppm 0 ... +50°C			
G287 ±0.28ppm -30 ... +85°C			
D807 ±0.8ppm -20 ... +70°C			
D287 ±0.28ppm -20 ... +70°C			

### Notes:

- 1 Contact factory for improved stabilities or additional product options. Not all options and codes are available at all frequencies.
- 2 Unless otherwise stated all values are valid after warm-up time and refer to typical conditions for supply voltage, frequency control voltage, load, temperature (25°C)
- 3 Phase noise degrades with increasing output frequency.
- 4 Subject to technical modification.
- 5 Contact factory for availability.