



※Please refer to page 145 about recommended tightening torque and permissible current of terminal.

**◆STANDARD SIZE**

Cap(μF)	350V		400V		450V		500V	
	WV(V.DC)							
1200					51×98	6.5	51×98	5.6
1500			51×98	6.9	51×118	7.4	51×118	6.3
1800	51×98	7.8	51×118	7.7	51×138	8.3	51×148	7.1
2200	51×118	8.7	51×138	8.6	64×119	10.1	64×119	8.5
2700	51×138	9.8	51×148	9.5	64×139	11.3	64×139	9.6
3300	51×148	10.8	64×119	11.5	64×149	12.5	64×149	10.5
3400			77×126	10.4				
3900	64×119	12.9	64×139	12.7	77×121	15.3	77×131	13.3
4700	64×139	14.3	64×149	13.8	77×141	17.0	77×151	14.8
			77×121	15.8	90×121	18.1	90×121	17.8
5600	77×121	17.8	64×189	15.4	77×151	17.4	90×131	19.5
			77×141	17.5				
6800	64×189	17.7	77×151	19.2	77×191	19.2	77×191	18.1
	77×141	19.8	90×121	22.9	90×141	21.0	90×151	21.7
8200	77×151	21.8	77×191	21.4	90×191	25.1	90×191	24.5
	90×121	25.8	90×141	25.4				
10000	77×191	24.6	90×151	27.9	90×221	27.9	90×221	27.4
	90×141	28.8						
12000	90×191	30.6	90×191	31.5	90×241	30.0	90×241	30.1
15000	90×191	36.2	90×221	35.8				
18000	90×221	40.1	90×241	38.9				
20000			101×253	42.2				

↑ ↑  
 Case Size φD×L(mm)      Ripple Current (A r.m.s./120Hz, 85°C)