



PT08 SE SP08 SE 90 degree plug




TERMINATION ASSEMBLIES


"SE" Open Wire Seal. "SE" (SR) Strain Relief




PT08SE-XX-XXX
SP08SE-XX-XXX
PT08SE-XX-XXX (SR)
SP08SE-XX-XXX (SR)



"SP" Potting Boot 75°



PT08SP-XX-XXX
SP08SP-XX-XXX



All lockwire holes are .044 Dia. Min.

Shell Size	Plug Front View		Class "SE", "SE" (SR)				Plug Side View			
	G Dia.	B	C	D	E	L	A	H	L	K
	Max.	±.031	+0.10 -.025	±.062	+0.047 -.025	Max.	±.025	±.015	Max.	±.015
10	.921	.749	.170	1.191	.393	2.137	.547	.438	2.031	.562
12	1.046	.812	.264	1.191	.450	2.222	.625	.516	2.093	.688
14	1.171	.905	.310	1.254	.519	2.370	.734	.625	2.203	.781
16	1.297	1.030	.330	1.316	.583	2.572	.750	.656	2.250	.890
18	1.422	1.015	.444	1.562	.621	2.680	.781	.703	2.296	1.000
20	1.562	1.077	.510	1.625	.683	2.753	.859	.766	2.343	1.125
22	1.672	1.139	.515	1.719	.739	2.799	.906	.812	2.390	1.234
24	1.797	1.250	.656	1.750	.787	3.037	1.181	.918	2.624	1.374

All dimensions for reference only.